D-P-190b
FEBRUARY 25, 1958
SUPERSEDING
Int. Fed. Spec. D–P–00190a(GSA–FSS)
June 6, 1957

FEDERAL SPECIFICATION

PEN, FOUNTAIN, TEAR GAS

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. — This specification covers a miniature gun having the appearance of a regular fountain pen, and being capable through manual operation of discharging a tear-gas shell for the purpose of subduing unruly persons, and for protection of law enforcement personnel.

1.1.1 *Federal specification coverage.*—Federal specifications do not include all types and classes of the commodity indicated by the titles of the specifications, but cover only those generally used by the Federal Government.

1.2 Classification.

1.2.1 *Type and grade.*—The tear-gas pens covered by this specification shall be of one type and grade.

1.2.2 *Sizes.*—The tear-gas pens covered by this specification shall be of the following sizes and as specified in the invitation for bids, contract or order (see 6.1).

Size 0.38-inch caliber.—For 0.38-inch-caliber shell.

Size 0.405-inch caliber.—For 0.405-inch-caliber shell.

Size 0.410-inch caliber.—For 0.410-inch-caliber shell.

2. APPLICABLE SPECIFICATIONS, STANDARDS, AND OTHER PUBLICATIONS

2.1 Specifications and standards.—The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification:

Federal Specifications:

D–C–115—Cartridges, Projectiles, and Shells, Gas and Flare.

Federal Standards:

Fed. Std. No. 102—Preservation, Packaging, and Packing Levels.

(Activities outside the Federal Government may obtain copies of Federal Specifications and Standards as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, Seattle, and Washington, D. C.

(Federal Government activities may obtain copies of Federal Specifications and Standards and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

441888/58/No. 237

FSC 1010

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

2.2 Other publications.—The following publication, of the issue in effect on date of invitation for bids, forms a part of this specification.

Nongovermental:

Consolidated Freight Classification Rules and Container Specifications.

(Application for copies should be addressed to the Consolidated Classification Committee, 202 Chicago Union Station, Chicago 6, Illinois.)

3. REQUIREMENTS

3.1 Design.—The tear-gas pen shall be of the latest design, convenient to operate, and entirely adequate for the purpose intended. All parts subject to wear shall be readily accessible for adjustment or repair. It shall be capable of discharging tear-gas cartridges for the purpose of subduing unruly persons and for self-protection of law enforcement personnel.

3.2 Construction.—Construction shall be free from any characteristics or defects that may render the tear-gas pen unsuitable or inefficient for the intended purpose. The tear-gas gun shall be complete so that when operated in its intended application it shall function as required.

3.2.1 *Material.*—Unless otherwise specified, the material shall be a corrosive-resistant metal of such composition that no permanent deformation shall result from continuous application of its intended use.

3.2.2 *Safety devices.*—Each tear-gas pen shall be furnished with suitable safety devices of the latest type. Parts which are hazardous to the operator shall be suitably guarded where practicable.

3.2.3 *Interchangeability.*—All replaceable parts shall be manufactured to definite standards, tolerances, and clearances in order that any such part of a particular type or model may be replaced or adjusted without requiring modification.

3.3 Performance.—The pen shall efficiently receive and discharge 0.38-inch, 0.405-inch and 0.410-inch shells as specified in Federal Specification D–C–115. The discharge from these shells shall be blasted or sprayed and accurately guided to a minimum distance of 10 feet.

3.4 Component units.—The tear-gas pen shall consist of a barrel, firing mechanism, container and a clip.

3.4.1 *Barrel.*—The barrel shall be suitable for holding shell with chamber bore of sufficient size and suitable finish to discharge tear-gas-agent shell of the caliber specified in the invitation to bid, contract, or order (see 6.1). The barrel shall be mechanically attached to the container which encloses fire mechanism.

3.4.1.1 *Caliber of barrel.*—The caliber of the barrel shall be as specified in the invitation to bid, contract, or order (see 6.1), as selected from the following sizes:

Size 0.38-inch caliber.—For 0.38-inch-caliber shell

Size 0.405-inch caliber.—For 0.405-inch-caliber shell

Size 0.410-inch caliber.—For 0.410-inch-caliber shell

Note.—For shell requirements see Federal Specification D–C–115.

3.4.2 *Firing mechanism, container, and clip.*—The firing mechanism shall consist of a trigger-operated device which actuates the firing pin which in turn discharges the gas-charged shell. The firing mechanism shall be enclosed in a container and mechanically attached to the barrel (see 3.4.1). The container shall be provided with a clip having a gripping action as a fountain pen clip.

3.5 Finish.—Unless otherwise specified, the external surface finish of the weapon shall be manufacturer's standard.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

3.6 Workmanship.—The pen shall be new and of quality workmanship necessary to produce a weapon of good appearance, stability, and efficient operating and productive characteristics found in first class, commercial-quality items of a similar nature.

4. SAMPLING, INSPECTION, AND TEST PROCEDURE

4.1 General. — Unless otherwise specified, the tear-gas pen and all material entering into the manufacture thereof, shall be subject to inspection by authorized Government inspectors. When inspection is conducted at the contractor's plant, all tests required by this specification and/or contract or purchase order shall be conducted by the contractor under the supervision of an authorized Government inspector. The Government inspector may at his option conduct any or all of the tests. The place of inspection and acceptance shall be as specified in the invitation for bids, contract, or purchase order (see 6.1). The contractor shall provide all the necessary facilities, instruments and equipment necessary to conduct the inspection and tests required to determine compliance with this specification, contract or purchase order.

4.2 Inspection.—Each tear-gas pen shall be given a general inspection for material, workmanship, dimensions, performance, weight, painting, marking, packaging, packing, labeling, as applicable, and general compliance with the requirements of this specification.

4.3 Tests. — The tear-gas gun shall be tested for compliance with performance requirements of this specification (see 3.3).

4.4 Retest.—Rejected pens shall not be resubmitted for inspection without furnishing full particulars concerning previous rejections and measures taken to overcome the defects.

5. PREPARATION FOR DELIVERY

(Nonmilitary agencies. — Federal Standard No. 102 should be referred to for definitions and applications of the various levels of packaging protection for supplies and equipment.)

5.1 Preservation and packaging.

5.1.1 *Level A.*—Level A preservation and packaging shall afford adequate protection against corrosion, deterioration, and physical damage during shipment, handling, intermediate storage and world-wide distribution.

5.1.2 *Level C.*—Level C preservation and packaging shall afford adequate protection against corrosion, deterioration, and physical damage during shipment from the supply source to the first receiving activity for immediate use. This level may be the supplier's commercial practice when such meets the requirements.

5.2 Packing.

5.2.1 *Level A.* — Level A packing shall afford adequate protection during shipment, handling, intermediate storage, and world-wide distribution.

5.2.2 *Level B.* — Level B packing shall afford adequate protection against multiple domestic shipment, handling and storage.

5.2.3 *Level C.* — Level C packing shall afford protection against damage during direct shipment from the supply source to the first receiving activity for immediate use. This level in general shall conform to the applicable requirements of the Consolidated Freight Classification Rules or regulations of other carriers according to the mode of transportation, and may be the supplier's commercial practice when such meets the requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

5.3 Marking.—Unless otherwise specified, shipping containers shall be marked with the name of the article, the type, class, style, if any, and the quantity contained therein, as defined by the contract or order (see 6.2).

6. NOTES

6.1 Ordering data. — Procurement documents should specify the following:

(*a*) Title, number and date of this specification.

(*b*) Caliber size (see 1.2.2).

(*c*) Color of paint and type of finish, if different (see 3.5).

(*d*) Specify place of inspection (see 4.1).

(*e*) Packaging, packing, and marking requirements, if other than specified (see section 5).

Notice. — When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Copies of this specification may be purchased for [illegible] cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.