D-R-1187/1
June 28, 1974

FEDERAL SPECIFICATION SHEET

FEDERAL SPECIFICATION

REVOLVER, CALIBER .38 SPECIAL, DOUBLE ACTION,

5 SHOT AND 6 SHOT, COMMERCIAL

This specification sheet was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

The complete requirements for procuring the revolvers described herein shall consist of this document and the latest issue of specification DD-R-1187/GEN.

1. SCOPE

1.1 Scope. This specification sheet covers commercial, 5 shot and 6 shot, double action, caliber .38 special revolvers.

2. APPLICABLE DOCUMENTS

2.1 Publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Sporting Arms and Ammunition Manufacturers Institute:

Technical Committee Manual, Volume II, Center Fire Pistol and Revolver.

(Applications for copies should be addressed to the Sporting Arms and Ammunition Manufacturers' Institute, 420 Lexington Avenue, New York, New York 10017.)

3. REQUIREMENTS

3.1 Bid samples

FSC 1005

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:05Z
Check the source to verify that this is the current version before use.

3.1.1 Unless otherwise specified (see 6.2), each bidder shall furnish the specified number of bid sample revolvers of the design he proposes to supply for test and evaluation for determination of compliance with this specification and such other characteristics as may be desired by the Government. Revolvers shall be representative of the latest commercially available design modified as necessary to meet this specification. Unless otherwise specified, bid sample revolvers shall be prepared for delivery in accordance with level C requirements and shall be forwarded to the test and evaluation agency specified in the contract. Along with the submitted bid sample, each bidder shall indicate the commercial nomenclature and model designation of the samples submitted.

3.1.2 Upon award of the contract, samples submitted by the successful bidder and approved by the evaluation and test agency will be retained for use by the contractor and the Government as inspection standards. These standards shall apply to all characteristics for which definite requirements are not prescribed.

3.2 Configuration. Unless otherwise specified (see 6.2), configuration shall be in accordance with Table 1.

3.3 Firing pin. The firing pin shall not cause pierced primers and shall protrude a sufficient distance to insure proper cartridge ignition.

3.4 Trigger pull. The trigger pull shall be within the range of 2-1/2 to 5 pounds for single action and not more than 14 pounds for double action.

3.5 Ammunition. The revolvers shall meet the requirements specified herein and in D-R-1187 (except high-pressure resistance) using 158 grain, lead bullet, inside lubricated, caliber .38 special, commercial cartridges conforming to Sporting Arms and Ammunition Manufacturers Institute (SAAMI) standards.

4. QUALITY ASSURANCE PROVISIONS

4.1 Bid sample inspection. Bid sample revolvers shall be subjected to the quality conformance inspection specified in D-R-1187 (only one revolver will be subjected to endurance test) the examination specified herein and such other inspection as is necessary to determine compliance with the requirements of the contract.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:05Z
Check the source to verify that this is the current version before use.

TABLE I

Dash #	Barrel	Cylinder Mat'l	Frame	Trigger	Front Sight	Rear Sight	Hammer	Weight (Max-Empty)
1	2" ± 1/4	5 Shot	Stainless Steel	Grooved or Smooth	Quick Draw Ramp Style	Square Notched Frame or Square Notched Bar Dovetailed Into Frame	Spur Grooved or Checkered	23 ounces
2	2" ± 1/4	5 Shot	Steel	Grooved or Smooth	Quick Draw Ramp Style	Square Notched Frame or Square Notched Bar Dovetailed Into Frame	Spur Grooved or Checkered	23 ounces
3	2" ± 1/4	6 Shot	Aluminum	Grooved or Smooth	Quick Draw Ramp Style	Square Notched Frame or Square Notched Bar Dovetailed Into Frame	Spur Grooved or Checkered	21 ounces
4	2" ± 1/4	6 Shot	Steel	Grooved or Smooth	Quick Draw Ramp Style	Square Notched Frame or Square Notched Bar Dovetailed Into Frame	Spur Grooved or Checkered	33 ounces
5	4" ± 1/4	6 Shot	Steel	Grooved	Quick Draw Ramp Style	Adjustable	Spur Grooved or Checkered	36 ounces
6	4" ± 1/4	6 Shot	Steel	Grooved or Smooth	Quick Draw Ramp Style	Square Notched Frame or Square Notched Bar Dovetailed Into Frame	Spur Grooved or Checkered	36 ounces
7	4" ± 1/4	6 Shot	Stainless Steel	Grooved or Smooth	Quick Draw Ramp Style	Adjustable	Spur Grooved or Checkered	36 ounces
8	6" ± 1/4	6 Shot	Steel	Grooved	Quick Draw Ramp Style	Adjustable	Spur Grooved or Checkered	40 ounces

Source: https://assist.dla.mil -- Downloaded: 20260-26T11:05Z
Check the source to verify that this is the current version before use.

4.2 Examination. Revolvers shall be examined in accordance with the following. Inspection lot and examination provisions of D-R-1187 apply.

Characteristic	Requirement	Inspection Method
Configuration	Table I	Visual

4.3 Testing.

4.3.1 Ammunition. All testing (except high-pressure resistance) shall be accomplished using ammunition specified in 3.5.

5. PREPARATION FOR DELIVERY

This section is not applicable to this specification.

6. NOTES

6.1 Identification number. The identification number consists of the document number plus the dash number.

Examples:

D-R-1187/1-1 2" barrel, 5 shot, stainless steel frame, grooved or smooth trigger, quick draw ramp style front sight, square notched frame rear sight, spur grooved or checkered hammer and 23 oz max-empty weight.

D-R-1187/1-6 4" barrel, 6 shot, steel frame, grooved or smooth trigger, quick draw ramp style front sight, square notched frame rear sight, spur grooved or checkered hammer and 36 oz max-empty weight.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

a. Title, number and date of this specification sheet.

b. Identification number required (see 6.1 and Table I).

c. Bid sample requirements (see 3.1).

d. Configuration, if different (see 3.2).

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:05Z
Check the source to verify that this is the current version before use.

e. Responsibilities for furnishing ammunition.

Military Custodians
Army - WC
Navy - OS
Air Force - 84

Review Activities:
Navy - OS
Air Force - 84

User Activity:
Air Force - 11

Preparing Activity:
Army - WC

Civil Agency Coordinating Activities:
JUSTICE - FPI
TREASURY - IRS
DC GOVT - DCG
GSA - FSS
DOT - FIS
POSTAL - POS
INTERIOR - GES

Project number:
1005-0482-2

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain copies and other documents referenced herein. Price 25 cents each.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:05Z
Check the source to verify that this is the current version before use.