D-R-1187/2
June 28, 1974

FEDERAL SPECIFICATION SHEET

FEDERAL SPECIFICATION

REVOLVER, CALIBER .38 SPECIAL, DOUBLE ACTION,

5 SHOT AND 6 SHOT, MILITARY

This specification sheet was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

The complete requirements for procuring the revolvers described herein shall consist of this document and the latest issue of specification DD-R-1187/GEN.

1. SCOPE

1.1 Scope. This specification sheet covers military, 5 shot and 6 shot, double action, caliber .38 special revolvers.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Military Specifications:
MIL-C-46409 - Cartridge, Cal. .38 Special, Ball, M41

(Copies of Military Specifications, Standards, and Drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 1005

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. Requirements **for submission of first article shall be as specified in the contract (see 6.2).**

3.2 Configuration. Unless otherwise specified (see 6.2), configuration shall be in accordance with Table I.

3.3 Barrel dimensions The barrel shall conform *to* the dimensional requirements specified in Table II.

TABLE 11

Bore diameter	0.346 + .001
Groove diameter	0.3555 + .0017
Groove width	0.114 + .003
Number of grooves	Five equally spaced
Rifling	Right hand twist, one turn in 18.75 + .50 inches.

3.4 Cylinder. The bullet seat diameter for each chamber of the cylinder shall be 0.358 minus 0.001 inch.

3.5 Firing pin. The firing pin tip shall be 0.072 + 0.003 inch diameter with a spherical radius at the end of not less than one-half the diameter of the firing pin tip, and a plus 0.005 inch tolerance. The intersection of the spherical radius and the cylindrical section of the firing pin shall be smoothly blended. The firing pin hole diameter in the breech face shall not exceed the maximum firing pin tip diameter by more than 0.010 inch.

3.6 Firing Pin Protrusion. The firing pin protrusion shall be not less than 0.042 inch. The firing pin shall retract to rear of breech face prior to cylinder rotation.

3.7 Firing pin indent. With the revolver *in* a vertical position, muzzle down, the firing pin indent shall be not less than 0.011 inch and not more than 0.016 inch for all chambers in both single action and double action. The firing pin indent shall not be off center more than one-half the diameter of the firing pin tip.

3.8 Trigger pull. The trigger pull shall be within the range of 2-1/2 to 5 pounds for single action and not more than **16** pounds for double action.

3.9 Ammunition. The revolvers shall meet the requirements specified herein and in specification D-R-1187 using cartridges, Cal. **.38,** Special, Ball, M41 in accordance with MIL-C-46409. High-pressure resistance ammunition shall be as specified in D-R-1187.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

TABLE I

Dash #	Barrel Lgt	Cylinder Cap	Frame Mat'1	Trigger	Front Sight	Rear Sight	Hammer	Weight (Max-Empty)
1	2" + 1/4	6 Shot	Steel	Grooved or Smooth	Fixed Ramp Style	Square Notched Frame or Square Notched Bar Dove-tailed Into Frame	Spur Grooved or Checkered	34 ounces
2	2" ± 1/4	5 shot	Aluminum	Grooved or Smooth	Quick Draw Ramp Style	Square Notched Frame or Square Notched Bar Dove-tailed Into Frame	Spur Grooved or Checkered	16 ounces
3	2" + 1/4	6 Shot	Steel	Wide Tar-get Type Grooved or Smooth	Quick Draw Ramp" Style	Adjustable	Target Type Spur Grooved or Checkered	34 ounces
4	4" + 1/4	6 Shot	Steel	Grooved or Smooth	Fixed Ramp Style	Square Notched Frame or Square Notched Bar Dove-tailed Into Frame	Spur Notched or Checkered	36 ounces
5	4" ± 1/4	6 Shot	Steel	Wide Tar-get Type Grooved or Smooth	Quick Draw Ramp Style	Adjustable	Target Type Spur Grooved or Checkered	37 ounces

sJ

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

3.10 Lanyard swivel. When specified, revolvers shall have a lanyard swivel securely attached to the butt of the revolver. The lanyard ring must be capable of revolving 360 degrees and swinging 180 degrees. The width of the ring shall be not less than 5/8 inch and no wider than the butt of the revolver. The depth of the ring shall be not less than 1/4 inch.

4. QUALITY ASSURANCE PROVISIONS

4.1 First article inspection. A first article shall be submitted for testing in accordance with the contract requirement. The first article shall be representative of the production processes *to* be used during quantity production. The first article shall be subjected to the Quality Conformance Inspection specified D-R-1187, the inspection specified herein, and such other inspection as necessary to determine that all requirements of the contract have been met.

4.2 Examination. Revolvers shall be examined in accordance with the following. Inspection lot and examination provisions of D-R-1187 apply.

Characteristic	Requirement	Inspection Method
Configuration .	Table I	Visual
Barrel	Table II	SMTE
Cylinder (bullet seat diameter)	3.4	SMTE
Firing pin	3.5	SMTE
Firing pin protrusion	3.6	SMTE

4.3 Testing.

4.3.1 Ammunition. All testing (except high-pressure resistance) shall be accomplished using ammunition specified in 3.9.

4.3.2 Firing pin indent testing. Twenty-five revolvers shall be selected at random from each represented inspection lot and tested using the inspection equipment conforming to drawing B8595796, Fixture, Holding and Drawing B8596142, Gage, Indicating, Firing Pin. Each chamber shall be tested both single and double action. Failure to meet the requirement (see 3.7) shall be cause for taking three additional readings in each failed chamber, in the failure mode (single or double action) and the average of the three (3) additional readings must be within the specified requirements. The firing pin indent impression shall be examined to determine if the concentricity requirement has been met. Failure of any one revolver to meet the requirement by averaging the three additional readings shall be cause for random selection of a second twenty-five revolvers and repeating the above procedures. Failure of any one revolver in the second twenty-five revolvers to meet the requirements

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

shall be cause for testing each chamber of each revolver in the lot. If no failures occur all other revolvers in the lot shall be tested in one chamber single action and in one other chamber double action. The copper compression cylinder shall be measured prior to-insertion in the chamber. The holding fixture containing copper compression cylinder (Drawing B5039436) shall be inserted in the chamber forward of the firing position. Holding the revolver in the vertical position, muzzle down, the trigger shall be pulled fully rearward double action to cause the firing pin to indent the compression cylinder. The holding fixture shall be removed and the depth of the indent in the copper compression cylinder shall be computed by subtracting the lowest reading of the firing pin impression from the original measured height. The above procedure shall be used for single action except the hammer is moved to the rear cocked position and trigger is pulled to **cause** the firing pin to indent the compression cylinder.

5* PREPARATION FOR DELIVERY

This section is not applicable to this specification.

6. NOTES

6.1 Identification number. The identification number consists of the document number plus the dash number.

Examples:

D-R-1187/2-l 2" barrel, 6 shot, steel frame grooved or smooth trigger, fixed ramp style front sight square notched frame rear sight, spur grooved or checkered hammer, and 34 ounces max-empty weight.

D-R-1187/2-5 4" barrel, 6 shot, steel frame, wide target type grooved or smooth trigger, quick draw ramp style front sight, adjustable rear sight, target type spur grooved or checkered hammer, and 37 ounces max-empty weight.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

a. Title, number and date of this specification sheet.

b. Identification number required (see 6.1 and Table I).

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T11:05Z
Check the source to verify that this is the current version before use.

c. First article requirements (see 3.1).

d. Configuration, if different (see 6.2).

e. **Responsibilities for furnishing ammunition.**

Military Custodians:
Army - Wc
Navy - OS
Air Force - 84

Review Activities:
Navy - OS
Air Force - 84

User Activities:
Air Force - 11

Preparing Activity:
Army - WC

Civil Agency Coordinating Activities:
JUSTICE - FPI
TREASURY - IRS
DC GOVT - DCG
GSA - FSS
DOT - FIS
POSTAL - POS
INTERIOR - GES

Project number:
1005-0482-3

U. S. GOVERNMENT PRINTING OFFICE : 1974 0- 585-642/1310

orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain copies and other documents referenced herein. Price 25 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.