F-G-621B (GSA-FSS)
March 5, 1973
SUPERSEDING
Int. Fed. Spec. F-G-00621A (GSA-FSS)
September 2, 1969

FEDERAL SPECIFICATION

GOVERNORS, GASOLINE ENGINE; CENTRIFUGAL, VELOCITY, AIR-VANE, HYDRAULIC, AND ELECTRONIC

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers governors intended for use on gasoline engines.

1.1.1 Federal specification coverage. This specification does not include all commercially available governors but covers only those which are purchased by the Federal Government.

1.2 Classification.

1.2.1 Types. Gasoline engine governors of types which either control the air-fuel mixture to the cylinders or the amount of fuel supplied to the cylinders shall be furnished as specified in the invitation for bids (see 6.2).

I - Actuated by centrifugal and mechanical force (including relay types).
II - Actuated by engine manifold vacuum or differential pressure.
III - Actuated by air flow (air-vane).
IV - Actuated by hydraulic forces.
V - Actuated by electronic devices.

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-636 - Box, Fiberboard.
PPP-B-665 - Boxes, Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676 - Boxes, Setup.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Wash.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:05Z
Check the source to verify that this is the current version before use.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks, and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standard:

MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications, Standards, Drawings, and Publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material. All materials used in the construction of the governor shall be those most suitable for the use intended. They shall not warp or otherwise become permanently deformed and shall be resistant to any corrosive action of the atmosphere, fuel, and hot gases of combustion under all normal working conditions.

3.1.1 Sample. When specified (see 6.2), the supplier shall furnish one complete governor for inspection. The sample may be either a preproduction item or a production item to determine conformance with requirements of this specification. In either case, the sample shall be physically and functionally interchangeable with the production items in accordance with the terms of the contract. Approval of a sample shall not relieve the supplier of the responsibility to furnish the governor in accordance with the requirements of this specification.

3.2 Workmanship. The governor shall conform to current manufacturing practices. Component parts and units shall be designed to definite standard dimensions with proper fits and tolerances for replacement purposes as recommended by the manufacturer.

3.3 Operating characteristics. With the engine operating at the manufacturer's specified horsepower rating, the governor shall have only that affect on the power of the engine as specified at speed below cutoff, which is defined as the point on the horsepower-speed curve beyond which the horsepower is no longer permitted to increase with increase in speed. The speed difference between full load and no load shall be maintained at a minimum, but under no condition shall this difference be so small that hunting or surging will occur. In the speed interval between maximum load and no load, operation shall be stable; i.e., there shall be no hunting or surging under any operating conditions. The engine with the governor installed shall operate at its most efficient r.p.m. through all gear ratios, despite changing loads and road speeds. The peak torque of the engine power curve shall not be affected by the installation of the governor.

3.4 Design and construction. The governor shall be the manufacturer's current production model as regularly advertised and sold and shall be suitable for the engine model as specified in the invitation for bids. The governor shall be so designed that manipulation of the throttle will not materially increase the governed speed when the engine is operating at its maximum governed r.p.m.

3.5 Tampering. The governor and its actuating mechanism shall be so constructed as to suffer no damage from engine back firing, or any throttle manipulation, while engine is being rotated above governed speed, either from coasting or other means. The type II governors shall be so designed as to assure against tampering and shall be furnished with seals, lock and key, or equivalent safeguard as specified.

3.6 Governor operation. The governor shall be suitable for operation with the engine make and model designated in the invitation for bids and shall be practical for intended use. All the governor types mentioned herein shall be capable of controlling engine speed at maximum acceptable application limits. When specified (see 6.2), governors shall be controlled to the limits indicated in the invitation for bids.

3.7 Installation and servicing. The governor shall be simple to install and easy to replace and adjust. The safeguards specified (see 3.5) shall be designed to preclude removal or adjustment without breaking the integrity of the safeguard. Each governor shall be provided with the necessary parts for replacement on the applicable engine.

3.8 Identification. Each governor shall be stamped with the manufacturer's name, model and part number and, when specified, the r.p.m. for which it is set.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:05Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection and test requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections and tests set forth in the specification where such inspections and tests are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Acceptance inspection. Unless otherwise specified (see 6.2), acceptance inspection shall be applied to two governors taken at random from the lot. (A lot shall consist of all governors submitted for acceptance at one time.) When the two sample governors selected meet the specification requirements, the lot from which the samples were selected shall be accepted. When one of the two sample governors fails to meet the requirements, two additional governors shall be selected as previously stated, and the two additional governors must meet the specification requirements in order that the lot represented may be accepted. When any two governors from those selected fail to qualify, the lot represented shall be rejected, and the contractor shall make the necessary corrections or adjustments, after which resampling shall be conducted.

4.3 Test methods. Compliance with the requirements of this specification shall be determined by the governor manufacturer using his own test procedures and techniques, to assure that each governor is capable of performing to the limits required by the make, model, and design of the engine, in accordance with the manufacturer's specifications. When specified (see 6.2), the governor shall be mounted on an engine of the make and model designated. This engine shall then be mounted on a laboratory dynamometer test stand and the necessary testing carried out to assure qualification of the governor. When specified (see 6.2), the governor shall be tested on the make and model of vehicle for which it is designed under actual road conditions or on a suitable test track or circuit.

4.4 Inspection of preparation for delivery. An inspection shall be made to determine that the packaging, packing, and marking requirements comply with section 5.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

5.1.1 Levels A and B. Each governor, with all necessary parts for replacement to attach it to the engine, shall be packaged in a close-fitting box conforming to PPP-3-566, PPP-B-665, or PPP-B-676.

5.1.2 Level C. Governors shall be packaged in accordance with the supplier's commercial practice.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. Governors, packaged as specified in 5.1 and in quantities as specified (see 6.2), shall be packed in a close-fitting box conforming to PPP-B-636, class weather-resistant. The box shall be close, water-proofed, and strapped in accordance with the appendix to PPP-B-636.

5.2.2 Level B. Governors, packaged as specified in 5.1 and in quantities as specified (see 6.2), shall be packed in a box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to PPP-B-636.

5.2.3 Level C. Governors shall be packed to insure carrier acceptance and safe delivery at destination at the lowest rates, in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Marking. In addition to marking required by the contract or order, the unit and shipping container shall be marked in accordance with Fed. Std. No. 123 or MIL-STD-129, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The governors covered by this specification are intended for use on gasoline engines.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type of governor required (see 1.2.1).
(c) Sample, when required (see 3.1.1).
(d) Governor operation, if other than standard (see 3.6).
(e) Acceptance inspection, if other than standard (see 4.2).
(f) Test methods, state if other than standard (see 4.3).
(g) Selection of applicable level of packaging and packing required (see 5.1 and 5.2).
(h) Parts list and service manual if required.

6.3 Purchasers should indicate the make, model, displacement and speed of the engine (s) on which the governor will be installed.

6.4 Dynamometer tests. When dynamometer engine tests are required (see 4.3), the tire size, rear axle gear ratio, gross vehicle weight, payload, and the speed of the applicable vehicle should also be given.

Orders for this publication are to be placed with the General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 10 cents each.

☆U.S. GOVERNMENT PRINTING OFFICE: 1974-713-151/3806

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.