MIL-C-18795F(YD)
18 September 1986
SUPERSEDING
MIL-C-18795E(YD)
5 November 1981

MILITARY SPECIFICATION

CART, CONCRETE

This specification is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a 6 cubic foot minimum capacity, two wheeled, pneumatic tired, hand pushed concrete cart.

1.2 Part numbers. The specification part number for the cart covered by this specification shall be M18795-01.

2. APPLICABLE DOCUMENTS.

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-T-60 - Tape: Packaging, Waterproof.

|Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.|

FSC 3895

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

AMSC N/A

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:56Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116 - Preservation, Methods of.
MIL-B-121 - Barrier Material, Greaseproofed, Waterproofed Flexible.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-794 - Parts and Equipment, Procedures for Packaging and Packing of.
MIL-STD-1186 - Cushioning, Anchoring, Bracing, Blocking,and Waterproofing; with Appropriate Test Methods.

(Copies of specifications and standards required by contractors in connection with specific acquisition functions should be obtained from the procuring activity or as directed by the contracting activity)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of the documents not listed in the DODISS shall be the issue of the non-Government documents which is current on the date of the solicitation.

TIRE AND RIM ASSOCIATION, INC. (TRA)

TRA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 West Market Street, Akron OH. 44313.)

(Non-Government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other information sources.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The cart shall consist of a steel body, axle(s), two pneumatic tired wheels, support legs, rockers, and a handle. The cart shall have a struck capacity of not less than 6 cubic feet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:56Z
Check the source to verify that this is the current version before use.

3.2 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.2.1 and 6.3).

3.3 Standard commercial product. The cart shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the cart being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

3.4 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

3.5 Design and construction.

3.5.1 Dimensions. The overall width of the cart shall be not greater than 31 inches. The grip part of the handle shall be 1.0 to 1.5 inches in diameter. The handle shall be from 30.0 to 35.0 inches high, when measured from level ground surface to the top of the handle while the cart is resting on its supporting legs.

3.5.2 Body The body shall be constructed of sheet steel components welded together, or of a single steel sheet formed to the required shape. Nominal thickness of the sheet steel shall be not less than 0.0747 inch (U.S. revised standard gage No. 14). Component members shall be joined using one of the arc welding processes (see 3.7.5). Welding of components shall be performed in a manner to preclude protrusions on the inner surfaces which would restrict or catch the edge of a shovel blade. The interior surfaces of the body shall be smooth and free of obstructions. To withstand the stresses imposed, and to prevent permanent deformation or damage to the cart, the body shall be reinforced wherever necessary, but particularly where the axle(s), support legs, handle, and rockers connect to the body and along the upper rim. A towing eye or bail shall be secured to the cart in a position which shall permit a second man, with a hook or line, to pull the cart up a steep incline.

3.5.3 Axle(s) and wheels. The cart shall be furnished with a drop type axle or two stub type axles. Wheels shall be the steel spoke or disk type, with recessed hubs. Wheel hubs shall be equipped with heavy duty, roller, or ball type bearings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:56Z
Check the source to verify that this is the current version before use.

3.5.4 Tires Tires shall be tube or tubeless type. If provided, tubes shall be heavy-duty type and of correct size to match the tires as recommended by the TRA. Size of tires furnished shall be not less than 4 by 18, with a ply rating of not less than 4. Tires shall not extend above the upper rim of the body.

3.5.5 Identification plate. The contracting officer will furnish to the Government inspector the required identification plates. The contractor will be required to stamp the necessary data in the blank spaces thereon and securely affix said plates in a conspicuous place on each unit, assembly or subassembly, and parts as directed by the Government inspector. Nonferrous screws, rivets, or bolts of not less than 1/8 inch in diameter shall be used to affix the plates. Nomenclature shall be "Cart, Concrete".

3.5.6 Treatment and painting. Unless otherwise specified (see 6.2.1), the cart shall be treated and painted in accordance with the manufacturer's standard practice. All surfaces of the cart other than corrosion-resisting steel shall be protected against corrosion and present a neat appearance

3.6 Performance characteristics. The cart shall be designed so that when fully loaded:

a. One man can easily maneuver the cart over uneven surfaces, such as are commonly found at construction sites.
b. Resting on its support legs, the cart shall not dump its load, roll, turn, or move when left unattended.
c. Two men, one pushing the other pulling using a line or hook, shall be able to maneuver the cart up an incline of not less than 8 feet in length and a slope of 4 to 1.
d. The center of gravity is located in a position which shall allow one man to dump the entire contents with minimum effort.

3.7 Workmanship.

3.7.1 Steel fabrication The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.7.2 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the castings ability to perform its intended function.

3.7.3 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts and screws shall be tight.

3.7.4 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:56Z
Check the source to verify that this is the current version before use.

countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in fill contact with the surface of the member.

3.7.5 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. The first article inspection shall be performed on one cart when a first article is required (see 3.2 and 6.2.1). This inspection shall include the examination of 4.4, the tests of 4.5, and, when specified, the preproduction pack inspection of 4.6 (see 4.6 and 6.2.1). The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:56Z
Check the source to verify that this is the current version before use.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.4, the tests of 4.5, and the packaging inspection of 4.6. This inspection shall be performed on the samples selected in accordance with 4.3

4.3 Sampling. Sampling and inspection procedures shall be in accordance with MIL-STD-105. The unit of product shall be one cart. All carts offered for delivery at one time shall be considered a lot for the purpose of inspection. The inspection level shall be level II and the Acceptable Quality Level shall be 2.5 percent defective. If an inspection lot is rejected, the contractor may rework it to correct the defects, or screen out the defective units, and resubmit for a complete reinspection. Resubmitted lots shall be reinspected using tightened inspection. If the rejected lot was screened, reinspection shall be limited to the defect causing rejection. If the lot was reprocessed, reinspection shall be performed for all defects. Rejected lots shall be separated from new lots, and shall be clearly identified as reinspected lots.

4.4 Examination. Each cart shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirement shall constitute one defect.

4.5 Tests. The cart shall be loaded to within 2 inches of the upper rim with low slump concrete or a mixture of sand, coarse aggregate, and water. The cart will then be subjected to the following:

a. One man shall maneuver the loaded cart for 10 minutes over an uneven surface or at a construction site where other carts are being utilized for transporting concrete. During the coarse of this maneuver, the cart shall be rested on its support legs not less than five times.
b. Two men, one pushing and the other pulling using a line or hook, shall maneuver the loaded cart up an incline not less than 8 feet in length and having a slope of 4 to 1.
c. One man shall dump the loaded cart.

4.6 Packaging inspection. The preservation, packing, and marking of the cart shall be inspected to verify conformance to the requirements of section 5. The inspection shall consist of the quality conformance inspection; and, when specified (see 6.2.1), a preproduction pack shall be furnished for examination and test within the time frame required (see 6.2.1).

5. PACKAGING

5.1 Preservation. Preservation shall be level A or C as specified (see 6.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:56Z
Check the source to verify that this is the current version before use.

5.1.1 Level A.

5.1.1.1 Disassembly. Disassembly shall be the minimum necessary to protect parts subject to damage or loss, and to accomplish reduction in cube. Removed bolts, nuts, pins, screws, and washers shall be reinstalled in mating parts and secured to prevent their loss.

5.1.1.2 Preservatives. Preservatives specified shall conform to the applicable specifications listed in, and shall be applied in accordance with MIL-P-116.

5.1.1.3 Wheels, axles, bearings, and tires. When wheels are removed the tires shall be inflated to two-thirds of the specified operating pressure. The wheel nuts shall be replaced on the studs and the exposed threaded surfaces shall be coated with type P-1 preservative. When wheels and hubs are removed from axles or spindles, the interior bearing surfaces of the hubs and the bearings or bearing surfaces of the axles or spindles shall be coated with type P-11 preservative. The coated surfaces of the axles or spindles shall be wrapped and hub openings shall be covered with barrier material conforming to MIL-B-121, type I, grade A, class 2. The barrier material shall be secured in place with tape conforming to PPP-T-60, type IV. Bearings removed from the wheels shall be coated with type P-11 preservative and preserved method IA-8. When wheels are not removed, the tires shall be inflated to 10 pounds above the specified operating pressure and wheel bearings shall be preserved with type P-11 preservative.

5.1.1.4 Hardware. Removed hardware (e.g., nuts, bolts, washers, and pins) not painted and subject to corrosion shall be painted or have a preservative applied in accordance with MIL-P-116, method IC-1 or IC-3, as applicable.

5.1.1.5 Consolidation. The hardware, removed bearings, and other small components shall be consolidated in containers conforming to PPP-B-636, Class water resistant. Contents shall be cushioned, blocked, and braced to prevent movement in accordance with MIL-STD-1186. Containers shall be secured to the equipment with appropriate strapping. Arrangement and location on the equipment shall be such as not to increase cubage or interfere with lifting or mobility of the equipment.

5.1.2 Level C. The equipment shall be preserved in accordance with the contractor's standard practice in a manner to prevent deterioration and damage. The equipment shall be lubricated for operational service as required in the operator's manual.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2.1).

5.2.1 Levels A, B, and C. Packing shall be accordance with MIL-STD-794 for the applicable level specified. Containers shall be selected from table I of MIL-STD-794 for the appropriate level. Open crates shall not be used for Level A packing.

5.3 Marking. Marking shall be in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:56Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The concrete cart is intended for use in transporting low slump concrete.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Treatment and painting, if other than as specified (see 3.5.6).
c. When a first article inspection is required. When a preproduction package inspection is required and time frame required (see 4.2.1 and 4.6).
d. Level of preservation and level of packing required (see 5.1 and 5.2).

6.2.2 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL) and invokes the provisions of DoD Federal Acquisition Regulations (FAR) Supplement 27.410-6, the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL (DD Form 1423) incorporated into the contract. When the provisions of DoD FAR 27.410-6 are not invoked, the data shall be delivered in accordance with the contract requirements.

6.3 First article. When a first article inspection is required, the item will be tested and should be a first production item or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The first article should consist of one unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

6.4 Subject term (key word) listing.

Cart
Concrete

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Preparing activity:

Navy - YD

(Project 3895-0281)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:56Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-18795F(YD)	CART, CONCRETE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*:
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(FOLD DETACH THIS FORM, CUT ALONG THIS LINE)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:56Z
Check the source to verify that this is the current version before use.

REPRODUCED AT GOVERNMENT EXPENSE

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer (156)
Naval Construction Battalion Center
Port Hueneme, CA 93043-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:56Z
Check the source to verify that this is the current version before use.