INCH-POUND

MIL-P-18704A(OS)
13 May 1992
SUPERSEDING
MIL-P-18704(NOrd)
2 June 1955

# MILITARY SPECIFICATION

# PRIMER, LOCK, COMBINATION, MARK 15 MOD 2

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This specification establishes the minimum requirements for the Combination Lock Primer, Mk 15 Mod 2, hereinafter referred to as the "primer" (see 6.1).

## 2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the specification (see 6.2).

SPECIFICATIONS

FEDERAL

| | |
|---|---|
| PPP-B-636 | Boxes, Shipping, Fiberboard |

MILITARY

| | |
|---|---|
| MIL-D-3464 | Desiccants, Activated, Bagged, Packaging Use and Static Dehumidification |

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Indian Head Division, Naval Surface Warfare Center, Standardization Branch (Code 3730), 101 Strauss Avenue, Indian Head, MD 20640-5035 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by sending a letter.

AMSC N/A FSC 1390

DISTRIBUTION STATEMENT A. Approved for public release; distribution is limited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:50Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

| | |
|---|---|
| MIL-STD-129 | Marking for Shipment and Storage |
| MIL-STD-331 | Fuze and Fuze Components, Environmental and Performance Tests for |
| MIL-STD-453 | Inspection, Radiographic |
| MIL-STD-1167 | Ammunition Data Card |
| MIL-STD-1168 | Ammunition Lot Numbering |
| DOD-STD-2101 | Classification of Characteristics |

(Unless otherwise indicated, copies of federal and military specifications and military standards are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

**2.1.2 Other Government documents, drawings, and publications.** The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues shall be those cited in the solicitation.

DRAWINGS

NAVAL SEA SYSTEMS COMMAND (CAGE CODE 10001)

| | |
|---|---|
| LD166537 | Test Set, Mark 135 Mod 0 |
| 439155 | Primer, Lock, Mark 15 Mod 2 |
| 1251320 | Primer, Container, Mark 12 Mod 0 (Inner) |
| 2846999 | Primer, Lock, Mark 15 Mod 2 Packaging Assembly |

(Application for copies of NAVSEA drawings should be addressed to: Commanding Officer, Naval Ordnance Station, Crane Division, Naval Surface Warfare Center, Attn: Code 802, Louisville, KY 40214-5001.)

PUBLICATIONS

NAVAL SEA SYSTEMS COMMAND (CAGE CODE 10001)

| | |
|---|---|
| OD 5823 | Sensitivity Test of Primers and Detonators |



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:50Z
Check the source to verify that this is the current version before use.

(Application for copies of OD's should be addressed to: Commander, Port Hueneme Division, Naval Surface Warfare Center, NAVSEA Data Support Activity (Code 5H30), Port Hueneme, CA 93043.)

CODE OF FEDERAL REGULATIONS (CFR)

49 CFR 100-199 Transportation

(The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

**2.2 Order of precedence.** In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

## 3. REQUIREMENTS

**3.1 First article.** When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.7) in accordance with 4.4.

**3.2 Characteristics.** The primer shall conform to all requirements specified herein and on Drawing 439155.

**3.3 Radiographic (M101).** The primer shall not exhibit any loose components (except black powder) or any missing or extra parts. Primers exhibiting possible defects shall be included in the detail strip sample and meet the requirements of 3.7 (see 4.7.1 and 4.7.5).

**3.4 Electrical resistance (M102).** The primer bridge wire shall have an electrical resistance of 0.55 to 0.70 ohm. Primers with a bridge wire electrical resistance greater than 0.70 ohm or less than 0.55 ohm shall be rejected (see 4.7.2).

**3.5 Leak test (M103).** A sample of primers from each lot shall be subjected to a leak test. The leak rate for any primer shall not exceed $1 \times 10^{-3}$ atmosphere cubic centimeter/sec (see 4.7.3).

**3.6 Black powder moisture content (M104).** The moisture content of the black powder within the primer shall not exceed 0.70 percent by weight (see 4.7.4).

**3.7 Detail strip.** The primer and its components shall conform to the following requirements (see 4.7.5):

a. (C1) Each critical characteristic shall be as specified in the applicable documents listed on Drawing 439155 and this specification.

b. (M105) Each major characteristic shall be as specified in the applicable documents listed on Drawing 439155 and this specification.

**3.8 No-fire (C2).** The primer shall not fire in the no-fire test (see 4.7.6).



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:50Z
Check the source to verify that this is the current version before use.

**3.9 All-fire (M106).** The primer shall fire in the all-fire test (see 4.7.7 and 4.7.8).

**3.10 Functioning.** The primer shall meet the following criteria (for electric primers, see 4.7.7; for percussion primers, see 4.7.8):

a. **(M107)** Primer functioning time shall be a maximum of 0.020 second.

b. **(M108)** The primer shall not misfire (see 6.6.1).

c. **(M109)** The primer shall not exhibit blowback (see 6.6.2).

d. **(M110)** The primer shall not exhibit splitting or distortion which prevents ready extraction from the primer lock, or detachment of metallic components.

**3.11 Vibration.** The primer shall meet the following requirements (see 4.7.9):

a. **(C3)** The primer shall not function during vibration.

b. **(C4)** The stock and seal assembly shall maintain material integrity, and the primer shall maintain assembly integrity at the mating threads of the stock and seal assembly.

c. **(M111)** The primer shall not otherwise physically break down during vibration.

d. The primer shall meet the requirements of 3.8, 3.9, and 3.10 after vibration.

**3.12 Ignition test (M112).** Each primer tested shall successfully ignite the ignition pad and meet the requirements of 3.10b, 3.10c, and 3.10d (see 4.7.10).

**3.13 Workmanship.** All parts shall be free of chips, dirt, grease, rust, and all other foreign materials. There shall be no burrs or other imperfections of manufacture which would affect the assembly, functioning, or handling of the product. The cleaning methods used shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agents. All markings shall be legible.

## 4. QUALITY ASSURANCE PROVISIONS

**4.1 Responsibility for inspection.** Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:50Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4)
b. Quality conformance inspection (see 4.5)

4.3 Test and examination methods (see 6.2). Primers shall be selected at random for each test or examination. Identification of each primer's complete test and examination results shall be secured for additional examination until otherwise directed by the contracting activity (see 6.5).

4.4 First article inspection. The first article shall be a homogeneous sample of 304 assembled primers and five each of every component and subassembly (less explosive components) fabricated, packaged, and packed in accordance with the requirements of this specification and the contract, using the methods and procedures to be used for production. This sample is in addition to those primers required for contractor inspection and tests. The first article shall be submitted to the facility designated in the contract or order for test and examination in accordance with the first article inspection plan of table I (see 6.2 and 6.7). Prior to delivery, a first article shall be inspected and tested by the contractor for all requirements specified herein.

4.4.1 First article sample rejection. Failure of the first article sample to meet any of the requirements specified herein shall be cause for rejection of the sample.

4.5 Quality conformance inspection.

4.5.1 Lot formation. Unless otherwise specified in the contract or purchase order (see 6.2), production lots shall consist of 10,000 homogeneous primers plus those required for inspection (see 4.5.2). Each production lot shall contain one Class 4 and one Class 6 black powder lot.

4.5.2 Sampling for inspection. Unless otherwise specified in the contract or purchase order (see 6.2), 266 samples shall be selected at random from each production lot for test and examination in accordance with the quality conformance inspection plan of table I. This sample is in addition to those primers required for contractor inspection and tests.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:50Z
Check the source to verify that this is the current version before use.

TABLE I. First article and quality conformance inspection plan.

| Test or Examination | Requirement Paragraph | Test Paragraph | First Article Inspection | | | Quality Conformance Inspection | | |
|---|---|---|---|---|---|---|---|---|
| | | | Sample Size | Accept | Reject | Sample Size | Accept | Reject |
| Radiographic | 3.3 | 4.7.1 | 304[1/] | 0 | 1 | 266[1/] | 0 | 1 |
| Electrical resistance | 3.4 | 4.7.2 | 304[1/] | 0 | 1 | 266[1/] | 0 | 1 |
| Leak test | 3.5 | 4.7.3 | 50 | 0 | 1 | 50 | 0 | 3[2/] |
| Detail strip | 3.7 | 4.7.5 | | | | | | |
| a. major | | | 56 | 0 | 1 | 56 | 1 | 2 |
| b. critical | | | — | 0 | 1 | — | 0 | 1 |
| c. black powder moisture | 3.6 | 4.7.4 | 20[3/] | 0 | 1 | 20[3/] | 0 | 1 |
| Functional, electrical, at 20 Vdc | 3.9, 3.10 | 4.7.7 | 50 | 0 | 1 | 40 | 0 | 1 |
| Functional, percussion, at 10 inches | 3.9, 3.10 | 4.7.8 | 50 | 0 | 1 | 32 | 0 | 1 |
| No-fire, percussion, at 3 inches | 3.8 | 4.7.6 | 50 | 0 | 1 | 32 | 0 | 1 |
| Vibration | 3.11 | 4.7.9 | 12 | 0 | 1 | | | |
| Ignition test | 3.12 | 4.7.10 | | | | | | |
| Percussion | | | 5 | 0 | 1 | 5 | 0 | 1 |
| Electrical | | | 5 | 0 | 1 | 5 | 0 | 1 |
| Packaging | Section 5 | 4.8 | 8 pk | 0 | 1 | 7 pk | 0 | 1 |

[1/] Radiographic examination and resistance test shall be performed on all samples prior to any other test or examination.

[2/] The incident of one failure shall cause a sample of 200 to be tested. If there is more than one failure in the second test, the entire lot shall be leak tested and all nonconforming primers removed from the lot.

[3/] Samples shall be taken from those for the detail strip examination.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:50Z
Check the source to verify that this is the current version before use.

**4.6 Classification of characteristics.** The characteristics verified by the tests and examination herein are classified as critical, major, or minor in accordance with DOD-STD-2101. Requirements for critical characteristics are identified by the symbol (C) and major characteristics by the symbol (M). The number following the classification symbol indicates the serial number of the characteristic. Requirements not annotated with a classification code are classified as minor.

**4.7 Methods of inspection.**

**4.7.1 Radiographic.** The primer shall be subjected to a radiographic inspection in accordance with MIL-STD-453. The primer shall be mounted in the vertical position with the primer stock up and X-rayed perpendicular to its axis, focused at a point 0.25 ± 0.20 inch from the stock face. Any primer which meets the requirements of 3.3 but appears to have been misassembled shall be subjected to detail strip and shall meet the requirements of 3.7.

**4.7.2 Electrical resistance.** The primer electrical resistance shall be measured by using a test circuit which limits the bridge current to 50 milliamperes, maximum. The primer stock and the plunger shall be used as terminals. Fifteen to twenty pounds force shall be applied to the electrode during resistance measurement with a probe having a 0.050 ± 0.005 inch spherical radius. Assure that contact on clean bright surfaces is obtained.

**4.7.3 Leak test.** Each primer shall be tested in accordance with Test C8 (volume-sharing method) of MIL-STD-331.

**4.7.4 Determination of moisture content.** Moisture analysis procedure for the black powder shall be as follows:

a. Twenty primers shall be randomly selected. The entire black powder charge from a primer seal assembly shall be used for each sample. Black powder shall be tested in the granular form.

b. The black powder shall be removed from primer tubes and placed in a dry container with a tight cover. Sample from each primer shall be kept separate from other samples. Black powder shall not be exposed to the atmosphere for more than 3 minutes.

c. Sample containers must be covered and placed in a desiccator until ready to test the moisture content.

d. Carefully weigh 1.9 ± 0.1 grams (g) of sample into a tared weighing dish or container. The sample shall be weighed to the nearest 0.1 mg. Black powder shall not be exposed to the atmosphere for more than 3 minutes.

e. Uncovered samples shall then be placed in an oven at 70 to 75 degrees Celsius (°C). Do not draw vacuum.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:50Z
Check the source to verify that this is the current version before use.

f. After 4 hours minimum, remove samples from oven, cover, and place in a desiccator to cool for 1 hour. After cooling, carefully weigh samples to the nearest 0.1 mg. Calculate the percent moisture as follows:

$$\text{Percent moisture} = \frac{E}{C} \times 100$$

Where:

$C = A - B$
$E = A - D$

and

A = Sample weight plus container weight, undried, g
B = Undried container weight, g
C = Undried sample weight, g
D = Sample weight plus container weight, after drying, g
E = Weight difference, after drying, g

**4.7.5 Detail strip.** The primer shall be disassembled to determine conformance to all the discernible critical and major characteristics specified on Drawing 439155. All inspections shall be performed at the highest level of assembly possible.

**4.7.6 No-fire.** The primer shall be assembled into Test Set Mk 135 Mod 0 (LD166537) and tested in accordance with the appropriate procedures of OD 5823 using a 16.34-ounce steel ball. The ball drop height shall be 3.0 inches. Primers which function shall be considered defective.

**4.7.7 Electrical functioning.** The primers shall be tested in a safety chamber which simulates service operation. A power source of 20 volts direct current (Vdc) shall be used. The primer stock and plunger shall serve as terminals. Primers which fail to function within 0.006 second or show evidence of blowback, splits, or in which metallic components other than closing disks are detached, shall be considered defective. Electronic timing which is activated by the firing pulse and the explosive output shall be used. The explosive output shall be measured at a distance of less than 1.0 inch from the output end by means of a piezoelectric gage or a device of at least equal speed.

**4.7.8 Percussion functioning.** Fit the Mk 135 Mod 0 Test Set with a firing chamber and plunger actuator. Mounting of the primer shall simulate support against the forces of explosion equivalent to service operation. Adjust the scale and align the test set, as provided in OD 5823, to deliver impacts coincident with axis of the plunger. The primer shall function when the plunger is actuated by the impact of a 16.34-ounce steel test ball falling from a height of 10.0 inches. Defectives for this test include failure to fire, hangfire which is obvious to the operator without instrumentation, blowback, split stock, and detachment of metallic components from the primer.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:50Z
Check the source to verify that this is the current version before use.

4.7.9 Vibration. The primer shall be subjected to the transportation vibration test of MIL-STD-331, Test B1, section 6.1.2, Table B1-4, except that the orientation of each primer during this three-phase test shall be as follows:

a. Phase I: Primer axis horizontal
b. Phase II: Primer axis vertical, primer stock down
c. Phase III: Primer axis vertical, primer stock up

The primer shall be marked with a line in the axial direction at the junction of the stock and seal assembly tube indexing their initial relative position, in order to determine the integrity after vibration. The primer shall be rigidly mounted to the vibration table at the primer stock. After vibration, the primer shall be subjected to the tests of 4.7.2, 4.7.6, 4.7.7, and 4.7.8. The lot shall be rejected if more than one primer fails to meet the bridge resistance requirements of 3.4. Randomly divide the sample into groups of three, three, and six primers. Subject the group of six primers to the electrical functioning test of 4.7.7. Subject the two remaining groups to the percussion functioning test of 4.7.8 and the no-fire test of 4.7.6. The incidence of more than one functioning defect shall cause rejection of the lot.

4.7.10 Ignition test. The primer shall be tested on the basis of each lot for performance. Sample primer shall be fired in standard firing locks in a bag gun for which the primer is a service item and using dummy charges with live ignition ends or ignition pad mounted on a plywood disk. Use a standoff distance of 9.0 inches.

4.8 Inspection of packaging. The packaging, packing, and marking shall be visually examined for conformance to section 5.

## 5. PACKAGING

5.1 Packaging (Level A). Thirty-eight primers shall be packaged in accordance with the drawings listed on Drawing 1251320 for the inner pack. Forty-five units of desiccant, conforming to Type I of MIL-D-3464, shall be placed in each container prior to securing the cover.

5.1.1 Inert components. Components and subassemblies shall be packaged in commercial fiberboard containers meeting the requirements of PPP-B-636. Each container shall incorporate corrugated or solid fiberboard dividers or collars suitable for preventing damage in handling and transportation. The gross weight of the container contents shall not be greater than 70 pounds.

5.2 Packing (Level A). Thirty-two inner packs shall be packed in an outer container in accordance with Drawing 2846999.

5.3 Marking. In addition to any special marking required by the contract or purchase order (see 6.2), all markings shall be in accordance with MIL-STD-129 and 49 CFR 171-178.



Source: https://assist.dla.mil -- Downloaded: 202610-18T11:50Z
Check the source to verify that this is the currentversion before use.

**5.4 Ammunition data cards.** When specified in the contract or purchase order (see 6.2), one ammunition data card prepared in accordance with MIL-STD-1167 shall be placed in the top of each pack (see 5.1), two shall be forwarded to the contracting activity, and two shall go to the ammunition depot receiving the primers. For Navy acquisitions, two data cards shall also go to each of the activities listed in 6.5 (see 6.3).

**5.5 Ammunition lot number.** Ammunition lot number shall be in accordance with MIL-STD-1168.

## 6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory)

**6.1 Intended use.** The Mk 15 Mod 2 Combination Lock Primer is used to ignite the propellant charge in all bag guns.

**6.2 Acquisition requirements.** Acquisition documents must specify the following:

a. Title, number, and date of this specification.

b. Issue of DODISS to be cited in the solicitation, and, if required, the specific issue of individual documents referenced (see 2.1.1 and 2.1.2).

c. Whether a first article sample is required (see 3.1).

d. The facility designated to perform first article inspection (see 4.4).

e. The facility designated to perform quality conformance inspection if other than the contractor (see 4.1).

f. Inspection lot quantity if other than specified in 4.5.1.

g. Inspection lot sample quantity if other than specified in 4.5.2.

h. Test and examination procedures and equipment to be used (see 4.3, 6.3, and 6.5).

i. Special marking, if required (see 5.3).

j. Ammunition data cards (see 5.4, 6.3 and 6.8).

k. Safety precautions (see 6.4).

**6.3 Consideration of data requirements.** The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Descriptions (DID's) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/provided and that the DID's are tailored to reflect the requirements of the specific acquisition.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:50Z
Check the source to verify that this is the current version before use.

To ensure correct contractual application of data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DOD FAR Supplement 27.475-1 exempts the requirement for a DD Form 1423.

| Reference paragraph | DID Number | DID Title | Suggested Tailoring |
|---|---|---|---|
| 4.3 | DI-NDTI-80603 | Test Procedure | — |
| 5.4 | DI-MISC-80043 | Ammunition Data Card | — |

The above DID's were those cleared as of the date of this specification. The current issue of DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DID's are cited on the DD Form 1423.

6.4 Safety precautions. The safety precaution requirements of the "Contractors' Safety Manual for Ammunition, Explosives, and Related Dangerous Material" (DOD 4145.26M) are applicable and should be specified in the contract or order as required by the Federal Acquisition Regulation (FAR) 23.3. NOTE: When this specification is used as part of the description of work to be accomplished by a Government activity, the safety precaution requirements of "Ammunition and Explosives Ashore" (OP 5) should be made applicable.

6.5 Test procedures and reporting. For Navy acquisitions, the contracting activity should include in each work authorization for first article and quality conformance inspections, the requirement for the preparation and forwarding to the activities listed below of all test and examination procedures prior to performance of any inspection. The work authorization should also include the requirement for the forwarding of all test data in an intelligible form to the activities listed below within five working days of the completion of the tests.

Commander
Crane Division
Naval Surface Warfare Center
Code 50254
Crane, IN 47522-5000

Commander
Indian Head Division
Naval Surface Warfare Center
Code 6110
Indian Head, MD 20640-5035

6.6 Definitions.

6.6.1 Misfire. Misfire is the failure of the main black powder charge of the primer to ignite when the primer is subjected to the appropriate firing source.

6.6.2 Blowback. Blowback is gas leakage around or through the stock end of the primer and is verified by observance during firing or by visual evidence of residue after firing.

6.7 First article. When a first article inspection is required, it should consist of 304 assembled primers and five each of every component and subassembly (less explosive components). The contracting officer should provide specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering such products which have been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test,



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:50Z
Check the source to verify that this is the current version before use.

must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

**6.8 Primer (percussion element) sensitivity.** The sensitivity of each lot of percussion primers should be determined within the six month period prior to assembly into the Mk 15 primers. The sensitivity values should be recorded on the ammunition data card. The sensitivity values are principally for process control in that variations in sensitivity values will not directly cause rejection of the primers but may be a reason for checking materials and processes for conformance with drawing and specification requirements. The sensitivity test shall be conducted on the basis of 50 percussion primers from each production lot in Test Set Mk 135 Mod 0 (LD166537) and tested in accordance with the staircase method (Bruceton) as prescribed in OD 5823 using a 16.34-ounce steel ball and 0.50-inch drop increments starting at a suggested height of 6.0 inches for the test. Compute the 50 percent firing height (H) and the standard deviation (S), and record the values on the ammunition data card.

**6.9 Changes from previous issue.** Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

**6.10 Subject term (key word) listing.**

Black powder
Igniter, propellant charge

Preparing activity:
Navy - OS
(Project 1390-N766)



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:50Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

## INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

| I RECOMMEND A CHANGE: | 1. DOCUMENT NUMBER | 2. DOCUMENT DATE (YYMMDD) |
|---|---|---|
| | MIL-P-18704A(OS) | 920513 |

3. DOCUMENT TITLE
PRIMER, LOCK, COMBINATION, MARK 15 MOD 2

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

| a. NAME (Last, First, Middle Initial) | b. ORGANIZATION | |
|---|---|---|
| c. ADDRESS (Include Zip Code) | d. TELEPHONE (Include Area Code)<br>(1) Commercial<br>(2) AUTOVON<br>(If applicable) | 7. DATE SUBMITTED (YYMMDD) |

8. PREPARING ACTIVITY

| a. NAME | b. TELEPHONE (Include Area Code) | |
|---|---|---|
| Commander, Indian Head Division<br>Naval Surface Warfare Center (Code 3730) | (1) Commercial<br>(301)743-4358/4510 | (2) AUTOVON<br>364-4510 |
| c. ADDRESS (Include Zip Code)<br>101 Strauss Avenue<br>Indian Head, MD 20640-5035 | IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:<br>Defense Quality and Standardization Office<br>5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466<br>Telephone (703) 756-2340 AUTOVON 289-2340 | |

Source: https://assist.dla.mil -- Downloaded: 2021-10-21 11:50Z
Check the source to verify that this is the current version before use.