MIL-C-10119C(EA)
4 April 1984
SUPERSEDING
MIL-C-10119B(MU)
27 March 1984

MILITARY SPECIFICATION

CANISTER, M11; COMPONENTS FOR

This specification is approved for use by US Army Armament, Munitions and Chemical Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

This specification covers the components for the M11 canister.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

STANDARDS

FEDERAL

Fed. Std. No. 141 - Paint, Varnish, Lacquer, and Related Materials; Methods for Sampling and Testing.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

: Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed: to: Commander, Armament Research and Development Center, US Army Armament, Munitions and Chemical Command, ATTN: DRSMC-TSC-S(A), Aberdeen Proving Ground, MD 21010 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter. :

FSC 4240

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:34Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS AND ASSOCIATED LISTS

US ARMY ARMAMENT, MUNITIONS AND CHEMICAL COMMAND

CHEMICAL RESEARCH AND DEVELOPMENT CENTER

TDPL 5-3-588 - Canister, M11.

(Copies of specifications, standards, handbooks, drawings and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM) STANDARDS

D 3951 - Standard Practice for Commercial Packaging.

(Application for copies should be addressed to ASTM, 1916 Race Street, Philadelphia, PA 19103.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Materials. All materials used in the manufacture of the components shall comply with the requirements of the specifications and drawings forming a part of this specification.

3.2. Manufacture. The components shall be manufactured in accordance with the drawings listed on TDPL 5-3-588, as applicable.

3.3 Preproduction. Prior to the start of regular production a preproduction sample of each component shall be produced in accordance with this specification for examination and tests (see 4.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:34Z
Check the source to verify that this is the current version before use.

3.4 Workmanship.

3.4.1 Irregularities. The components shall be free from burrs and sharp edges, from damage such as rips, tears, cuts, perforations, abrasion, dents, die marks, cracks and any other deformation which could affect its intended use.

3.4.2 Foreign matter. The components shall be free from all foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.2 Objective evidence. The contractor shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection procedures have not been given are satisfied.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction inspection

4.3.1 Sample. A preproduction sample of 150, of each component, shall be produced using the same methods, materials, equipment, and processes as will be used during regular production.

4.3.2 Inspection procedure.

4.3.2.1 For examination. The preproduction sample shall be inspected for all the requirements of the drawings and of this specification.

4.3.3 Acceptance/rejection criteria. The preproduction sample shall comply with the examinations and tests specified in 4.3.2 to be acceptable. The contractor shall obtain written approval from the contracting officer prior to proceeding with regular production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:34Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.3.1 Lotting. A lot shall consist of like components produced by one manufacturer, at one plant, from the same materials, under essentially the same manufacturing conditions.

4.2.2 Sampling. Sampling for examination shall be conducted in accordance with MIL-STD-105.

4.4.3 Inspection procedure.

4.4.3.1 For examination. Sample components shall be examined in accordance with the classification of defects (4.4.3.2) and MIL-STD-105.

4.4.3.2 Classification of defects.

(a) Bottom (Dwg 5-3-845, 5-3-836 and 5-3-844).

Categories		Defects
Critical:		None defined
Major:	AQL 0.65 percent defective	
*101		Inside diameter at lip incorrect
*102		Inside diameter below offset incorrect
103		Retainer incorrectly assembled or loose
104		Retainer holes diameter or location incorrect
*105		Inlet inside diameter incorrect
*106		Inlet rim height incorrect
*107		Depth (0.732) incorrect
108		Workmanship (3.4.1)
Minor:	AQL 1.0 percent defective	
*201		Overall depth (1-1/8) incorrect
202		Lip incorrect
203		Reinforcing ribs missing or incorrect
204		Marking missing, illegible, or incorrect
205		Protective finish incorrect or missing
	AQL 10 percent defective	
*206		Radii incorrect
207		Workmanship (3.4.2)

*To be checked prior to coating.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:34Z
Check the source to verify that this is the current version before use.

(b) Container (Dwg

Categories		Defects
Critical:		None defined
Major:	AQL 0.65 percent defective	
*101		Component missing or incorrectly assembled
102		Major diameter (2.335) incorrect
103		Minor diameter (2.275) incorrect
104		Thread pitch incorrect
105		Neck inside diameter (2.078) incorrect
106		Threads minimum effective length incorrect
*107		Body inside diameter (4.138) incorrect
108		Body depth before crimping (2-5/16) incorrect
109		Sorbent retainer support incorrectly formed
110		Workmanship (3.4.1)
111		Depth (0.906) incorrect
Minor:	AQL 1.0 percent defective	
201		Sorbent retainer support legs length or width incorrect
202		Height of threaded neck (0.62) incorrect
203		Outside diameter after crimping incorrect
204		Reinforcing embossments missing or incorrect
205		Protective finish incorrect or missing
206		Crimping incorrect
	AQL 10 percent defective	
207		Radii incorrect
208		Workmanship (3.4.2)

(c) Ring, filter (Dwg 5-3-558).

Categories		Defects
Critical:		None defined
Major:	AQL 0.65 percent defective	
*101		Diameter at lip incorrect
102		Burrs at top edge
103		Workmanship (3.4.1)

*To be checked prior to coating.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:34Z
Check the source to verify that this is the current version before use.

Cateogires	Defects
Minor:	AQL 1.0 percent defective
201	Section profile incorrect
202	Protective finish incorrect or missing
203	Workmanship (3.4.2)

(d) Ring, sealing (Dwg 5-3-822).

Categories	Defects
Critical:	None defined
Major:	AQL 0.65 percent defective
101	Thickness incorrect
102	Inside length (3-1/2) incorrect
103	Workmanship (3.4.2, grease, oil or solvents only)
104	Workmanship (3.4.1)
Minor:	AQL 1.0 percent defective
201	Workmanship (3.4.2, other than grease, oil or solvents)

(e) Retainer, sorbent, upper (Dwg 5-3-814, 5-3-810, 5-3-816, and 5-3-811).

Categories	Defects
Critical:	None defined
Major:	AQL 0.65 percent defective
101	Component missing or incorrectly assembled
102	Outside diameter incorrect
103	Disk or retainer element perforations incorrect
104	Burred side exposed
105	Reinforcing ribs incorrect
106	Workmanship (3.4.1)
Minor:	AQL 1.0 percent defective
201	Crimping incorrect
202	Workmanship (3.4.2)
203	Protective finish incorrect or missing

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:34Z
Check the source to verify that this is the current version before use.

(f) Cap, closure (Dwg 5-3-532).

Categories		Defects
Critical:		None defined
Major:	AQL 0.65 percent defective	
101		Gasket missing or incorrectly assembled
102		Workmanship (3.4.1)
103		Workmanship (3.4.2, grease, oil or solvents only) (see Dwg 5-2-607)
Minor:	AQL 1.5 percent defective	
201		Adhesive missing or incorrect
202		Workmanship (3.4.2, other than grease, oil or solvents)

(g) Cap, closure (Dwg 5-3-527).

Categories		Defects
Critical:		None defined
Major:	AQL 1.0 percent defective	
101		Thread major diameter (2.335)
102		Thread minor diameter (2.275)
103		Thread pitch incorrect
104		Ovality excessive
105		Workmanship (3.4.1)
Minor:	AQL 2.5 percent defective	
201		Overall outside diameter incorrect
202		Crown diameter (1-61/64) incorrect
203		Overall height incorrect
204		Lower flange incorrect
205		Depth to crown (1/8) incorrect
206		Protective finish missing or incorrect
	AQL 10 percent defective	
207		Radii incorrect
208		Workmanship (3.4.2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:34Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Industrial packaging. Canister components shall be industrially packaged in accordance with ASTM D 3951.

6. NOTES

6.1 Intended use. This specification covers the components that make up the M11 canister.

6.2 Ordering data. Procurement documents should specify the following:

(a) The title, number and date of this specification.
(b) Preproduction:

(1) Time allowed for contractor submission of samples for Government test and evaluation after award of contract.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the contractor whether or not to proceed with production.

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 4240-A808

☆ U.S. GOVERNMENT PRINTING OFFICE: 1984—705—040/A3349

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:34Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-10119C(EA)	CANISTER, M11; COMPONENTS FOR

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation.

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 EDITION OF 1 OCT 76 IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:34Z
Check the source to verify that this is the current version before use.