MIL-F-10117A
4 FEBRUARY 1953
SUPERSEDING
MIL-F-10117 (CMLC)
2 FEBRUARY 1950

MILITARY SPECIFICATION

FACEPIECE, COMBAT, M9

This specification has been approved by the Departments of the Army, the Navy, and the Air Force

1. SCOPE

1.1 **Scope.**—This specification covers a facepiece for use on protective masks.

1.2 **Classification.**

1.2.1 *Size.*—The facepieces covered by this specification shall be of the following sizes, as specified (see 6.2):

Small
Medium
Large.

1.2.2 *Canister mounting.*—The facepieces covered by this specification shall have the canister mounting on the right or left cheek as specified (see 6.2).

2. APPLICABLE SPECIFICATIONS, STANDARDS, DRAWINGS, AND PUBLICATIONS

2.1 The following specifications, standards, drawings, and publications, of the issue in effect on the date of invitation for bids, form a part of this specification:

SPECIFICATIONS

FEDERAL

NN-B-621—Boxes; Wood, Nailed and Lock-Corner.
UU-C-282—Chipboard; Plain.
LLL-B-631—Boxes; Fiber, Corrugated (For Domestic Shipment).

MILITARY

JAN-P-106—Packaging and Packing for Overseas Shipment—Boxes; Wood, Nailed.
JAN-P-108—Packaging and Packing for Overseas Shipment—Boxes; Fiberboard (V-Board and W-Board), Exterior and Interior.
MIL-P-116—Preservation, Methods of.
MIL-L-10547—Liners, Case, Waterproof.

U. S. ARMY

19-10—Fillers, Interior Packing, Fiberboard, Corrugated, Single and Double Faced (For General Packing Purposes).

NAVY DEPARTMENT

General Specifications for Inspection of Material.

STANDARDS

MILITARY

MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129—Marking of Shipments.

DRAWINGS

CHEMICAL CORPS

C5-2-758—Facepiece, Combat, M9—Bill of Material.
D5-22-47—Faceform, Gas Mask, M5 (For large and medium facepiece)—Assembly and Bill of Material.
D5-22-52—Faceform, Gas Mask, M5 (For small facepiece)—Assembly and Bill of Material.

PUBLICATIONS

CHEMICAL CORPS DIRECTIVES

100—Operation of the Inlet and Outlet Valve Resistance Indicator.
101—Operation of the Inlet and Outlet Valve Leakage Indicator, E3.
265—Directive for Testing Adhesion of Nosecup to Faceblank in Service Facepieces.
525—Operation of Indicator, Eyepiece Leakage, M2.

243034—53

FSC 4240

Source: https://assist.dla.mil -- Downloaded: 202610-17T13:33Z
Check the source to verify that this is the current version before use.

532—Directive for Pilot Lot Testing and Acceptance of Nosecup-To-Faceblank Assemblies.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.—All materials and components used in the manufacture and assembly of the facepiece shall conform to the specifications and drawings forming a part of this specification.

3.2 Manufacture and assembly.—The facepiece shall be manufactured and assembled as specified on Drawing C5-2-759 which is listed on Drawing C5-2-758.

3.3 Eyepiece assembly leakage.—The eyepiece assembly shall not leak when tested as specified in 4.4.1.

3.4 Outlet valve assembly resistance.—The outlet valve assembly shall show the necessary resistance when tested as specified in 4.4.2.

3.5 Outlet valve assembly leakage.—The outlet valve assembly shall not leak when tested as specified in 4.4.3.

3.6 Adhesion of nosecup to faceblank.—Adhesion of nosecup to faceblank shall be not less than 5 pounds when tested as specified in 4.4.4. Separation of either side of the nosecup from the faceblank shall not exceed one-half inch below the curled edge of the nosecup.

3.7 Workmanship.—All work shall be done in a neat and workmanlike manner.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Lot.—A lot shall consist of the quantity of facepieces manufactured from one lot of faceblanks, one lot of outlet valves, and one lot of nosecups. The inspection lot for nondestructive inspection, within the above limitations, shall be designated by the inspector. Prior to the start of production, a pilot lot of 100 nosecup-to-faceblank assemblies, cemented and vulcanized on the same equipment and in the same manner planned for regular production, shall be tested for compliance with the requirements of Directive 532. If the method of assembling nosecups to faceblanks under which the original pilot lot was accepted is modified, a new pilot lot shall be established prior to submitting further production for acceptance. Regular production pending approval of a pilot lot, will be at the risk of the manufacturer.

4.2 Sampling.

4.2.1 *For nondestructive inspection.*—Sampling for nondestructive inspection shall be conducted in accordance with the classification of defects (4.3.4) and Standard MIL-STD-105.

4.2.2 *For destructive test.*—Thirty-two representative samples, 16 for test and 16 for retest, shall be taken at random from each lot for testing as specified in 4.4.4 (see 6.3).

4.3 Inspection.

4.3.1 *Components.*—The inspector shall ascertain that all materials, components, or subassemblies of the facepieces covered by separate drawings, specifications, or standards are in accordance with the applicable drawings, specifications, or standards prior to final acceptance of the facepieces.

4.3.2 *Packaging, packing, and marking.*—The inspector shall inspect the packaging, packing, and marking of the facepiece for compliance with section 5.

4.3.3 *Procedures.*—For Navy purchases, the general inspection procedures shall be in accordance with General Specifications for Inspection of Material.

4.3.4 *Classification of defects.*—Inspection of the facepiece shall be conducted as follows:

4.3.4.1 *Facepiece, combat, M9—assembly.*—(Dwg. C5-2-759 which is listed on Dwg. C5-2-758).

Categories and defects	*Gage or other method of inspection*
Critical	
A. Eyepiece assembly leakage	4.4.1
B. Outlet valve assembly resistance	4.4.2
C. Outlet valve assembly leakage	4.4.3

AQL 1.0 percent

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:33Z
Check the source to verify that this is the current version before use.

Categories and defects	Gage or other method of inspection
Major	
1. Facepiece cut or damaged	Visual.
2. Component; missing, damaged, or improperly assembled.	Visual.
a. Eyering.	
b. Lens.	
c. Outlet valve assembly.	
d. Canister mounting.	
e. Neck strap.	
f. Nosecup assembly.	
g. Outlet valve cover, missing.	
3. Canister mounting, thread nonfunctioning.	B24-104-6.
4. Hardware, missing or inoperative	Visual and manual.
5. Permanent set	Visual.
6. Incorrect riveting of temple tabs	Visual.
7. Sharp edges on metal components	Tactual.
8. Lot number, marking incorrect	Visual.
9. Contamination (grease and oil)	Visual.
AQL 2.5 percent	
Minor	
51. Lot number marking, illegible or missing.	Visual.
52. Contamination (other than Major defect No. 9).	Visual.
53. Nosecup valve disc, missing or damaged.	Visual.
54. Nosecup valve assembly, damaged	Visual and manual.
55. Inadequate paint coverage	Visual.
56. Taping inadequate	Visual.
57. Outlet valve cover, damaged	Visual.
Incidental	
None.	

4.4 Tests.

4.4.1 *Eyepiece assembly leakage.*—The eyepiece assembly leakage shall be determined in accordance with Directive 525.

4.4.2 *Outlet valve assembly resistance.*—The outlet valve assembly resistance shall be determined in accordance with Directive 100.

4.4.3 *Outlet valve assembly leakage.*—The outlet valve assembly leakage shall be determined in accordance with Directive 101.

4.4.4 *Adhesion of nosecup to faceblank.*—Sixteen facepieces, taken as specified in 4.2.2, shall be tested in accordance with Directive 265. If more than one and less than five facepieces fail, the test shall be repeated using the 16 facepieces taken for this purpose. If, in the test plus the retest, five failures are observed, the lot represented shall be rejected.

5. PREPARATION FOR DELIVERY

5.1 Packaging.

5.1.1 *General.*—The contour of the facepiece shall be protected by inserting a faceform as specified on Drawings D5-22-47 or D5-22-52, as applicable. The chinpiece of the faceform shall rest in the interior chin portion of the facepiece and the brow piece support the brow portion. The head harness shall be neatly folded against the back of the faceform and the facepiece tied in a compact package.

5.1.2 *For shipment as spare parts.*—Two facepieces of one type and size, packaged as specified in 5.1.1, shall be further packaged in a style FOL fiberboard box of appropriate size and conforming to Specification JAN-P-108. The facepieces shall be separated by either a double-faced corrugated fiberboard spacer conforming to Specification 19-10 or a $\frac{1}{16}$-inch plain chipboard spacer conforming to Specification UU-C-282. The box shall be wrapped and sealed in conformance with method IA-2 of Specification MIL-P-116.

5.2 Packing.

5.2.1 *For shipment to assembly plants.*—A uniform number of facepieces of one type and size, packaged as specified in 5.1.1, shall be packed in a style RSC corrugated fiber box conforming to Specification LLL-B-631 for size of box and weight of contents. The box shall be fitted with a waterproof case liner conforming to Specification MIL-L-10547 and folded and sealed in accordance with appendix I thereto. A style 2, 2½, or 4 nailed wood box conforming to Specification NN-B-621 may be used as an alternate for the fiber box. The gross weight of the packed box shall not exceed 150 pounds.

5.2.2 *For shipment as spare parts.*—Ten fiberboard boxes, packaged as specified in 5.1.2, shall be packed in a style 2, 2½, or 4 nailed wood box of appropriate size and conforming to Specification JAN-P-106. The box shall be fitted with a waterproof case liner conforming to Specification MIL-L-10547 and folded and sealed in accordance with appendix I thereto. The box shall be strapped in accordance with appendix I to Specification JAN-P-106.

Source: https://assist.dla.mil -- Downloaded: 20261-17T13:33Z
Check the source to verify that this is the current version before use.

5.3 Marking.

5.3.1 *General.*—All packages and shipping containers shall be marked:

"CANISTER MOUNTING ON LEFT CHEEK"
OR
"CANISTER MOUNTING ON RIGHT CHEEK"

and the size, as applicable.

5.3.2 *Interior packages.*—Each interior package and each layer of overwrapping material used in the packaging shall have a permanent, water-proofed label or tag firmly affixed to the outside of the package and to each protective component, and marked in accordance with Standard MIL-STD-129.

5.3.3 *Shipping containers.*—In addition to any special marking required by the contract or order, all shipping containers shall be marked in accordance with Standard MIL-STD-129.

6. NOTES

6.1 Intended use.—The item covered by this specification is intended for use on gas masks with canister mounting on the right, or left cheek.

6.2 Ordering data.—Procurement documents should specify the following:

(a) The title, number, and date of this specification.

(b) The size of facepiece and location of canister mounting.

(c) Whether shipment to assembly plants or as spare parts is required.

6.3 Sampling and testing.—When the contractor consistently produces high quality material and operates under a system of quality control acceptable to the Government, the Government, at its discretion, may modify in whole or in part, the sampling and testing procedures specified herein. However, the Government reserves the right to return at any time, without previous notice to the contractor, to the sampling and testing procedures specified in this specification.

Notice.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodians:
Army—Chemical Corps
Navy—Bureau of Yards & Docks

Other interest:
Navy—Md.

Source: https://assist.dla.mil -- Downloaded: 20260-17T13:33Z
Check the source to verify that this is the current version before use.