MIL-H-0010120K(EA)
8 August 1983
SUPERSEDING
MIL-H-0010120J(EA)
30 June 1977
USED IN LIEU OF
MIL-H-10120E
30 September 1964

MILITARY SPECIFICATION

HEADHARNESS, C8R1

This limited coordination military specification has been prepared by the US Army Armament, Munitions and Chemical Command based upon currently available technical information, but it has not been approved for promulgation as a coordinated revision of Military Specification MIL-H-10129E. It is subject to modification. However, pending its promulgation as a coordinated military specification, it may be used in acquisition.

1. SCOPE

1.1 Scope. This specification covers one type of head harness for chemical-biological masks.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

: Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-TSC-S, Aberdeen Proving Ground, MD 21010 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 4240

Source: https://assist.dla.mil -- Downloaded: 202610-17T13:34Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

JJ-W-155 - Webbing, Textile, (Cotton, Elastic).

STANDARDS

FEDERAL

Fed. Std. No. 123 - Marking for Shipment (Civil Agencies).

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

US ARMY ARMAMENT, MUNITIONS AND CHEMICAL COMMAND

CHEMICAL RESEARCH AND DEVELOPMENT CENTER

D5-2-762 - Harness, Head, C8R1.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Materials and components. All materials and components cited on Drawing D5-2-762 and on the subsidiary drawings shall conform to the specifications thereon or the specific characteristics set forth on the drawings, except as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:34Z
Check the source to verify that this is the current version before use.

3.1.1 Elastic webbing. (JJ-W-155).

3.1.1.1 Initial tension. The initial tension shall be 1.65 pounds minimum and 3.25 pounds maximum in lieu of the tension values specified in table III of JJ-W-155.

3.1.1.2 Flexing. The webbing shall show no rupture of elastic threads nor more than 10 percent permanent set after flexing as specified in 4.4.4.1.

3.2 Manufacture and assembly. The head harness shall be manufactured and assembled in accordance with Drawing D5-2-762.

3.2.1 Pads. The inner and outer pads shall be evenly cut and shall coincide without wrinkles or puckers when stitched together with the elastic webbing between them.

3.2.2 Stitching. When stitching is not continuous thread, it shall be back-stitched no less than one-half inch. In sewing, the thread tension shall be properly maintained so that there will be no loose stitching, and the lock shall be embedded in the center of the sewn material.

3.2.3 Strap end clips. When attaching strap and clips, the elastic webbing shall be inserted the full depth of the clip. The pressure used in assembling the clips to the webbing shall not be sufficient to cut, break, or materially weaken the webbing. The clip shall form a smooth, flat, tight and compact assembly at the end of the webbing. The tightness of clinch assembly shall be tested in accordance with 4.4.4.2.

3.3 Preproduction. Prior to the start of regular production, a preproduction lot of head harnesses shall be produced for inspection (see 4.3).

3.4 Workmanship. The head harness shall be free from damage such as tears, rips, holes, or deformed clips, and foreign matter such as dirt, grease, or oil.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Contractor's responsibility. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202640-17T13:34Z
Check the source to verify that this is the currenversion before use.

4.1.2 Objective evidence. The contractor shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1, and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (4.3)
(b) Quality conformance inspection (see 4.4)

4.3 Preproduction inspection.

4.3.1 Sample.

4.3.1.1 For examination and nondestructive test. A preproduction sample of 25 head harnesses produced using the same methods, materials and equipment as will be used during regular production.

4.3.1.2 For destructive test. No less than 20 yards of webbing shall be submitted from each lot of webbing for testing in accordance with 4.4.4.

4.3.2 Inspection procedure.

4.3.2.1 For examination. 25 head harness samples shall be examined for all requirements of the drawings and of this specification.

4.3.2.2 For nondestructive tests. The strap end clip tightness shall be tested in accordance with 4.4.4.2. The acceptance number is zero.

4.3.2.3 For destructive tests. Sample webbing shall be tested in accordance with 4.4.4.1. The acceptance number is zero.

4.3.3 Acceptance/rejection criteria. The preproduction sample shall meet the examinations and tests specified by 4.3.2.1, 4.3.2.2, and 4.3.2.3 to be acceptable. The contractor shall obtain written approval from the contracting officer before proceeding with regular production.

4.4 Quality conformance inspection.

4.4.1 Lotting. A lot shall consist of the head harness offered for acceptance at one time, produced by one manufacturer, at one plant, under essentially the same manufacturing conditions. However, no more than one lot of elastic webbing shall be represented in any one lot of finished head harnesses.

Source: https://assist.dla.mil -- Downloaded: 202610-17T13:34Z
Check the source to verify that this is the currentversion before use.

4.4.2 Sampling.

4.4.2.1 For examination and nondestructive test. Sampling shall be conducted in accordance with MIL-STD-105. Sampling for strap end clip tightness test shall be conducted in accordance with MIL-STD-105, inspection level S-4.

4.4.2.2 For destructive tests. No less than 9 yards of webbing shall be submitted from each lot of webbing for testing in accordance with 4.4.4.

4.4.3 Inspection procedure.

4.4.3.1 For examination. Sample head harnesses shall be examined in accordance with the classification of defects and with MIL-STD-105.

4.4.3.2 For destructive test (4.4.4.2). The strap end clip tightness shall be tested in accordance with 4.4.4.2. The Acceptable Quality Level (AQL) shall be 1.0 percent defective.

4.4.3.3 For destructive tests. Sample webbing shall be tested in accordance with 4.4.4.1. The acceptance number is zero.

4.4.3.4 Classification of defects.

(a) Harness, head, C8R1 (Drawing D5-2-762).

Categories		Defects
Critical:		None defined
Major:	AQL	1.0 percent defective
101		Component missing
102		Sharp edges on metal components
103		Component incorrectly assembled
104		Workmanship (3.4)
105		Marking incorrect
106		Unraveling of serging stitch
Minor:	AQL	2.5 percent defective
201		Stitching incorrect (3.2.2)
202		Marking illegible
203		Pads incorrect (3.2.1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:34Z
Check the source to verify that this is the current version before use.

4.4.4 Tests. Tests shall be conducted as follows (see 6.3):

4.4.4.1 Flexing.

(a) Initial flexing. Three test specimens measuring 14 inches shall be cut from the webbing and marked so that a distance of 10 inches is between the gage marks. Hold each specimen horizontally on an apparatus equipped with a reciprocating arm arranged to transmit a direct horizontal elongation to the webbing and flex for 5,000 cycles at a rate of 45 to 60 cycles per minute, under a 50 percent elongation. Examine the specimen visually for compliance with 3.1.1.2 and determine permanent set after the sample has been released and allowed to rest for 10 minutes. The extension remaining shall be measured and expressed as a percentage of initial distance between the gage marks.

(b) Flexing after boiling water pre-treatment. Approximately 3 yards of webbing shall be subjected to boiling water pretreatment as specified in JJ-W-155. The samples shall then be marked and tested as specified in (a) above.

(c) Flexing after accelerated aging (oxygen bomb). Approximately 3 yards of webbing shall be subjected to accelerated aging in the presence of oxygen as specified in JJ-W-155. The samples shall then be marked and tested as specified in (a) above.

4.4.4.2 Strap end clip tightness. Grasp strap in one hand 1 inch from clip. Grasp clip in other hand and pull straight out till elasticity is removed from strap. Hold for 5 seconds. Slipping or pulling off the clip shall be evidence of looseness. Perform test on all six straps having clips. Looseness of any one of the clips on a head harness shall constitute a defective unit.

5. PACKAGING

5.1 Unit packing, packing, and marking, interplant shipment (see 6.6). The head harnesses shall be unit packed and packed to provide adequate protection from physical damage from the supply source to the first receiving activity for immediate use or further processing. Shipping containers shall be in compliance with the rules and regulations applicable to the mode of transportation. Marking shall be in conformance with Fed. Std. No. 123.

5.2 Repair part. When head harnesses are procured for storage and issue as a repair part, preservation, unit packing, packing, and marking shall be as specified on the packaging data sheet which is identified by the National Stock Number.

6. NOTES

6.1 Intended use. This head harness is intended for use as a component of the M9A1, ABC-M17, M17A1 and M17A2 chemical-biological masks.

Source: https://assist.dla.mil -- Downloaded: 202610-17T13:34Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Preproduction:

(1) Time allowed for contractor submission of samples for Government test and evaluation after award of contract.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the contractor whether or not to proceed with production.

6.3 Tests. It is suggested that destructive tests (see 4.4.4) on the webbing be conducted prior to manufacture of the head harness.

6.4 Toxicity. Any question raised regarding toxicity should be referred to the departmental medical authority. In the case of Army procurement, the Surgeon General will act as the advisor to the procuring agency.

6.5 International interest. Certain provisions of this specification are the subject of international standardization agreement (see Part 2, QSTAG List). When amendment, revision or cancellation of this specification is proposed which will affect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

6.6 Interplant shipments. Packaging for interplant shipment is for supplies and materials that do not enter the military supply system. Typical interplant shipments are shipments from a vendor to a subcontractor or a prime contractor, or from a subcontractor to a prime contractor, or from a vendor or contractor to a military arsenal or plant.

Custodians:

Army - EA

Preparing activity:

Army - EA

Project No. 4240-A795

Source: https://assist.dla.mil -- Downloaded: 202640-17T13:34Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:34Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
Armament Research and Development Center
US Army Armament, Munitions and Chemical Command
ATTN: DRSMC-TSC-S(A)
Aberdeen Proving Ground, MD 21010

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-17T13:34Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions -- Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-H-0010120K(EA)	HEADHARNESS, C8R1

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)* _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 EDITION OF 1 OCT 76 IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:34Z
Check the source to verify that this is the current version before use.