MILITARY SPECIFICATION

MOUNTING, CANISTER, GAS MASK

This amendment forms a part of Military Specification MIL-M-10156A, 24 June 1952, and has been approved by the Department of Defense for use of the Departments of the Army, the Navy, and the Air Force.

Page 2, paragraph 3.3.2: Delete in its entirety and substitute:

"3.3.2 *Air resistance.*—The air resistance of the assembled mounting shall not exceed 6 mm. of water when measured as a pressure drop with air flowing at 85 liters per minute (see 4.4.1)".

Page 2, paragraphs 4.3.4, 4.3.4.1 and 4.3.4.2: Delete and substitute:

4.3.4 *Classification of defects.*—Inspection of the mounting shall be conducted as follows:

4.3.4.1 *Mounting, canister — assembly.* — (Dwg. E5–2–535, which is listed on Dwg. E5–2–534)

Categories and defects		*Gage or other method of inspection*
Major A	AQL 0.25 percent	
1a.	Air resistance	4.4.1
Major	AQL 0.65 percent	
1.	Rolled thread, damaged or nonfunctioning.	E24–104–6 and IEA–D1–4–4.
2.	Clearance between socket and stud incorrect.	E24–17–5
3.	Component assembled incorrectly.	Visual
4.	Contamination (grease or oil).	Visual
Minor	AQL 1.0 percent	
51.	Air hole missing	Visual
52.	Finish missing, inadequate or incorrect.	Visual
53.	Outside diameter (2.516") incorrect.	Caliper
54.	Damage or deformation	Visual
55.	Height overall incorrect	E24–72–11
56.	Burrs or sharp edges	Tactual
57.	Contamination (other than Major Defect 4).	Visual
Incidental	None	

Custodians:
Army—Chemical Corps
Navy—Bureau of Yards and Docks.

311571—54—(107)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:37Z
Check the source to verify that this is the current version before use.