MIL-M-10156A
24 JUNE 1952
SUPERSEDING
MIL-M-10156(CmlC)
23 FEBRUARY 1950

MILITARY SPECIFICATION

MOUNTING, CANISTER, GAS MASK

This specification was approved by the Departments of the Army, the Navy, and the Air Force for use of procurement services of the respective Departments.

1. SCOPE

1.1 This specification covers a mounting for attaching a canister to a gas mask facepiece.

2. APPLICABLE SPECIFICATIONS, STANDARDS, DRAWINGS, AND PUBLICATIONS

2.1 The following specifications, standards, drawings, and publications of the issue in effect on date of invitation for bids, form a part of this specification.

SPECIFICATIONS

FEDERAL

LLL-B-631 —Boxes, Fiber, Corrugated (For Domestic Shipment).

MILITARY

JAN-P-106 —Packaging and Packing for Overseas Shipment—Boxes, Wood, Nailed.

JAN-P-120 —Packaging and Packing for Overseas Shipment — Cartons, Folding, Paperboard.

MIL-A-140 —Adhesive, Water-Resistant, Waterproof Barrier Material.

MIL-L-10547 — Liners, Case, Waterproof.

MIL-C-10116 —Canister, Combat, M11.

NAVY DEPARTMENT

General Specifications for Inspection of Material.

STANDARDS

MILITARY

MIL-STD-105 — Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-129 —Marking of Shipments.

DRAWINGS

CHEMICAL CORPS

E5-2-534 — Mounting, Canister — Bill of Material.

PUBLICATIONS

CHEMICAL CORPS DIRECTIVE

100 — Operation of the Inlet and Outlet Valve Resistance Indicator.

(Copies of specifications, standards, drawings, and publications, required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.—All materials used in the manufacture and assembly of the mounting shall conform to the specifications and drawings forming a part of this specification.

3.2 Manufacture.—The mounting shall be manufactured as specified on Drawing E5-2-535 and subsidiary drawings listed on Drawing E5-2-534.

3.3 Assembly.

3.3.1 *Inlet valve disk.*—The inlet valve disk shall be mounted as specified on Drawing

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:37Z
Check the source to verify that this is the current version before use.

E5–2–535. The deflected valve disk shall make a smooth and even contact over its entire outside edge with the concave surface of the valve seat. The valve disk shall be sufficiently free in the snap fastener so that when gripped by the fingers at various points around the periphery, stretched radially for approximately one-quarter inch, and released, it returns to its original shape and makes a smooth and even contact over its entire outside edge with the concave surface of the valve seat.

3.3.2 *Air resistance.*—The air resistance of the assembled mounting shall not exceed 6 millimeters (mm.) of water when tested as specified in 4.4.

3.4 Workmanship.—All work shall be done in a neat and workmanlike manner.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Lot.—A lot shall consist of the mountings produced by one manufacturer, from the same materials, and under essentially the same manufacturing conditions. The inspection lot for nondestructive inspection, within the above limitations, shall be designated by the inspector.

4.2 Sampling for nondestructive inspection. —Sampling for nondestructive inspection shall be conducted in accordance with the authorized classification of defects (4.3.4) and Standard MIL–STD–105.

4.3 Inspection.

4.3.1 *Components.*—The inspector shall ascertain that, prior to assembly, all materials, components, or subassemblies of the mounting procured under separate specifications or drawings have been inspected, tested, and accepted in accordance with their respective specifications or drawings.

4.3.2 *Packaging, packing, and marking.*—The inspector shall inspect the packaging, packing, and marking of the mounting for compliance with section 5.

4.3.3 *Procedures.*—For Naval purchases, general inspection procedures shall be in accordance with General Specifications for Inspection of Material.

4.3.4 *Classification of defects.*—Inspection of the mounting shall be conducted as follows:

4.3.4.1 *Mounting, canister.*—(Dwg. E5–2–536, which is listed on Dwg. E5–2–534)

Categories and defects	*Gage or other method of inspection*
Major AQL 0.65 percent	
1. Rolled thread, major and minor diameter.	B24–104–6.
Minor AQL 1.0 percent	
51. Hole diameter (.120") incorrect	Drill rod.
52. Air hole missing	Visual.
53. Coating missing, inadequate or incorrect.	Visual.
54. Outside diameter (2.516") incorrect	Caliper.
55. Damage or deformation	Visual.
56. Height overall incorrect	Caliper.
57. Burrs or sharp edges	Tactual.
Incidental	
None	

4.3.4.2 *Mounting, canister—assembly.*—(Dwg. E5–2–535, which is listed on Dwg. E5–2–534)

Categories and defects	*Gage or other method of inspection*
Major A AQL 0.1 percent	
1a. Air resistance	4.4.1.
Major AQL 0.65 percent	
1. Rolled thread, major and minor diameter.	B24–104–6.
2. Clearance between socket and stud incorrect.	E24–17–5.
3. Component assembled incorrectly	Visual.
Minor AQL 1.0 percent	
51. Coating marred or metal exposed	Visual.
52. Damage or deformation	Visual.
53. Burrs or sharp edges	Tactual.
Incidental	
None	

Source: https://assist.dla.mil -- Downloaded: 202610-17T13:37Z
Check the source to verify that this is the current version before use.

4.4.1 *Air resistance test.*—The air resistance of the completely assembled inlet valve disk and mounting shall be measured in accordance with Directive 100 (see 6.2).

5. PREPARATION FOR DELIVERY

5.1 Packaging.

5.1.1 *For shipment as spare parts.*—Five mountings shall be packaged in a paperboard folding carton conforming to Specification JAN–P–120.

5.2 Packing.

5.2.1 *For shipment to assembly plants.*—A uniform number of mountings shall be packed in a corrugated fiberboard box conforming to Specification LLL–B–631. The gross weight of the box shall not exceed 150 pounds.

5.2.2 *For shipment as spare parts.*—Fifty cartons (5.1.1) shall be packed in a style 2, 2½, or 4 nailed wood box conforming to Specification JAN–P–106, the gross weight of which shall not exceed 70 pounds. Each box shall be fitted with a case liner conforming to Specification MIL–L–10547. The liner shall be sealed with adhesive conforming to Specification MIL–A–140. The box shall be bound, not less than one week prior to shipment, with two bands of nailless metal strapping or wire in accordance with Specification JAN–P–106, appendix I.

5.3 Marking.—In addition to any special marking required by the contract or order, all shipping containers shall be marked in accordance with Standard MIL–STD–129.

6. NOTES

6.1 **Ordering data.** — Procurement documents should specify the following:

(a) The title, number, and date of this specification.

(b) The type of packing required.

6.2 Valve disk.—Valve disks required for the resistance test will be furnished manufacturers on request.

Notice.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodians:
Army—Chemical Corps
Navy—Bureau of Yards and Docks.

Source: https://assist.dla.mil -- Downloaded: 202640-17T13:37Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:37Z
Check the source to verify that this is the current version before use.