MIL-M-00120156B(MU)
30 July 1970
USED IN LIEU OF
MIL-M-10156A
6 August 1954

MILITARY SPECIFICATION

MOUNTING, CANISTER, GAS MASK

This limited coordination Military specification has been prepared by Edgewood Arsenal based upon currently available technical information, but it has not been approved for promulgation as a coordinated revision of Military Specification MIL-M-10156A. It is subject to modification. However, pending its promulgation as a coordinated Military specification, it may be used in procurement.

1. SCOPE

1.1 This specification covers a gas mask canister mounting.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

DRAWINGS

US ARMY MUNITIONS COMMAND

EDGEWOOD ARSENAL

B5-2-535 - Mounting, Canister.
C38-6-327-12 - Q106 Inlet and Outlet Valve Resistance Indicator.
D150-2-1 - Marking Diagram for Shipping Containers.

FSC 4240

Source: https://assist.dla.mil -- Downloaded: 202640-17T13:37Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by the suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies of these ratings, rules and regulations should be addressed to Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

AMERICAN TRUCKING ASSOCIATIONS, INC.

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., 1616 P Street, N. W., Washington, D. C. 20036.)

3. REQUIREMENTS

3.1 Material. All materials used in the manufacture and assembly of the mounting shall conform to the specifications and drawings forming a part of this specification.

3.2 Manufacture. The mounting shall be manufactured as specified on Drawing B5-2-535 and subsidiary drawings listed thereon.

3.3 Assembly.

3.3.1 Inlet valve disk. The inlet valve disk shall be mounted as specified on Drawing B5-2-535. The deflected valve disk shall make a smooth and even contact over its entire outside edge with the concave surface of the valve seat. The valve disk shall be sufficiently free in the snap fastener so that when gripped by the fingers at various points around the periphery, stretched radially for approximately one-quarter inch, and released, it returns to its original shape and makes a smooth and even contact over its entire outside edge with the concave surface of the valve seat.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:37Z
Check the source to verify that this is the current version before use.

3.3.2 Airflow resistance. The airflow resistance of the assembled mounting shall not exceed 6 millimeters of water at an airflow rate of 85 liters per minute when tested as specified in 4.4.4.1.

3.4 Workmanship. The canister mounting shall be free from contamination (grease, oil, or foreign matter) and damage such as permanent set of valve disk, cracks, dents, burrs, sharp edges, and distortion of metal parts. Valve seat and threads shall be free of cement.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Quality conformance inspection.

4.2.1 Lotting. A lot shall consist of the mountings produced by one manufacturer, from the same materials, and under essentially the same manufacturing conditions, however, no lot of canister mountings shall contain more than one lot of inlet valve discs.

4.2.2 Sampling.

4.2.2.1 For examination and tests. Sampling shall be conducted in accordance with MIL-STD-105.

4.4.3 Inspection procedure.

4.4.3.1 For examination and tests. Sample mountings shall be examined and tested in accordance with the classification of defects and MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 202610-17T13:37Z
Check the source to verify that this is the currentversion before use.

4.4.3.2 Classification of defects.

(a) Mounting, canister (Dwg B5-2-535 and Dwg B5-2-536).

Categories	Defects	Acceptance standards
Critical:	None defined	
Major:	AQL 0.25 percent defective	
101	Airflow resistance	4.4.4.1
	AQL 1.0 percent defective	
102	Major diameter	
103	Minor diameter	
104	Rolled thread damaged or nonfunctioning	
105	Clearance between socket and stud incorrect	
106	Components missing or incorrectly assembled	
107	Workmanship (see 3.4)	
Minor:	AQL 2.5 percent defective	
201	Marking incorrect	
202	Finish missing, incorrect, or inadequate	
203	Overall height	

4.4.4 Tests.

4.4.4.1 Airflow resistance. Airflow resistance of the mounting shall be determined with the Q106 Inlet and Outlet Valve Resistance Indicator (C38-6-327-12).

5. PREPARATION FOR DELIVERY

5.1 Packaging, level C. Mountings shall be packaged to provide adequate protection against corrosion, moisture, dust, fungus, deterioration, and damage from the supply source to the first receiving activity for immediate use.

5.2 Packing, level C. Mountings, packaged as specified in 5.1, shall be packed to insure carrier acceptance and safe delivery to the first domestic destination. Shipping containers shall be in compliance with

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:37Z
Check the source to verify that this is the current version before use.

Uniform Freight Classification Rules or National Motor Freight Classification Rules.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages shall be marked in accordance with MIL-STD-129. Shipping containers shall be marked in accordance with drawing D150-2-1.

5.4 Repair parts. When this item is procured for storage and issue as a repair part, preservation, packaging, packing, and marking shall be as specified on the packaging data sheet which is identified by the Federal Stock Number.

6. NOTES

6.1 Intended use. The mounting covered by this specification is intended for use in the M9 Facepiece with a canister mounting on the right or left cheek.

6.2 Ordering data. Procurement documents should specify the title, number, and date of this specification.

Custodian:

Army - MU

Preparing activity:

Army - MU(EA)

Project Number 4240-A425

Source: https://assist.dla.mil -- Downloaded: 202610-17T13:37Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:37Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO (If "Yes", in what way?)

4. REMARKS (Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)

SUBMITTED BY (Printed or typed name and activity - Optional)

DATE

DD FORM 1426

Source: https://assist.dla.mil -- Downloaded: 202610-17T13:37Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding Officer
Edgewood Arsenal
ATTN: SMUEA-QAES
Edgewood Arsenal, Maryland 21010

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:37Z
Check the source to verify that this is the current version before use.