MIL-P-10129A(MU)
19 March 1970
SUPERSEDING
MIL-P-10129(CmlC)
8 February 1950

MILITARY SPECIFICATION

PLUG, AIR INLET

1. SCOPE

1.1 This specification covers one type of canister air-inlet plug.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

STANDARDS

FEDERAL

FED-STD-601 - Rubber; Sampling and Testing.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

DRAWINGS

US ARMY MUNITIONS COMMAND

EDGEWOOD ARSENAL

B5-3-771 - Plug, Air Inlet.
D150-2-1 - Marking Diagram for Shipping Containers.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:35Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies of this publication should be addressed to Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

AMERICAN TRUCKING ASSOCIATIONS, INC.

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., 1616 P Street, N. W., Washington, D. C. 20036.)

3. REQUIREMENTS

3.1 Material. A synthetic or reclaimed rubber formulation may be used in the manufacture of the plug.

3.2 Manufacture. The plug shall be manufactured as shown on Dwg. C5-3-533 by the conventional process of molding under heat and pressure. Ten test slabs, 6 by 6 by 0.075 + 0.01 inches, shall be made from the stock used for each production lot. The slabs shall have a cure equivalent to that of the production plugs.

3.3 Physical properties.

3.3.1 Tensile strength. The average tensile strength shall be not less than 1600 p.s.i. when tested as specified in 4.2.4.2.

3.3.2 Ultimate elongation. The average ultimate elongation shall be not less than 600 percent when tested as specified in 4.2.4.3.

3.3.3 Tear resistance. The average tear resistance shall be not less than 165 pounds per inch when tested as specified in 4.2.4.4.

3.3.4 Hardness. The average hardness, as measured on the Shore durometer, shall be between 47 and 52 inclusive when tested as specified in 4.2.4.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:35Z
Check the source to verify that this is the current version before use.

3.4 Workmanship. The plug's outer surfaces shall be free from porous areas, cracks, checks, cuts, abrasions, blisters, or any defect that would adversely affect either the serviceability or the effectiveness of the finished plug. The plug shall be compact and free from bubbles and foreign matter. Ridges of mold parting lines, when closely trimmed, shall not be considered as defects.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5, for which specific inspection has not been provided in this specification, have been satisfied.

4.2 Quality conformance inspection.

4.2.1 Lotting. A lot shall consist of the plugs produced by one manufacturer, from the same material, and under essentially the same manufacturing conditions.

4.2.2 Sampling.

4.2.2.1 For examination. Sampling shall be conducted in accordance with MIL-STD-105.

4.2.2.2 For tests. The ten test slabs; prepared in accordance with 3.2, shall be submitted with each lot of plugs.

4.2.3 Inspection procedure.

4.2.3.1 For examination. Sample plugs shall be examined in accordance with the classification of defects and MIL-STD-105.

4.2.3.2 For tests. Specimens, taken at random from the test slabs (see 3.2), shall be tested as specified in 4.2.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:35Z
Check the source to verify that this is the current version before use.

4.2.3.3 Classification of defects.

(a) Plug, air inlet (C5-3-533).

Categories		Defects
Critical:	None defined	
Major:	AQL 0.65 percent defective	
101		Functional diameter (.970) incorrect
102		Damage
Minor:	AQL 1.0 percent defective	
201		Hole in tab missing
202		Diameter of tab incorrect
203		Outside diameter of flange incorrect
204		Thickness of plug at functional diameter incorrect
205		Knurling missing
206		Radius underside of plug missing
	AQL 10.0 percent defective	
207		Contamination
208		Workmanship (3.4)

4.2.4 Tests.

4.2.4.1 Test specimens. Thirty test specimens shall be died from the slabs as specified in FED-STD-601. No specimen shall be buffed or stretched before testing. The specimens shall be aged for 24 hours before testing. Ten specimens shall be tested for each requirement. Ten hardness tests shall be made on portions of test slabs left after dieing out specimens.

4.2.4.2 Tensile strength. Tensile strength shall be determined as specified by Method 4111 of FED-STD-601.

4.2.4.3 Ultimate elongation. Ultimate elongation shall be determined as specified by Method 4121 of FED-STD-601.

4.2.4.4 Tear resistance. Tear resistance shall be determined as specified by Method 4211 of FED-STD-601.

4.2.4.5 Hardness. Hardness shall be determined as specified by Method 3021 of FED-STD-601.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:35Z
Check the source to verify that this is the current version before use.

4.2.5 Acceptance/rejection criteria. In case any test fails the physical properties requirements, a retest shall be made using 20 specimens for each test. In case of failure on the retest, the lot represented shall be rejected.

5. PREPARATION FOR DELIVERY

5.1 Packaging, level C. The plugs shall be packaged to provide adequate protection against corrosion, moisture, dust, fungus, deterioration, and damage from the supply source to the first receiving activity for immediate use.

5.2 Packing, level C. Plugs, packaged as specified in 5.1, shall be packed to insure carrier acceptance and safe delivery to the first domestic destination. Shipping containers shall be in compliance with Uniform Freight Classification or National Motor Freight Classification Rules.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages shall be marked in accordance with MIL-STD-129. Shipping containers shall be marked in accordance with Dwg. D150-2-1.

5.4 Repair parts. When this item is procured for storage and issue as a repair part, preservation, packaging, packing, and marking shall be specified on the repair part packaging data sheet which is identified by the Federal Stock Number for the repair part.

6. NOTES

6.1 Intended use. The plug covered by this specification is intended to be used with the M11 Canister to close the air inlet of the canister when not in use.

6.2 Ordering data. Procurement documents should specify the title, number, and date of this specification.

Custodian:

Army - MU

Preparing activity:

Army - MU(EA)

Project Number 4240-A416

☆U.S. GOVERNMENT PRINTING OFFICE: 1970-393-096/S5440

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:35Z
Check the source to verify that this is the current version before use.