MIL-V-10134C
14 MARCH 1963
SUPERSEDING
MIL-V-10134B
26 DECEMBER 1956

MILITARY SPECIFICATION

VALVE, OUTLET, PROTECTIVE MASK, C15

This specification has been approved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy, and the Air Force.

1. SCOPE

1.1 This specification covers one type of protective mask outlet valve.

2. APPLICABLE DOCUMENTS

2.1 **Government documents.** The following documents, of the issue in effect on date of invitation for bids, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105 — Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-129 — Marking for Shipment and Storage

DRAWINGS

CBR AGENCY

B5-2-597 — Valve, Outlet, C15—Assembly and Bill of Material

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 **Other publications.** The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification Rules

(Application for copies of these uniform classification rules should be addressed to the Uniform Classification Committee, 202 Union Station, Chicago 6, Ill.)

3. REQUIREMENTS

3.1 **Materials and components.** All materials and components shall conform to the specifications and drawings forming a part of this specification.

3.2 **Manufacture and assembly.** The outlet valve shall be manufactured and assembled as specified on Drawing B5-2-597.

3.3 **Resistance to airflow.** The assembled outlet valve shall have a resistance not exceeding a pressure differential of 22 millimeters of water, at an airflow rate of 85 liters per minute, when tested as specified in 4.7.1.

3.4 **Leakage.** Leakage through the assem-

FSC 4240

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:36Z
Check the source to verify that this is the current version before use.

bled outlet valve shall not exceed 15 milliliters of air per minute, at a pressure differential of 25 millimeters of water, when tested as specified in 4.7.2.

3.5 Preproduction sample. Prior to the start of regular production, a sample of 10 outlet valve assemblies shall be produced using the same methods, materials, and equipment as will be used during regular production. Any change in materials or operating conditions shall require a new preproduction sample.

3.6 Workmanship. The outlet valve asembly shall be free from contamination (foreign matter) and damage, such as distortion, dents, roughened valve seat, and torn disc that would impair its function.

4. QUALITY ASSURANCE PROVISIONS

4.1 Supplier's responsibility. The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 *Government's responsibility.* The Government will be responsible for the performance of the inspection set forth in 4.3. Samples shall be forwarded to the laboratory designated by the contracting officer.

4.2 Special provisions.

4.2.1 *Alternative inspection (including testing) procedures.* The supplier may utilize any alternative inspection procedure which will insure equal or better quality by submitting a written proposal with justification and obtaining written approval from the Government prior to instituting the procedure. In case of dispute, the procedures of this specification will govern.

4.2.2 *Objective evidence.* The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 have been satisfied.

4.3 Preproduction sample inspection.

4.3.1 *Examination.* The sample outlet valve assemblies shall be inspected for all requirements of the drawings and this specification.

4.3.2 *Tests.* The sample outlet valve assemblies shall be tested in accordance with paragraph 4.7.

4.3.3 *Acceptance/rejection criteria.* The preproduction sample shall meet the examination and tests specified by 4.3.1 and 4.3.2 to be acceptable. The supplier shall obtain written approval from the contracting officer before proceeding with regular production.

4.4 Lotting. A lot shall consist of the valves offered for acceptance at one time, which have been produced by one manufacturer, under essentially the same manufacturing conditions. No more than one lot of valve discs shall be included in each lot of valve assemblies.

4.5 Sampling for nondestructive examination. Sampling shall be conducted in accordance with MIL–STD–105.

4.6 Examination. Sample outlet valves shall be examined in accordance with the classification of defects and with MIL–STD–105.

4.6.1 *Classification of defects.*

4.6.1.1 *Outlet valve, C15, assembly (Dwg. B5–2–579).*

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:36Z
Check the source to verify that this is the current version before use.

Categories	Defects	Acceptance standards
Critical:		
1	Leakage	4.7.2
Major:	AQL 0.65 percent defective	
101	Component missing	
102	Damage	
103	Contamination (grease or oil)	
Minor:	AQL 2.5 percent defective	
201	Stem trimmed incorrectly	
202	Color incorrect	
Major A:	AQL 0.25 percent defective	
301	Resistance to air flow	4.7.1

* Each item in the lot shall be examined for critical defects.

4.7 **Tests.**

4.7.1 *Resistance to airflow.* The resistance to airflow of the C15 outlet valve shall be determined using the E3 Inlet and Outlet Valve Resistance Indicator.

4.7.2 *Leakage.* The C15 outlet valve shall be tested for leakage using the M4 Outlet Valve Leakage Indicator.

5. PREPARATION FOR DELIVERY (see 6.3).

5.1 **Packaging, level C.** The outlet valves shall be packaged in accordance with the manufacturer's commercial practice, suitable for shipment from the supply source to the first receiving activity for immediate use.

5.2 **Packing, level C.** Outlet valves, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at first domestic destination for immediate use. Containers shall be in accordance with Uniform Freight Classification Rules or regulations of other carriers applicable to the mode of transportation.

5.3 **Marking.** In addition to any special marking required by the contract or order, unit and intermediate packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 **Intended use.** The item covered by this specification is an outlet valve, intended for use with protective masks.

6.2 **Ordering data.** Procurement documents should specify the title, number, and date of this specification.

6.3 **Packaging and packing levels.** When other than level C packaging and packing is desired for components authorized for stocking as repair parts, the repair parts data sheet covering the C15 Outlet Valve should be used.

(Copies of repair parts data sheets may be obtained from the Commanding Officer, U. S. Army, CBR Engineering Group, ATTN: Chief, Design Division, Army Chemical Center, Maryland.)

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation; or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

Custodians:

Army—MU

Navy—Ships

Preparing activity:

Army—MU

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:36Z
Check the source to verify that this is the current version before use.