MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, SUPERMETALLIZED PLASTIC FILM DIELECTRIC, DIRECT CURRENT, FOR LOW ENERGY, HIGH IMPEDANCE APPLICATIONS, HERMETICALLY SEALED IN METAL CASES, HIGH RELIABILITY, STYLES CHS01, CHS02, AND CHS03

This amendment forms a part of MIL-C-87217/1, dated 11 March 1985, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 7

Seal, delete and substitute:

"Seal: Method 112, MIL-STD-202, test condition C, procedure IIIa, followed by test condition A with the exception of the following:

lbf/in^2	Exposure time hours	Maximum dwell hours	R_1 Reject limit ($atm\ cm^3/s$)
45 ±5	1 +1-0	1	1×10^{-6}

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR, MI
Navy - AS, CG, MC, OS, SH
Air Force - 17, 19
DLA - ES

Preparing activity:
DLA -ES

(Project 5910-1903)

DISTRIBUTION STATEMENT A. Approved for public release; distibution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:20Z
Check the source to verify that this is the current version before use.