FED. SUP CLASS
4930



NOTES:
1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is ± .031 inch.
3. Material: Steel.
4. Heat treatment: Case harden to a depth of not less than .005 inch.
5. Finish for steel that is not corrosion resistant shall be in accordance with QQ-P-416, Class 2, Type II, or QQ-Z-325, Type II, Class 2.
6. Reference documents shall be of the issue in effect on date of invitations for bid or request for proposal.
7. For design feature purposes, this standard takes precedence over procurement documents referenced herein.

Ⓑ ENTIRE STANDARD REVISED

P.A. ARMY-ME Other Cust NAVY-YD AIR FORCE-99	TITLE Coupling, grease gun; flush type nozzle	MILITARY STANDARD MS 24205
PROCUREMENT SPECIFICATIONS MIL-L-4387	SUPERSEDES:	PAGE 1 OF 1

DD FORM 1 SEP 57 672-1 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE. 4930-0276

APPROVED 27 JULY 1954 REVISED Ⓐ 29 AUGUST 1966 Ⓑ 21 APRIL 1977

User activities:
Army - AT
Navy - SH

Review activity:
DLA - CS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document, when applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:50Z
Check the source to verify that this is the current version before use.