REVIEW INTEREST: DCSC, 69

USER INTEREST: YD, AT.AC

FED. SUP CLASS
2805





Ⓑ CANCELED AFTER 23 February 1982
NO SUPERSEDING STANDARD.



SECTION A-A



SECTION B-B

NOTES:

1. MATERIAL: COPPER-LEAD LINING. S.A.E. NO. 49 ON STEEL, S.A.E. NO. 1008, OR 1010
2. PLATING: LEAD-TIN PLATE I.D. (6% MIN. TIN) TO A THICKNESS .001 NOMINAL. FLASH-TIN PLATE ALL OVER AFTER LEAD-TIN PLATE.
3. IN 1.6875 DIA. INSPECTION BLOCK WITH ONE PARTING LINE FACE AGAINST A STOP AT HORIZONTAL CENTER LINE OF BLOCK AND A PRESSURE OF 1260 LBS. ON OTHER P.L. FACE, HEIGHT WILL BE .84475 - .84575 ON SIDE OPPOSITE STOP.
4. REMOVE ALL BURRS.
5. MS PART NUMBER AND PART MANUFACTURER'S IDENTIFICATION TO BE CLEARLY MARKED WITHOUT INTERFERING WITH THE FUNCTION OF THE PART.
6. TOLERANCES: UNLESS OTHERWISE SPECIFIED, LINEAR MACHINED DIMENSIONS ±.010: ANGULAR MACHINED DIMENSIONS ±30'. DO NOT SCALE DRAWING.
7. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.
8. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.
9. ALL DIMENSIONS IN INCHES.

APPROVED 26 JAN 1955 REVISED Ⓐ 15 DEC 1965 Ⓑ 23 FEB 1982

Ⓐ ENTIRE STANDARD REVISED

PART NO. MS 13834-1

P.A. MO (ERDL)
Other Cust
A.F. - 60
NAVY - YD

TITLE
BEARING, SLEEVE: ENGINE, PLAIN, 1-9/16" X 1"

MILITARY STANDARD
MS 13834

PROCUREMENT SPECIFICATION
MIL-E-11275

SUPERSEDES:

SHEET 1 OF 1

DD FORM 672-4

This Military Standard has been approved by the Department of Defense and is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:29Z
Check the source to verify that this is the current version before use.