FED. SUP CLASS
6685



FRONT-WHITE COATED SIDE

HUMIDITY-INDICATING COLOR COMPARISON CHART

INDICATOR PLUGS WHOSE COLOR HAS FADED BEYOND THE "SAFE" MARGIN HAVE LOST THEIR DEHYDRATING PROPERTY AND SHALL NOT BE USED.

MFRS. NAME MFRS. ADDRESS

REVERSE SIDE

DASH NO.
-1

NOTES:

1. "SAFE" AND "UNSAFE" TO BE 14-PT. TYPE, ALL CAPS, ON FRONT SIDE. "SAFE" TO BE PRINTED IN SHADE A, "UNSAFE" IN RED.
2. SHADES A, B, C, AND D TO BE IN ACCORDANCE WITH THE COLORS SHOWN ON CHART MS16188.
3. MATERIAL TO BE 4-PLY ONE SIDE WHITE-COATED CARDBOARD, FULL-SIZE SHEET 22 BY 28, 500 SHEETS PER REAM, FULL REAM WEIGHING 210 POUNDS.
4. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: FRACTIONS ±1/32.

APPROVED 15 Jul 69 REVISED

P.A. NAVY – AS Other Cust AF - 82 ARMY - ME	TITLE CARD-HUMIDITY-INDICATING COLOR COMPARISON	MILITARY STANDARD MS 3398
PROCUREMENT SPECIFICATION NONE	SUPERSEDES: AN7514	SHEET 1 OF 1

DD FORM 1 SEP 67 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

PLATE NO. 17709

USER SYMBOLS:

REVIEWER SYMBOLS:

"Review/user information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS."

This military standard is mandatory for use by all Departments & Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:04Z
Check the source to verify that this is the current version before use.