INCH-POUND

MIL-DTL-3628/2G
20 August 2002
SUPERSEDING
MIL-DTL-3628/2F
15 November 1996

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, DISTINGUISHED PISTOL SHOT, ARMY; PENDANT AND SUSPENSION BAR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-3628.



MATERIAL:

PENDANT AND SUSPENSION BAR: Red Brass
TARGET: Gilding Metal

FINISH:

PENDANT AND SUSPENSION BAR: Gold Plated, Rose Gold Plated, Matte Finished, Highlights and Rim Polished, and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 20.
TARGET: Hard Enameled, Gold Plated, Mirror-like Polished, and shall match TIOH Metal Finish Chip Number 6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:43Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

HEIGHT (overall):
ASSEMBLED: 2-43/64 inches (REF)
PENDANT: 1-1/4 inches (REF)
SUSPENSION BAR: 15/32 inch (REF)
TARGET: 17/32 inch (REF)

WIDTH (overall):
PENDANT: 1-3/64 inches (REF)
SUSPENSION BAR (including balls): 1-1/2 inches (REF)
TARGET: 15/32 inch (REF)

THICKNESS (at rim):
PENDANT: 0.086 inch ± 0.005 inch
SUSPENSION BAR: 0.070 inch ± 0.005 inch
TARGET: 0.035 inch ± 0.002 inch

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Enameled areas shall be as indicated. Color shall conform to TIOH Hard Enamel Color Chip Numbers listed below:

COLOR	CHIP NUMBER
Black	26
White	28

3. Piercing shall be as indicated.

4. Lugs shall be fabricated from gold plated wire with a nominal diameter of 0.050 inch. The overall diameter of the lugs shall be 3/16 inch ± 1/64 inch. Lugs shall be hard soldered to the pendant bar 19/32 inch ± 1/64 inch on centers. As an alternate method, lugs may be cut into the working die.

5. Links (jump rings) shall be fabricated from gold plated wire with a nominal diameter of 0.050 inch. The links shall have an outside diameter of 3/16 inch + 1/32 inch - 0 inch.

6. Two brass balls 0.105 inch in diameter shall be soldered to the sides of the suspension bar as shown. As an alternate method, the balls may be an integral part of the suspension bar and may be cut into the contractor's working die.

7. The target shall be superimposed on the pendant and shall be secured by means of two solid brass rivets.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:43Z
Check the source to verify that this is the current version before use.

8. The attaching device shall be prong and clutch type. Two prongs shall be located on the horizontal center line of the suspension bar equidistant from each end and 1-5/16 inch ± 1/64 inch apart.

9. A forcer may be used to bring up the design of the shield on the suspension bar.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0099/002)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:43Z
Check the source to verify that this is the current version before use.