NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/2L
16 February 2021
SUPERSEDING
MIL-DTL-3628/2K
21 April 2016

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, DISTINGUISHED PISTOL SHOT, ARMY; PENDANT AND SUSPENSION BAR

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.



MATERIAL:
PENDANT, TARGET AND SUSPENSION BAR: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH:
PENDANT AND SUSPENSION BAR: 24K Gold Plated, Matte Finished, Polished Highlights and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 8.
TARGET: Hard Enameled, 24K Gold Plated, Mirror-like Polished, and shall match TIOH Metal Finish Chip Number 6.

DIMENSIONS:
HEIGHT (Overall):
PENDANT: 1-1/4 inches (REF)
SUSPENSION BAR: 15/32 inch (REF)
TARGET: 17/32 inch (REF)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:43Z
Check the source to verify that this is the current version before use.

WIDTH (Overall):
PENDANT: 1-3/64 inches (REF)
SUSPENSION BAR (Including balls): 1-1/2 inches (REF)
TARGET: 15/32 inch (REF)
THICKNESS (At rim):
PENDANT: 0.086 inch ± 0.005 inch
SUSPENSION BAR: 0.070 inch ± 0.005 inch
TARGET: 0.035 inch ± 0.002 inch

EPOXY: Epoxy resin shall be applied to the lapel button as indicated above, and shall match TIOH Hard Enamel Color Chip Numbers listed below. If hard cloisonné enamel is used, the base material must be Gilding Metal 95/5 (UNS Alloy No. C-210).

TIOH HARD ENAMEL COLOR CHIPS	
COLOR	**CHIP NUMBER**
Black	#26
White	#28

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Piercing shall be as indicated.

3. Lugs shall be fabricated from gold plated wire with a nominal diameter of 0.050 inch. The overall diameter of the lugs shall be 3/16 inch ± 1/64 inch. Lugs shall be hard soldered to the pendant bar 19/32 inch ± 1/64 inch on centers. As an alternate method, lugs may be cut into the working die.

4. Links (jump rings) shall be fabricated from gold plated wire with a nominal diameter of 0.050 inch. The links shall have an outside diameter of 3/16 inch + 1/32 inch - 0 inch.

5. Two brass balls 0.105 inch in diameter shall be soldered to the sides of the suspension bar as shown. As an alternate method, the balls may be an integral part of the suspension bar and may be cut into the contractor's working die.

6. The target shall be superimposed on the pendant and shall be secured by means of two solid brass rivets.

7. The attaching device shall be prong and wing type clutch two prongs shall be located on the horizontal center line of the suspension bar equidistant from each end and 1-5/16 inch ± 1/64 inch apart.

8. A forcer may be used to bring up the design of the shield on the suspension bar.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:43Z
Check the source to verify that this is the current version before use.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2021-276)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:43Z
Check the source to verify that this is the current version before use.