NOT MEASUREMENT SENSITIVE


MIL-B-3628/3E
30 July 1993
SUPERSEDING
MIL-B-3628/3D
7 August 1991

MILITARY SPECIFICATION SHEET

BADGE, QUALIFICATION, DISTINGUISHED MARKSMAN, NAVY; PENDANT AND SUSPENSION BAR

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3628.



MATERIAL:
PENDANT: Gilding Metal
SUSPENSION BAR: Red Brass

FINISH:
PENDANT: Hard Enameled, Gold Plated, Matte Finish, Highlights and Rim Polished, and shall match TIOH Metal Finish Chip Number 8. REVERSE - Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

SUSPENSION BAR: Gold Plated, Matte Finish, Highlights and Rim Polished, and shall match TIOH Metal Finish Chip Number 8. REVERSE - Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:44Z
Check the source to verify that this is the current version before use.

DIMENSIONS:
HEIGHT (Overall): 1-33/64 inch (3.85 cm) (REF)
WIDTH (Overall): 1-9/32 inch (3.25 cm) (REF)
THICKNESS (Edge): 0.080 inch ± 0.005 inch (0.203 cm ± 0.012 cm)

SUSPENSION BAR:
HEIGHT (Overall): 5/16 inch (0.79 cm) (REF)
WIDTH (Overall): 1-7/8 inch (4.76 cm) (REF)
THICKNESS (Edge): 0.055 inch ± 0.005 inch (0.140 cm ± 0.012 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Enameled areas shall be as indicated. The color shall conform to the TIOH chip numbers listed below or the standard sample.

COLOR	CHIP NUMBER
Black	26
White	28

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of manufacturer. Epoxy resin shall be smooth and flush with the dikes.

4. The links shall be fabricated from gold plated wire with a nominal diameter of 0.044 inch (0.112 cm). The overall dimension of the links shall be 13/64 inch (0.52 cm) in width and 1/4 inch (0.64 cm) in length.

5. The lugs are intergral.

6. The attaching device shall be a prong and flat ball clutch type. The prongs shall be located on the horizontal center line of the suspension bar, equidistant from each end and 1-11/32 inches ± 1/32 inch (3.41 cm ± 0.08 cm) apart.

7. The use of any type of plastic packaging material is prohibited.

Custodian:
Army - IH
Navy - NU

Preparing Activity:
Army - IH

Review Activity:
DLA - CT

(Project No. 8455-0693)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:44Z
Check the source to verify that this is the current version before use.