NOT MEASUREMENT SENSITIVE


MIL-DTL-3628/3L(NU)
17 February 2026
SUPERSEDING
MIL-DTL-3628/3K(NU)
19 September 2024

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, DISTINGUISHED MARKSMAN, U.S. NAVY, PENDANT AND SUSPENSION BAR

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.



MATERIAL:
PENDANT: Gilding Metal 95/5 (UNS Alloy No. C-210)
SUSPENSION BAR: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH:
PENDANT: Epoxy resin, 24K Gold Plated, Matte Finish, Highlights and Rim Polished, and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 8.
REVERSE - 24K Gold Plated Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.
SUSPENSION BAR: 24K Gold Plated, Matte Finish, Highlights and Rim Polished, and shall match TIOH Metal Finish Chip Number 8.
REVERSE - 24K Gold Plated Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:44Z
Check the source to verify that this is the current version before use.

DIMENSIONS:
HEIGHT (Overall): 1-33/64 inches (REF)
WIDTH (Overall): 1-9/32 inches (REF)
THICKNESS (Edge): 0.080 inch ± 0.005 inch
SUSPENSION BAR:
HEIGHT (Overall): 5/16 inch (REF)
WIDTH (Overall): 1-7/8 inches (REF)
THICKNESS (Edge): 0.055 inch ± 0.005 inch

ATTACHING DEVICE AND LINKS:
1: The attaching device shall be a prong and wing clutch type.

2: The prongs shall be located on the horizontal center line of the suspension bar, equidistant from each end and 1-11/32 inches ± 1/32 inch apart.

3: The links shall be fabricated from gold plated wire with a nominal diameter of 0.044 inch ± 1/64 inch. The overall dimension of the links shall be 13/64 inch ± 1/64 inch in width and 1/4 inch ± 1/64 inch in length.

EPOXY: Epoxy enamel shall be applied to the Badge Qualification as indicated above and shall match TIOH Hard Enamel Color Chip Numbers listed below. Hard cloisonné enamel may be used in lieu of epoxy. If hard cloisonné enamel is used, the required base material shall be Gilding Metal 95/5 (UNS Alloy C-210)

TIOH HARD ENAMEL COLOR CHIPS	
COLOR	**CHIP NUMBER**
Black	#26
White	#28

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The lugs are integral.

3. The use of any type of plastic packaging material is prohibited.

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:44Z
Check the source to verify that this is the current version before use.

Custodian:
Navy - NU

Preparing activity:
Navy - NU

Review activity:
DLA - CT

(Project No. 8455-2026-051)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:44Z
Check the source to verify that this is the current version before use.