NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/5J
22 June 2021
SUPERSEDING
MIL-DTL-3628/5H
29 August 2016

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, DISTINGUISHED RIFLEMAN, CIVILIAN AWARD, ARMY; PENDANT AND SUSPENSION BAR

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.



MATERIAL:
PENDANT AND SUSPENSION BAR: Red Brass 85/15 (UNS Alloy No. C-230)
TARGET: Gilding Metal 95/5 (UNS Alloy No. C-210)

FINISH:
TARGET: Hard Enameled, Gold Plated, Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Metal Finish Number 6.
PENDANT AND SUSPENSION BAR: Gold Plated, Rose Gold Plated, Matte Finish, Highlights and Rim Polished shall match TIOH Metal Finish Number 20.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:45Z
Check the source to verify that this is the current version before use.

DIMENSIONS:
HEIGHT (overall):
ASSEMBLED: 2-9/32 inches (REF)
PENDANT: 1-1/2 inches (REF)
SUSPENSION BAR: 21/32 inch (REF)
TARGET: 11/16 inch (REF)
WIDTH (overall):
PENDANT: 1-13/32 inches (REF)
SUSPENSION BAR (including balls): 1-5/8 inches (REF)
TARGET: 11/16 inch (REF)
THICKNESS (at rim):
PENDANT (edge): 0.086 inch ± 0.005 inch
SUSPENSION BAR (thickest point): 0.095 inch ± 0.005 inch
TARGET: 0.035 inch ± .002 inch

ATTACHING DEVICE:
1. Attaching device shall be prong and wing type clutch.

2. The prongs shall be located on the horizontal center line of the bar equidistant from each end and 1-5/16 inch ± 1/64 inch apart.

EPOXY: Epoxy resin shall be applied to the Badge Identification as indicated above, and shall match TIOH Hard Enamel Color Chip Numbers listed below. Hard cloisonné enamel may be used in lieu of epoxy.

COLOR	CHIP NUMBER
Black	26
White	28

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Epoxy resin shall be smooth and flush with the dikes.

3. Lugs shall be fabricated from gold plated wire with a nominal diameter of 0.050 inch. The outside diameter of the lugs shall be 3/16 inch ± 1/64 inch. Lugs shall be hard soldered to the pendant bar 19/32 inch ± 1/64 inch on centers. As an alternate method, lugs may be cut into the working die.

4. Links (jump rings) shall be fabricated from gold plated wire with a nominal diameter of 0.050 inch. The links shall have an outside diameter of 3/16 inch + 1/32 inch - 0 inch.

5. Two brass balls 0.105 inch in diameter shall be soldered to the sides of the suspension bar as shown. As an alternate method, the balls may be an integral part of the suspension bar and may be cut into the contractor's working die.

6. Target shall be superimposed on the pendant and shall be secured by means of two solid brass rivets.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:45Z
Check the source to verify that this is the current version before use.

7. A forcer may be used to bring up the design of the shield on the suspension bar.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2021-548)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:45Z
Check the source to verify that this is the current version before use.