INCH-POUND
MIL-DTL-16475/61C
06 October 1997
SUPERSEDING
MIL-D-16475/61B(NU)
11 January 1989

DETAIL SPECIFICATION SHEET

DEVICES, METAL, (BREAST AND COLLAR) SECURITY PERSONNEL

This specification sheet is approved for use by the Defense Personnel Support Center, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the insignia described herein shall consist of this document and the latest issue of specification MIL-D-16475.

Size: Regulation

Classification: Type I - Star-in-shield
Type II - Fouled anchor
Class 1 - Gold
Class 2 - Silver

Material: Gilding metal, Brown & Sharpe Gauge No. 16, 0.051 inch thick (minimum).

Design: The badge design shall meet Navy reference samples V.H. Blackington style No. 15-22 (star-in-shield) and style No. 15-23 (fouled anchor).

Hubs: No Government hubs are available for the basic badge design. However, hubs are available for the badge centers. The badge centers shall conform to the hubs listed below:
Hub No. H-58, star-in-shield
Hub No. H-59, fouled anchor

Color: The badge shall be gold or silver.

Dimensions (inches):	Regulation (overall):
Width	1-3/4
Height	2-1/2
Tolerance (inches):	± 1/32

Weight: Gold badge with fastener - 27.5 (± 0.5) grams
Silver badge with fastener - 26.0 (± 0.5) grams

AMSC N/A **FSC 8455**

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:07Z
Check the source to verify that this is the current version before use.

Finish: Gold badge - 24 Karat Gold Electroplated, mirror-like polished and lacquered.
Silver badge - Nickel Underplated, Rhodium Electroplated, mirror-like polished and lacquered.
Letter and numeral Highlighting - Enamel, air dry. Color shall match shade Blue 15090 of FED-STD-595.
Finished badges shall be lacquered on both sides.

Forcer: Full forcer required.

Fastener: The badge shall have a 2 inch pin/joint fastener centered on the reverse side of the longest direction and hard soldered or electronically fused to the badge. The corresponding safety catch shall be a top opening type and shall be hard soldered or electronically fused in the correct position.

Inscriptions (See note):
First panel (top) - U.S. NAVY (Use 12 point type)
Second panel - Appropriate area of security for ship or squadron (Use 12 point type).
Third panel - Appropriate activity, ship or squadron:
13 letters, maximum (Use 10 point type)
18 letters, maximum (Use 8 point type)
21 letters, maximum (Use 6 point type)
28 letters, maximum (Use 4 point type)
Fourth panel - Serial numbers (Use 12 point type)

NOTE: All inscription shall be one line, suitably spaced and optically balanced. The ship, activity, or squadron shall supply the inscription information, when necessary any abbreviation, and shall be responsible for controlling the serialization of the numbers.

Where used: Badges shall be worn by all Navy military personnel serving in areas of security. The badge with shield shall be worn by the Chief and Master at Arms personnel and the badge with anchor shall be worn by Base Police, Guard and Corrections personnel.

Note: 1. The figure is for information purposes only.
2. Packaging and packing shall be standard commercial practice.
3. Type I, Class 1, Chief Master at Arms
Type I, Class 2, Master at Arms
Type II, Class 1, Corrections
Type II, Class 2, Corrections
Type II, Class 1, Base Police
Type II, Class 2, Base Police
Type II, Class 2, Guard

Custodians:
Navy - NU

Preparing Activity: DLA - CT

Project No. 8455-0904

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:07Z
Check the source to verify that this is the current version before use.