MIL-D-16475/48A(CG)
23 SEP 1988
SUPERSEDING
MIL-D-16475/48(SA)
10 August 1973

MILITARY SPECIFICATION SHEET
DEVICES, METAL, (BREAST AND COLLAR)
ENLISTED PERSONNEL (U.S. COAST GUARD)

This specification sheet is approved for use by the United States Coast Guard, Department of Transportation, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the insignia described herein shall consist of this document and the latest issue of Specification MIL-D-16475.



P.O. 1st class



P.O. 2nd class



P.O. 3rd class

Size:	Regulation
Material:	Brass
Design:	Government Hub
Color:	Shield - Silver
	Chevron - Gold

Guide Sample: Available for finish and workmanship.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Officer In Charge, Navy Clothing and Textile Research Facility, 21 Strathmore Road, Natick, Ma. 01760-2490 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:06Z
Check the source to verify that this is the current version before use.

Dimensions (inches):	Regulation (overall)
Width of Chevron	13/16
Height of Chevron	1/16
Width of Shield	1/2
Height of Shield	9/16
Overall height	
1st class P.O.	1
2nd class P.O.	7/8
3rd class P.O.	11/16
Tolerance (inches):	± 1/32

Thickness: (at thickest point):
Shield - 0.090 inch (minimum)

Chevron - 0.050 inch (minimum)

Finish:
Shield - Nickel underplated, rhodium electroplated.

Chevron - 24 Karat Gold Electroplated, mirror-like polish and lacquered on all sides.

Forcer: No forcer permitted.

Placement of Attachment: Two prongs and two clutch fasteners are required. The prongs shall be centered and placed as follows: One at the top peak of the shield and one at the vertex of the uppermost chevron. Prongs shall measure between their centers 17/32 (± 1/32) inch.

Where used: U. S. Coast Guard enlisted personnel collar device.

Note: 1. The figure is for information purposes only.
2. Packaging and packing shall be standard commercial practice.

Custodian:
Navy - NU

Preparing Activity:
Navy - NU

Review Activity:
DLA-CT

Project No. 8455-N319

User Activity:
Navy - CG

Source: https://assist.dla.mil -- Downloaded: 202610-18T09:06Z
Check the source to verify that this is the current version before use.