MILITARY SPECIFICATION

ADAPTER, BOMB CLUSTER, 750-POUND, M30E2

1. SCOPE

1.1 This specification covers one type of adapter.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1168 - Lot Numbering of Ammunition.

DRAWINGS

US ARMY MUNITIONS COMMAND

EDGEWOOD ARSENAL

E14-23-4080 - Adapter, Bomb Cluster, 750-Pound, M30E2.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material and components.

3.1.1 Material. All materials cited on Drawing E14-23-4080 or on the subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

3.1.2 Components. All components of the adapter shall conform to the specifications and drawings listed on Drawing E14-23-4080 and subsidiary drawings.

3.2 Assembly. The adapter shall be assembled as specified on Drawing E14-23-4080.

3.3 Leakage. The adapter shall not leak when tested as specified in 4.4.4.1.

3.4 Gasket joint. The gasket joint shall not show evidence of separation when tested as specified in 4.4.4.2.

3.5 Preproduction. Prior to the start of regular production, a preproduction sample of adapters shall be produced in accordance with this specification for examination and tests (see 4.3).

3.6 Workmanship. The adapter shall be free from foreign matter (oil, grease or dirt) and damage such as dents, cracks or deformation which could affect its intended use.

4. QUALITY ASSURANCE PROVISIONS

4.1.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

4.3 Preproduction inspection.

4.3.1 Sample. A preproduction sample of 10 adapters shall be manufactured using the same methods, materials, equipment and processes as will be used during regular production.

4.3.2 Inspection procedure.

4.3.2.1 For examination and nondestructive test (4.4.4.2). Each adapter shall be examined and tested in accordance with the classification of defects (4.4.3.3). The AQL's do not apply.

4.3.2.2 For nondestructive test (4.4.4.1). Each adapter shall be tested as specified in 4.4.4.1.

4.3.3 Acceptance/rejection criteria. The preproduction sample shall comply with the examinations and tests specified in 4.3.2 to be acceptable. The acceptance number is zero. The supplier shall obtain written approval from the contracting officer prior to proceeding with regular production.

4.4 Quality conformance inspection.

4.4.1 Lotting. Each lot shall be identified and controlled in accordance with MIL-STD-1168 and consist of one week's production.

4.4.2 Sampling for examination and nondestructive tests. Sampling shall be conducted in accordance with MIL-STD-105.

4.4.3 Inspection procedure.

4.4.3.1 For examination and nondestructive test (4.4.4.2). The sample adapters shall be examined and tested in accordance with the classification of defects and MIL-STD-105.

4.4.3.2 For nondestructive test (4.4.4.1). Each assembled adapter in each lot shall be tested in accordance with 4.4.4.1. Leaking adapters shall be rejected (see 6.3).

4.4.3.3 Classification of defects.

(a) Adapter, bomb cluster, 750-pound, M30E2 (Drawing E14-23-4080).

Categories	Defects
Critical:	None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

4.4.3.3 Classification of defects (Continued).

(a) Adapter, bomb cluster, 750-pound, M30E2 (Drawing E14-23-4080). (Continued).

Categories		Defects
Major:	AQL 1.0 percent defective	
*101		Component missing, incorrect or incorrectly assembled
*102		Thread (1-3/4-12UN-2B) incorrect (Drawing C14-23-4068)
103		Shell length or width incorrect
104		Hook location or attachment incorrect
105		Spotweld edge distance incorrect
106		Suspension lug incorrectly assembled
107		Fin orientation marking missing or incorrect
108		Adapter sealing plane warped beyond drawing tolerance
109		Sealing edge location with respect to hinge incorrect
110		Workmanship (3.6)
Minor:	AQL 4.0 percent defective	
201		Protective finish missing or incorrect

*Check prior to assembly.

(b) Gasket, extruded (Drawing C14-23-3144).

Categories		Defects	Acceptance standards
Critical:		None defined	
Major:	AQL 0.65 percent defective		
101		Joint separation	4.4.4.2

(c) Tube, hinge (Drawing B14-23-3033).

Categories		Defects
Critical:		None defined
Major:	AQL 1.0 percent defective	
101		Hardness incorrect
102		Material incorrect

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

4.4.4 Tests. Tests shall be conducted as follows:

4.4.4.1 Leakage. This test shall be performed prior to painting. Introduce air into the adapter at a pressure of 20 ± 5 pounds per square inch gage (psig). Submerge the adapter completely in water in a position that will allow it to be revolved around its longitudinal axis. A sufficient amount of wetting agent shall be in the water to prevent bubbles from clinging to the surfaces. Observe the adapter for a minimum period of 1 minute. A steady stream of bubbles denotes a leak.

4.4.4.2 Gasket joint. The gasket joint shall be tested in a tensile testing machine. The gasket joint shall be centered between the heads of the machine and the heads separated at the rate of 1 inch per minute until a minimum load of 300 psig has been applied. Load to be held for a minimum of 10 seconds.

5. PREPARATION FOR DELIVERY

5.1 Packing, level C. The adapters with packaged gaskets shall be packed in accordance with Drawing E14-17-435.

5.2 Marking. In addition to any special marking specified in the contract or order, marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. This item is intended for use in grouping certain types of bombs for dispersion by aircraft.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) The suspension lugs will be Government furnished.
(c) Preproduction.

(1) Time allowed for supplier submission of sample for Government test and evaluation after award of contract.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the supplier whether or not to proceed with production.

6.3 Repair of leaky adapters. An adapter found to be leaking, may be repaired and retested in accordance with 4.4.4.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

6.4 Supersession data. This specification supersedes Edgewood Arsenal Purchase Description EA-A-1077, 22 May 1970.

Custodian:

Army - MU

Preparing activity:

Army - MU(EA)

Project No. 1325-A329

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.