MIL-A-82516(OS)
AMENDMENT 2
23 JUNE 1970
Superseding
AMENDMENT 1
2 May 1969

MILITARY SPECIFICATION

ACCELEROMETER

This amendment forms a part of Military Specification MIL-A-82516(OS) of 17 November 1967 and has been approved by the Naval Ordnance Systems Command, Department of the Navy

Wherever it appears in specification delete "Bureau of Naval Weapons" and substitute "Naval Ordnance Systems Command"; also delete "BuWeps" and substitute "NAVORD".

Page 3, paragraph 3.3.4. Delete and substitute:
"3.3.4 Circuit resistance. The accelerometer shall have a resistance of 8000 plus or minus 1000 ohms between terminals A and C, and with the accelerometer inverted (mounting surface up), the resistance between terminals A and B shall be not more than 55 ohms."

Page 8, paragraph 4.4.3d: Delete "150 to 200 cps, 1.25 plus or minus 0.50g applied" and substitute "150 to 200 cps, 1.25 plus or minus 0.10g applied".

Page 11, paragraph 4.6.1.3. Delete and substitute:
"4.6.1.3 Circuit resistance. With the accelerometer oriented as specified, measure the resistance of the circuits using the resistance measuring device specified in 4.4.1f. The resistance shall be as specified below.

Terminals	Resistance (ohms)	Accelerometer Orientation
A to C	8000 ±1000	Mounting surface down
A to B	55 max.	Mounting surface up"

Preparing Activity
Navy - OS
Project No. 1135-N004

FSC 1135

☆ U. S. GOVERNMENT PRINTING OFFICE: 1970-433-688/198

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:13Z
Check the source to verify that this is the current version before use.