
MILITARY SPECIFICATION SHEET

SWITCHES, WAVEGUIDE, 1P2T, MANUALLY OPERATED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the switch described herein shall consist of this specification and the latest issue of MIL-S-55041.




INCHES	MM
.05	1.3
.250	6.35
.30	7.6
.50	12.7
4.03	102.4
4.75	120.6
5.48	139.2
5.80	147.3
6.10	154.9
6.75	171.4
7.75	196.8
8.53	216.7


FIGURE 1. Switch configuration and schematic, part no. M55041/9-001.

Ⓐ denotes changes

FSC 5985

Source: https://assist.dla.mil -- Downloaded: 202610-22T22:18Z
Check the source to verify that this is the current version before use.





SCHEMATIC AND PORT INFORMATION

Shown with S1, actuated to connect input port to output No. 2 port

A, C = 115 Vac 60 Hz, 3 amp max.

B, D = AC common

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
3. Round corners of case may be squared.
4. Unless otherwise specified, tolerances are ±.010 (.25 mm) for three place decimals and ±.03 (.8 mm) for two place decimals.
5. Knob (manual control) may be centrally located.
6. Waveguide size equivalent to MIL-W-85/1-041.

Ⓐ FIGURE 1. Switch configuration and schematic, part no. M55041/9-001 - Continued.

Source: https://assist.dla.mil -- Downloaded: 202640-22T22:18Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical performance characterisitics.

Dash number	Figure number	Housing	Operating frequency range	Interlock circuit		Actuation method
				Voltage	Current	
			GHz	ac	amperes	
001	1	1/ 2/	2.60-3.95	115	3	Manual

TABLE I. Electrical performance characteristics - Continued.

Dash number	Isolation (min)	VSWR (max)	Insertion loss (max)	Waveguide pressurization	Life cycle (X1000)	Weight (max)
	dB			lb_f/in^2		lbs
001	60	1.2:1	0.1	25	200	15

1/ Enclosed, sand- and dust-proof when waveguide flanges are capped.

2/ Rotor and housing of aluminum alloy.

REQUIREMENTS:

Design and construction:

Dimensions and configuration: See figure 1.

Power connectors: See figure 1.

Operating temperature range: -55°C to +95°C.

Electrical performance characteristics: See table I.

RF power handling capability: Peak - 1.5 MW with a duty cycle of 1×10^{-3}; average - 1.5 kW.

Part number: M55041/9-001.

(A) Substitutability data: The switch covered by this specification sheet is substitutable for the user's or manufacturer's part numbers specified in table II. This information in no way implies that the manufacturer's part number or NSN is suitable as a substitute for the military part number.

TABLE II. Substitutability data.

Dash number	Manufacturer's code	Commercial type	NSN
001	17480	1925-284-DNW	---
001	82152	34D90500	---
001	11787	S10715	---
001	24930	G330157	00-5840-109-9488

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:18Z
Check the source to verify that this is the current version before use.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - MI, SM
Air Force - 11, 17, 99
DLA - ES

User activities:
Navy - AS, MC, OS, SH
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5985-0975-6)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:18Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY
Naval Electronic Systems Command
Washington, DC 20363

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, DC 20363
ATTN: ELEX 8111

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:18Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-55041/9A	Switches, Waveguide, 1P2T, Manually Operated

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*:
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 202640-22T22:18Z
Check the source to verify that this is the current version before use.