MILITARY SPECIFICATION

SWITCH, ARM-SAFE, MARK 60 MOD 1

This amendment forms a part of Military Specification MIL-S-82520(OS) of 17 November 1967 and has been approved by the Naval Ordnance Systems Command, Department of the Navy

Wherever it appears in specification delete "Bureau of Naval Weapons" and substitute "Naval Ordnance Systems Command".

Page 6, paragraph 3.4.1.1: After "120 degrees F" add "Omit the 24 hour pre-soak requirement of 3.3.1.1 during the temperature, operating test of 4.5.1.13."

Pages 11 and 12. Delete Table I and substitute:

TABLE I

Preproduction and Periodic Production Test Sequence

Test	Paragraph Number	Test Quantities Preproduction	Periodic	
Quality Conformance Inspection	4.6	20	5	5
Temperature, Storage Condition	4.5.1.1	20	5	5
Current Capacity	4.5.1.2	20	5	5
Humidity	4.5.1.3	20	5	-
Fungus	4.5.1.4	20	-	-
Quality Conformance Inspection	4.6	20	5	-
Sand and Dust	4.5.1.5	20	-	-
Salt Spray	4.5.1.6	20	-	5

FSC 1135

Source: https://assist.dla.mil -- Downloaded: 202640-23T07:13Z
Check the source to verify that this is the current version before use.

TABLE I (Cont'd)

Preproduction and Periodic Production Test Sequence

Test	Paragraph Number	Test Quantities Preproduction	Periodic
Vibration, Standby Condition	4.5.1.7	20	- 5
Shock, Standby Condition	4.5.1.8	20	- 5
Quality Conformance Inspection	4.6	20	- 5
Acceleration	4.5.1.9	20	- 5
Vibration, Operating Condition	4.5.1.10	20	5 5
Temperature, Operating Condition	4.5.1.13		
Low Extreme	4.5.1.13.1	20	5 -
Quality Conformance Inspection	4.6	20	5 -
High Extreme	4.5.1.13.2	20	- 5
Quality Conformance Inspection	4.6	20	- 5
Shock, Operating Condition	4.5.1.11	20	5 5
Quality Conformance Inspection	4.6*	20	5 5
Pressure	4.5.1.12	20	5 5

*EXCEPT tests shall be limited to circuit resistance and insulation resistance tests with the Switch in the ARM position only.

Page 14, paragraph 4.5.1.1, last line: Delete "prior to performing subsequent tests".

Page 16, paragraphs 4.5.1.13.1 and 4.5.1.13.2. Add the following sentence to the end of each paragraph: "Omit the 24 hour pre-soak requirement of 3.3.1.1 during the temperature, operating test of 4.5.1.13."

Page 17, Table II. Delete the following:
"Preservation, packaging, packing, and marking ** ** 4.7"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:13Z
Check the source to verify that this is the current version before use.

Page 18, paragraph 4.7: Delete "The switch shall be examined ..." and substitute "Each switch submitted for delivery to the procuring agency shall be examined ...".

Preparing Activity
Navy - OS
Project No. 1135-N008

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:13Z
Check the source to verify that this is the current version before use.