MIL-T-82300/26(TD)
13 March 1970

MILITARY SPECIFICATION

TRANSPARENCY, ANIMATED: CYLINDER LUBE OIL METERING INJECTOR

This specification has been approved by the Naval Training Device Center, Department of the Navy

The technical requirements for procuring the animated transparency described herein shall consist of this document and the issue in effect of Specification MIL-T-82300.

1. SCOPE

1.1 This specification covers the requirements for an animated transparency of the Cylinder Lube Oil Metering Injector to aid in familiarizing students with the function of the operational equipment.

1.1.1 This item has been designated by the Naval Training Device Center as Device 2H84/1 for Navy procurement. (see 6.2).

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bid or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-T-82300	Transparencies; Animated, General Specification for

STANDARDS

Federal

FED-STD-595	Colors

PHOTOGRAPHS

Naval Training Device Center (NAVTRADEVCEN)

BXA-9827-2-67 BXA-9828-2-67 BXA-9829-2-67	Cylinder Lube Oil Metering Injector Training Aid

FSC 6910

Source: https://assist.dla.mil -- Downloaded: 202610-23T07:02Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

3. REQUIREMENTS

3.1 Except as specified herein, requirements shall be in accordance with the requirements of MIL-T-82300.

3.1.1 Cements.- Cements used for joining plastic components shall be those cements recommended by the manufacturer of the plastic and tested by the contractor as suitable to meet the construction and performance requirements of this specification.

3.2 Design.- The animated transparency as shown in Naval Training Device Center photographs BXA-9827-2-67 through BXA-9829-2-67 shall be designed in accordance with the design requirements of MIL-T-82300 and the Government-loaned laboratory model.

3.3 Construction.- Except as specified in 3.3.1, construction shall be in accordance with the construction requirements of MIL-T-82300.

3.3.1 Cementing.- Cementing shall be limited to those areas where assembly with screws is clearly impractical. Cemented joints shall be free of air bubbles and stress-crazing and shall have the transparency of the original plastic throughout the joint. The contact surface of the component to be cemented shall be thoroughly softened by means of a solvent, so that a soft layer or cushion is produced on that surface and the subsequent uniting and hardening will effect a strong homogeneous bond. Bonding by capillary attraction shall require specific written approval of the procuring activity for each specific variance. For recommendations on cementing acrylic plastics, the publications cited in the cementing requirements of MIL-T-82300 may be used.

3.4 Performance.- The animated transparency, when used on the overhead projector, with the heat filter removed, shall withstand the temperature produced by a 1,000 watt projection lamp for a period of 45 minutes. At the end of the 45 minute period, the animated transparency shall meet the performance requirements of MIL-T-82300.

3.5 Details of components.-

3.5.1 Baseplate dust seals.- The edges of the layers of the baseplate shall be sealed with white opaque or aluminum polyester tape so as to be dustproof and to mask edge lighting effects. Dust seals shall be provided wherever a laminated component or flap is used. Such seals, in projectable areas, shall be applied to the edges only.

3.5.2 Focusing mark.- The cross hairs and the 1/4-inch opening of the focusing mark shall be concentric.

Source: https://assist.dla.mil -- Downloaded: 202610-23T07:02Z
Check the source to verify that this is the current version before use.

3.5.3 Carrying case.- The top and bottom of the carrying case shall be 1/4-inch thick, exterior grade plywood, smooth on two sides.

3.5.3.1 Color.- The color of the carrying case shall be gray, number 26152 of FED-STD-595.

4. QUALITY ASSURANCE PROVISIONS

4.1 Except as specified in 4.1.1, quality assurance provisions shall be in accordance with the quality assurance provisions of MIL-T-82300.

4.1.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with delivery requirements of MIL-T-82300.

6. NOTES

6.1 Except as specified in 6.2, the notes of MIL-T-82300 shall be applicable.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number and date of this specification

(b) Procuring activity designation (see 1.1.1)

CUSTODIAN:
Navy-TD

PREPARING ACTIVITY:
Navy-TD
Project No. 6910-N232

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:02Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)* | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4003, WHICH IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:02Z
Check the source to verify that this is the current version before use.