MILITARY SPECIFICATION

TIMER, INTERVAL, MARK 11 MOD 2 (ASSEMBLY)

This amendment forms a part of Military Specification MIL-T-82535(OS) of 18 April 1968 and has been approved by the Naval Ordnance Systems Command, Department of the Navy

Wherever it appears in specification delete "Bureau of Naval Weapons" and substitute "Naval Ordnance Systems Command"; also, delete "BuWeps" and substitute "NAVORD".

Page 3. Add the following paragraphs:
"3.3.5 Resistances and continuity

3.3.5.1 The resistance of circuit E3 to E6 shall be 0.10 ohm maximum.

3.3.5.2 The resistance of circuits E4(+) to E1(-) and E2(+) to E5(-) shall be 10,000 ohms minimum."

Page 10, paragraph 4.4.1. Add the following new item:
"C. Resistance measuring device — Measure resistance from 0.10 to 10,000 ohms with an error of not more than 5 percent"

Page 15, Table II:
Delete: "Visual examination * 4.6.1.5 *"
Substitute: "Resistance and continiuty * 4.6.1.5 *
Visual examination * 4.6.1.6 *"

Page 17, paragraph 4.6.1.5. Delete and substitute:
"4.6.1.5 Resistance and continuity. Using the device specified in 4.4.1c., measure the resistance and continuity of the timer cirucits. The circuits and resistance shall be as specified below:

Circuit	Resistance
E3 to E6	0.10 ohm max.
E4(+) to E1 (-)	10,000 ohms min.
E2(+) to E5 (-)	10,000 ohms min."

FSC 1340

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:14Z
Check the source to verify that this is the current version before use.

"4.6.1.6 Visual examination. Visual examination shall be made on each timer submitted for delivery to the procuring agency. The timer shall be examined for conformance to the requirements of good workmanship specified in 3.6. Nonconformance is cause for rejection of individual unit."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:14Z
Check the source to verify that this is the current version before use.