MIL-C-46936B (AR)
AMENDMENT 2
6 December 1985
SUPERSEDING
AMENDMENT 1
24 September 1975

MILITARY SPECIFICATION

CARTRIDGE, 5.56MM, TEST, HIGH PRESSURE, M197

This Amendment forms a part of Military Specification MIL-C-46936B (AR) dated 5 March 1971, and is approved for use by the US Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Paragraph 2.1

Under "DRAWINGS", delete "Munitions Command" and substitute: "Armament Command".

Under "PUBLICATIONS", delete "Munitions Command" and "AMSMU-P715-501FA1" in entirety and substitute:

"Frankford Arsenal
SCATP-5.56 - Ammunition Ballistic Acceptance Test Methods Test Procedures for 5.56mm Cartridges".

Delete: "AMSMU-P715-501FA1" wherever it appears in the specification and substitute: "SCATP-5.56".

PAGE 4

Paragraph 4.3.2.1, Table I, add :29 Exposed steel (clad jacket)", as a minor defect.

PAGE 6

* Paragraph 4.3.3.1, delete definition of "Test Sample" in its entirety and substitute the following:

"4.3.3.1 Test samples. The quantities for the various tests shall be as specified in Table II. Only cartridges having met the visual, dimensional and weight requirements shall be used in Ballistic tests and shall have been selected in such a manner that the sample is representative of the entire lot. The cartridges (unplated cases for the residual stress test) shall be thoroughly mixed before being divided into samples for the various tests."

FSC 1305

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:20Z
Check the source to verify that this is the current version before use.

* Under "Table II" delete "2/" in its entirety and substitute the following:

"2/ A fifty (50 round sample of each case lot (before plating) is to be assembled with bullets into cartridges for residual stress testing purposes only. The occurance of splits in two (2) or more cartridges shall be cause for rejection of case lot. If one cartridge fails in the first test, a second sample consisting of double the number of cartridges in the first sample shall be tested. If any failing cartridges are found in the second sample, the case lot (before plating) shall be rejected."

PAGE 7

Paragraph 4.3.3.2, Table III, delete "a" and "b" under "Primer casualties" in their entirety and substitute:

"a.	Dropped primer	3	7
b.	Blown primer	0	1"

The margins of this amendment are marked with asterisks or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1305-A011)

Source: https://assist.dla.mil -- Downloaded: 202610-22T07:20Z
Check the source to verify that this is the current version before use.