MIL-C-46940(MU)
AMENDMENT 3
1 November 1973
SUPERSEDING
AMENDMENT 2
1 May 1967

MILITARY SPECIFICATION
CASE, CARTRIDGE, 105MM, M14

This amendment forms a part of Military Specification MIL-C-46940(MU), 15 March 1963.

Paragraph 3.6, delete: "After the final forming operation,".

Paragraph 3.9.2, Table I, line 2, change: "55,000 - Minimum" to "50,000 - Minimum".

* Add paragraph 4.3.2 a:

"4.3.2 a Tool Control Dimensions.-Dimensions marked tool control shall be gaged during first article inspection, and after 250 items are produced from each machine in operation and after any tooling change. Where destruction of components is necessary to inspect these dimensions, measurements of the tool may be substituted provided the contractor has established correlation between the tool dimensions and the component dimensions prior to the start of production. The contractor shall be responsible for maintaining adequate surveillance to assure that drawing requirements are being met throughout the life of the tool. Corrective action will be immediately instituted whenever a defective tool control dimension is found."

* Paragraph 4.3.2.1.1, delete "Major" 101 and 102, and substitute the following:

"101.	True position primer hole with body	Gage
102.	True position primer hole counterbore with primer hole	Gage".

* The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Army - MU

Preparing activity:

Army - MU(FA)

Project No. 1315-A243

FSC 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:21Z
Check the source to verify that this is the current version before use.