MILITARY SPECIFICATION

CUTTER, POWDER ACTUATED, REEFING LINE, XM23 METAL PARTS ASSEMBLY

1. SCOPE

1.1 This specification covers Cutter, Powder Actuated, Reefing Line, XM23, Metal Parts Assembly. The assembly will ultimately be loaded and used in conjunction with cargo parachute controlled airdrops.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-A-2550 — Ammunition and Special Weapons, General Specification for

MIL-I-45208 — Inspection Requirements, General Specification for

STANDARDS

MILITARY

MIL-STD-105 — Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-109 — Quality Assurance Terms and Definitions

MIL-STD-413 — Visual Inspection Guide for Rubber O-Rings

MIL-STD-639 — Surface Roughness Values Preferred for Army Ordnance Materiel

DRAWINGS

MUNITIONS COMMAND

C8864326 — Box, Packing, Ammunition, For Cutter, Powder Actuated, Reefing Line, M9, XM10, XM11, XM-12, M13, or XM23, with Cartridge (see 5.1)

C8864327 — Carton, Packing, Ammunition, for Cutter, Powder Actuated, Reefing Line M9, XM10, XM11, XM12, M13, or XM23, with Cartridge (see 5.1)

D10524024 — Cutter, Powder Actuated, Reefing Line, XM23, Metal Parts Assembly

(Copies of specifications, standards and drawings required by suppliers in connection with specific pro-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:22Z
Check the source to verify that this is the current version before use.

curement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General. Materials, parts and assemblies shall comply with the requirements specified on the applicable drawings, referenced specifications and the following:

3.2 Initial production sample. Unless otherwise directed by the contracting officer, an initial production sample shall be required.

3.3 Material. The contractor shall be responsible for selecting from the classification list contained in the raw material specification, the surface and physical condition of the raw material intended for use in manufacture.

3.4 Physical properties. Physical properties required by the drawing or specification shall be uniform throughout the part within specified tolerances. Requirements for all alloy steel parts shall be achieved by quenching and tempering.

3.5 Metal parts assembly. Parts shall be combined to produce an assembly which conforms to the requirements of the metal parts assembly drawing. The threaded joint between the head and housing shall be assembled handtight.

3.5.1 *Firing pin release.* The firing pin of the sear mechanism shall release when an axial load of 15 to 20 pounds has withdrawn the cable assembly from the mechanism.

3.6 Protective finish. Protective finish shall be in accordance with the applicable specifications and drawings and shall apply to all surfaces of the component regardless of contour configuration.

3.7 Workmanship. The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following:

3.7.1 *Metal defects.* All components shall be free from cracks, splits, cold shuts, inclusions, porosity or any similar defect.

3.7.2 *Burr.* No part shall have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.7.3 *Foreign matter.* No part or assembly shall contain chips, dirt, grease, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 *Quality assurance terms and definitions.* Reference shall be made to Standard MIL–STD–109 to define quality assurance terms used.

4.1.2 *Inspection.* Inspection shall be in accordance with Specifications MIL–A–2550 and MIL–I–45208, except as specified herein.

4.2 Initial production sample. Prior to the initiation of regular production, the contractor shall submit an initial production sample to a Government approved facility for evaluation. The sample shall consist of 15 metal parts assemblies and 5 sets of unassembled parts. The samples shall be subjected to the tests in 4.3.3. Test procedures shall be in

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:22Z
Check the source to verify that this is the current version before use.

accordance with 4.4, except as provided in Specification MIL–I–45208. The sample shall be manufactured in the same manner, using the same materials, equipment, processes and procedures as will be used in regular production. All parts and materials, including packaging and packing, must be the same as will be used for regular production and shall be obtained from the same source of supply. The contractor shall inspect the sample in accordance with his inspection system and other inspection requirements of Specification MIL–I–45208. After inspection and provisional acceptance at source, the initial production sample shall be inspected at the Government approved facility for all requirements of the drawings and specifications. The Government reserves the right to require new initial production samples until such time as an acceptable sample is submitted.

4.3 Inspection provisions.

4.3.1 ***Lot.***

4.3.1.1 ***Presentation of lots.*** The product shall be presented in accordance with Standard MIL–STD–105.

4.3.1.2 ***Size of lot.*** The lot size shall be as agreed upon between the contractor and the contracting officer, provided the formation of the lots is in accordance with Standar MIL–STD–105.

4.3.2 ***Examination.*** Examination for major and minor defects shall be performed on a defect basis in accordance with Standard MIL–STD–105, using an AQL of 0.25 percent for majors and an AQL of 0.40 percent for minors. All nonconforming material shall be rejected. Inspection for rubber O-rings shall be in accordance with Standard MIL–STD–413. The Ordnance Standard Finish Blocks prescribed in Standard MIL–STD–639 shall be used as a basis of comparison for surface roughness determination. Four power (4X) magnification may be used in performing visual examination for such defects as burr and foreign matter.

4.3.2.1 ***Firing Head Assembly, Drawing C10524022, a detail of Drawing D10524024.***

Defect	Method of inspection
CRITICAL:	
None defined.	
MAJOR:	
101. Location of cotter pin holes	Gage
102. Any part missing	Visual
103. Improper assembly	Visual
104. Metal defective	Visual
105. Surface finish improper	Visual
106. Burr	Visual
107. Foreign matter	Visual
MINOR:	
201. Diameter of cotter pin holes	Gage
202. Length of wrench flats	Measure
203. Width across wrench flat	Measure
204. Protective finish inadequate or defective	Visual
205. Location of wrench slots	Visual

4.3.2.2 ***Cutter, Powder Actuated, Reefing Line, Metal Parts Assembly, Drawings B10520527, B10520532, B10520533, B10524-026, MS 24665–287, C10520529, C10524021, C10524023 details of Drawing D10524024.***

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:22Z
Check the source to verify that this is the current version before use.

Defect	Method of inspection
CRITICAL:	
None defined.	
MAJOR:	
101. Diameter of body, max.	Gage
102. Diameter of reefing line holes	Gage
103. Location of reefing line holes	Gage
104. Anvil missing, or above flush of housing	Visual
105. Metal defective	Visual
106. Surface finish improper	Visual
107. Burr	Visual
MINOR:	
201. Foreign matter	Visual
202. Protective finish defective or inadequate	Visual
203. Cotter pin missing, distorted or insecure	Visual/Manual
204. Tag missing or insecure	Visual/Manual
205. Marking missing, incorrect or illegible	Visual

4.3.2.3 *Carton, Packing, Ammunition, for Cutter, Powder Actuated, Reefing Line, M9, XM10, XM11, XM12, M13, or XM23, with Cartridge, Drawing C8864327 (see 5.1).*

Defect	Method of inspection
CRITICAL:	
None defined.	
MAJOR:	
None defined.	
MINOR:	
201. Quantity of contents incorrect	Visual
202. Contents loose	Manual/Visual
203. Separator or filler missing	Visual
204. Cut or damage through impregnated carton	Visual
205. Marking missing, incorrect or illegible	Visual
206. Carton sealing defective, improper or missing	Visual

4.3.2.4 *Box, Packing, Ammunition, for Cutter, Powder Actuated, Reefing Line, M9, XM10, XM11, XM12, M13, or XM23, with Cartridge, Drawing C8864326 (see 5.1).*

Defect	Method of inspection
CRITICAL:	
None defined.	
MAJOR:	
None defined.	
MINOR:	
201. Quantity of contents incorrect	Visual
202. Contents loose	Manual/Visual
203. Contents of box exposed	Visual
204. Box damaged	Visual
205. Strapping missing, loose, broken or improperly applied	Visual
206. Marking missing, incorrect or illegible	Visual
207. Car seal missing, unsealed or improperly positioned	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:22Z
Check the source to verify that this is the current version before use.

4.3.3 *Inspection testing.* The following tests shall be performed in accordance with the provision of 4.4, except as provided in Specification MIL–I–45208.

4.3.3.1 *Hardness.* Fifty units from each heat treated lot of components shall be tested to determine compliance with the requirements of the applicable drawing. Failure of any unit to comply with the drawing requirements shall be cause for rejection of the lot.

4.3.3.2 *Firing pin release.* Each head assembly shall be subjected to the lanyard pull test. Failure of the head assembly to comply with the requirements of 3.5.1 shall be cause for rejection of the head assembly.

4.3.3.3 *Protective finish.* The number of specimens and acceptance criteria for protective finish tests shall be in accordance with the applicable military standard listed on the drawing.

4.3.4 *Inspection equipment.* The examination and tests shall be made using equipment as provided in Specification MIL–I–45208.

4.4 Test methods and procedures.

4.4.1 *Hardness.* A hardness tester shall be used to determine the hardness requirements specified on the detail drawing.

4.4.2 *Firing pin release.* The head subassembly shall be secured in the fixture and a pull applied to the cable eyelet along the major axis until firing pin releases.

4.4.3 *Protective finish.* Test procedures for protective finish shall be in accordance with the applicable military standard referenced on the drawing.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking. Level A — Packing and marking shall be in accordance with Drawings C8864326 and C8864327, except that the marking shall indicate that the reefing line cutters are without cartridges (metal parts only).

5.2 Data cards. Data card information shall be as specified in Specification MIL–A–2550.

6. NOTES. None.

Custodian:
Army—MU

Preparing activity:
Army—MU

Project No. 1375–A592

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:22Z
Check the source to verify that this is the current version before use.