MIL-C-46956B(EA)
3 December 1980
SUPERSEDING
MIL-C-46956A(MU)
20 April 1964

MILITARY SPECIFICATION

CARTRIDGE, 105MM, WP-T, M416

LOADING, ASSEMBLING AND PACKING

This specification is approved for use by the US Army Armament Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of cartridge designated as Cartridge, 105MM, WP-T, M416.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

MIL-P-50980 - Charge, Propelling, For Use With 105MM Cartridges, M393A2, HEP-T; M393A1, TP-T; M416, WP-T; M467, TP-T, Loading, Assembling, and Packing

FSC 1315

: Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed: to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-TSC-S, Aberdeen Proving Ground, MD 21010 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

CHEMICAL SYSTEMS LABORATORY

8836004 - Box, Packing, Ammunition for Cartridge 105MM, HEP-T, M393A1, M393A1E1, M393A2; TP-T, M393A1, M467; WP-T, M416 for Gun M68 in Fiber Container M451
8836005 - Container, Ammunition, Fiber, M451 for Cartridge 105MM HEP-T, M393A2; TP-T, M393A1, M467; WP-T, M416 for Gun M68
8828098 - Gage, Profile and Alignment
8828099 - Gage, Alignment Check
8828100 - Gage, Wear Limit Check
8886487 - Cartridge, 105MM, WP-T, M416 Assembly and Marking Diagram

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

ASTM E18 - Test for Rockwell Hardness and Rockwell Superficial Hardness for Metallic Materials

(Application for copies should be addressed to the American Society for Testing and Materials (ASTM), 1916 Race Street, Philadelphia, PA 19103).

3. REQUIREMENTS

3.1 Material. Material and parts shall be in accordance with the requirements of the applicable drawings and specifications.

3.2 Cartridges. The cartridge shall comply with all the requirements specified on Drawing (dwg) 8886487 and with all requirements specified in the applicable specifications.

3.3 Cartridge case crimp. The crimped cartridge case shall provide a bullet pull value of 5000 pounds, minimum, to 8000 pounds, maximum, when tested as specified in 4.5.2.

3.4 Proving ground. The cartridge shall comply with the following requirements when tested as specified in 4.5.5.

3.4.1 Muzzle velocity. The corrected muzzle velocity of the cartridge when fired at seventy degrees Fahrenheit (70°F) (21.1° Celsius (C)) shall not be more than 2430 feet per second (fps) (740.7 meters per second (mps)) nor less

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

than 2370 fps (722.4 mps) and the lot velocity standard deviation shall not be greater than 10.5 fps (4.0 mps) maximum.

3.4.2 Tracer functioning. The tracer shall ignite and there shall be visible evidence of burning of the tracer composition to a 2000 meter target, minimum.

3.4.3 Functioning. There shall be visible evidence of projectile functioning upon first or subsequent impact with the intended target as indicated by the presence of a smoke cloud with a minimum loss of screening effect due to pillaring action.

3.4.4 Safety. There shall be no premature bursts or indications of projectile metal parts breakup in the gunbore or in flight, prior to impact with the intended target, during any of the proving ground tests conducted.

3.5 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as spelcified in the contract.

3.6 Data requirements. The contractor shall generate data in accordance with the requirements of the data item descriptions cited in 4.4.2.1.

3.7 Workmanship.

3.7.1 General. The cartridge and all components shall be free of cracks or burrs; and chips, dirt, grease (including thread preservative), rust or other foreign material. Any cleaning method used shall not be injurious to any of the parts; nor, shall the parts be contaminated by the cleaning agents.

3.7.2 Painting and marking. The painting and marking shall be restored by the assembling contractor on any components furnished to him painted and marked, when such paintings and markings have been marred or obliterated. (Bare spots in exterior painting, other than marking, are allowable provided that they total not more than one-quarter square inch in aggregate, and that the maximum dimension of any individual bare spot does not exceed three-sixteenths inch).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspection shall be performed on this item:

(a) First Article Inspection
(b) Quality Conformance Inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

PART DESCRIPTION	DRAWING	QUANTITY
Gasket	8597096	20
Gas Check	8853730	10
Filler	8853732	10
Ring	8860609	10
Projectile Loading Assembly	8886486	10
Propelling Charge	8853734	10
Cartridge Case Assembly	8886487	10
Cartridge, 105MM, WP-T, M416	8886487	100

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of cartridges shall contain:

a. Cartridge cases of one lot interfix number from one manufacturer.

b. WP loaded projectiles of one loading lot interfix number from one manufacturer, containing projectile metal parts from one lot interfix number from one manufacturer.

c. M1 Propellant from not more than one lot.

d. Loaded fuzes of one lot interfix number from one manufacturer.

e. Loaded primers of one lot interfix number from one manufacturer.

f. Loaded tracers of one lot interfix number from one manufacturer.

g. Loaded projectile bursters of one lot interfix number from one manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46956B(EA)

PARAGRAPH	TITLE		SHEET 1 OF		DRAWING NUMBER
4.3.2	Cartridge, 105MM, WP-T, M416				See below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Gasket (Dwg 8597096)				
	Examination for defects	10		3.1	4.4.2.3
	Hardness	10		3.1	4.5.4
	Gas Check (Dwg 8853730)				
	Examination for defects	10		3.1	4.4.2.4
	Filler (Dwg 8853732)				
	Examination for defects	10		3.1	4.4.2.5
	Ring (Dwg 8860609)				
	Examination for defects	10		3.1	4.4.2.6
	Projectile Loading Assembly (Dwg 8886486)				
	Examination for defects	10		3.1	4.4.2.12
	Propelling Charge (Dwg 8853734)				
	Examination for defects	10		3.2	4.4.2.14
	Cartridge Case Assembly (Dwg 8886487)				
	Examination for defects	10		3.2	4.4.2.15
	Electrical resistance	10		3.2	4.5.1

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION (Cont'd)

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46956B(EA)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.3.2	Cartridge, 105MM, WP-T, M416		See below
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cartridge, 105MM, WP-T, M416				
	Examination for defects	10		3.2	4.4.2.17
	Cartridge case crimp	10		3.3	4.5.2
	Ballistic test				
	Muzzle velocity/Target Impact Dispersion	30		3.4.1	4.5.5.1, 4.5.5.4
	Projectile function			3.4.2	
	Tracer function			3.4.3	
	Security			3.4.4	4.5.5.2, 4.5.5.4
	145° $-5^{o}F$	25			
	-50° $+5^{o}F$	25			

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

4.4.2 Examination. See MIL-A-48078.

(a) Sampling plans. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, inspection level II.

4.4.2.1 Critical defect reporting. A report of all critical defects found, including the number of items inspected and corrective action taken, shall be prepared monthly in accordance with Data Item Description DI-R-1721 and copies delivered as specified in the contract.

4.4.2.2 Dimensional control of molded parts. In place of the normal sampling associated with the classification of defects, and subject to the approval of the Contracting Officer, the optional sampling plan in 4.4.2.2.1 may be used for dimensional control of molded parts. Use of these optional plans is unlimited to those dimensions and features controlled by the mold cavity. For all specified tests, visual examinations, and examinations of dimensions or features not developed exclusively by the mold cavity, these optional plans are not applicable. In the event of in-process reject during optional sampling, corrective action applicable to parts produced prior to the rejected, and subsequent to the last acceptable sample, shall require approval of the Contracting Officer.

4.4.2.2.1 Molded parts. A sample of five parts (as molded) shall be inspected to qualify a new or reworked cavity for use in production. The molded parts shall carry the individual cavity identification. As a control of each cavity during production, the above quantity of parts from each cavity shall be dimensionally inspected after continuous production of 5,000 parts or at the end of each week, whichever occurs first. If any defective parts are found during the qualification of the cavity, the cavity producing the defective part shall not be used in production. If any defective parts are found when inspection is performed for control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned for corrective action. All cavities removed from production because of some fault, may, after reworking, be returned to production, providing they pass the qualification test above.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Gasket		8597096
			NEXT HIGHER ASSEMBLY
			8886486

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of outside diameter with inside diameter	a	0.40%	3.1	Gage
102	Hardness			3.1	4.5.4/Test
Minor					
201	Inside diameter		0.65%	3.1	Gage
202	Outside diameter		0.65%	3.1	Gage
203	Thickness		0.65%	3.1	Gage
204	Evidence of poor workmanship		0.65%	3.7.1	Visual

NOTES:

a. See 4.4.3.2 for sample size.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Gas Check		8853730
			NEXT HIGHER ASSEMBLY
			8886486

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter at rear		0.40%	3.1	Gage
Minor					
201	Inside diameter at front		0.65%	3.1	Gage
202	Outisde diameter at front		0.65%	3.1	Gage
203	Length, total		0.65%	3.1	Gage
204	Thickness		0.65%	3.1	Gage
205	Radius missing or incorrect		0.65%	3.1	Visual
206	Evidence of poor workmanship		0.65%	3.7.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Filler				8853732
					NEXT HIGHER ASSEMBLY
					8886486
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter at rear		0.40%	3.1	Gage
Minor					
201	Length, total		0.65%	3.1	Gage
202	Inside diameter at front		0.65%	3.1	Gage
203	Outside diameter at front		0.65%	3.1	Gage
204	Radius missing or incorrect		0.65%	3.1	Gage
205	Thickness at rear (if applicable)		0.65%	3.1	Gage
206	Evidence of poor workmanship		0.65%	3.7.1	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.6	Ring		8860609
			NEXT HIGHER ASSEMBLY
			8886487

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter	a		3.1	Note a
102	Length	a		3.1	Note a
Minor					
201	Thickness		0.65%	3.1	Gage
202	Material torn or damaged		0.65%	3.1	Visual
203	Evidence of poor workmanship		0.65%	3.7.1	Visual

NOTES:

a. See 4.4.2.2 for inspection of mold control dimensions.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Projectile as Received From WP Loading Facility				8886485
					NEXT HIGHER ASSEMBLY
					8886486
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Evidence of WP leakage			3.2	Visual
Major					
101	Foreign matter present in fuze or burster cavity including WP contamination		100%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.7.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8886484
4.4.2.8	Projectile Burster Prior to Assembly to Projectile				NEXT HIGHER ASSEMBLY 8886486
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Cushioning pad missing			3.2	Visual
Major	None defined				
Minor					
201	Evidence of poor workmanship		0.65%	3.7.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.9	Projectile Loading Assembly Prior to Assembly of Plug		8886486
			NEXT HIGHER ASSEMBLY
			8886487

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Projectile burster inverted			3.2	Visual
Major					
101	Projectile burster missing		100%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.7.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46956B(EA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Projectile Loading Assembly Prior to Assembly of Fuze		8886486
			NEXT HIGHER ASSEMBLY 8886487

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Plug missing			3.2	Visual
Major					
101	Plug above flush with case impeller shoulder		100%	3.2	Manual
102	Plug fails to withstand reapplication of minimum assembly torque while sealant is wet		0.40%	3.2	Test
103	Base plug fails to withstand application of minimum assembly torque		0.40%	3.2	Test
104	Sealant missing from threads of plug prior to its assembly to case impeller		0.40%	3.2	Visual
105	Sealant missing from threads of base plug prior to its assembly to projectile		0.40%	3.2	Visual
106	Base plug above flush with rear of projectile body		0.40%	3.2	Manual
Minor					
201	Evidence of poor workmanship		0.65%	3.7.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.11	Fuze, Prior to Assembly to Projectile				8886486
					NEXT HIGHER ASSEMBLY
					8886487
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Gasket missing or damaged			3.2	Visual
Major					
101	Sealant missing from fuze threads		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.7.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.12	Projectile Loading Assembly Prior to Assembly to Cartridge Case				8886486
					NEXT HIGHER ASSEMBLY 8886487
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Gas or filler missing			3.2	Visual
Major					
101	Weight		100%	3.2	Balance
102	Fuze fails to withstand application of minimum disassembly torque with thread sealant wet		0.40%	3.2	Test
103	Depth from base of projectile body to gas check after caulking		0.40%	3.2	Gage
104	Sealant missing from tracer threads prior to assembly to fuze		0.40%	3.2	Visual
105	Tracer fails to withstand application of minimum disassembly torque with thread sealant wet		100%	3.2	Test
106	Ring missing, damaged or mislocated		0.40%	3.2	Visual
107	Length from projectile body nose to base of fuze, max.		0.40%	3.2	Gage
Minor					
201	Protective coating damaged in excess of one-quarter square inch total area		0.65%	3.7.2	Visual
202	Marking incorrect, illegible or missing, including color code band		0.65%	3.7.2	Visual
203	Evidence of poor workmanship		0.65%	3.7.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.13	Loaded Primer, Prior to Assembly to Cartridge Case				8847424
					NEXT HIGHER ASSEMBLY
					8886487
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Any flash hole missing			3.1	Visual
Major					
101	Primer check test			3.1	4.4.3.1/Test
Minor					
201	Evidence of poor workmanship		0.65%	3.7.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46956B(EA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.14	Propelling Charge Prior to Assembly to Cartridge Case		8853734
			NEXT HIGHER ASSEMBLY
			8886487

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Any opening in bag large enough to permit escape of propellant grains		100%	3.1	Visual
Minor					
201	Marking incorrect, illegible or missing (if applicable)		0.65%	3.1	Visual
202	Evidence of poor workmanship		0.65%	3.7.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.15	Cartridge Case Assembly, Prior to Assembly of Propelling Charge				8886487
					NEXT HIGHER ASSEMBLY
					None listed
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	One or more stakes missing		100%	3.2	Visual
102	Primer above flush		100%	3.2	Straight Edge
	Primer fails to withstand application of minimum disassembly torque after staking		100%	3.2	Test
103	Primer Electrode - Cartridge case circuit resistance		100%	3.2	4.5.1/Test
104	Distance from forward face of cartridge case flange to top of electrode, max.		100%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.7.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46956B(EA)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.16	Cartridge Case Assembly, Prior to Assembly of Loaded Projectile	1 OF 1	8886487
			NEXT HIGHER ASSEMBLY: None listed

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Propelling charge assembly with foil at mouth of cartridge case		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.7.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.17	Cartridge, 105MM, WP-T, M416				8886487
					NEXT HIGHER ASSEMBLY
					None listed
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Profile and alignment check		100%	3.2	4.5.3/Gage
102	Gap between shoulder of rotating band and mouth of cartridge case, max.		0.40%	3.2	Gage
103	Cartridge case crimp (bullet pull)	a		3.3	4.5.2/Test
Minor					
201	Marking incorrect, illegible or missing, including color code		0.65%	3.7.2	Visual
202	Evidence of poor workmanship		0.65%	3.7.2	Visual

NOTES:

a. See 4.4.3.3 for sample size.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.18	Unsealed Fiber Container				8836005
					NEXT HIGHER ASSEMBLY
					None listed
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Any packing component missing or improperly assembled		0.40%	3.2	Visual
Minor					
201	Cartridge cannot be removed by hand		0.65%	3.2	Manual
202	Container cap cannot be removed by hand		0.65%	3.2	Visual
203	Glue or asphalt on cartridge		0.65%	3.2	Visual
204	Evidence of poor workmanship		0.65%	3.7.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.19	Sealed Fiber Container				8836005
					NEXT HIGHER ASSEMBLY
					8836004
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Sealing tape incomplete		0.40%	3.2	Visual
102	Metal end loose or distorted		0.40%	3.2	Visual/Manual
103	Container cut or damaged through all asphalt impregnated layers		0.40%	3.2	Visual/Manual
Minor					
201	Sealing tape tab length, min.		0.65%	3.2	Gage
202	Contents loose		0.65%	3.2	Manual
203	Cuts, scuffs, or gouges in outer layer		0.65%	3.2	Visual
204	Gap between cover and body of container exceeds one-eighth inch		0.65%	3.2	Visual
205	Evidence of poor workmanship		0.65%	3.7.1	Visual
206	Marking incorrect, illegible or missing		0.65%	3.7.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.20	Sealed Wood Packing Box				8836004
					NEXT HIGHER ASSEMBLY
					None listed
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Box damaged, exposing contents		0.40%	3.2	Visual
102	Hardware or strapping missing, broken, or loose		0.40%	3.2	Visual/Manual
103	Marking incorrect, illegible, or missing, including DOD symbol		0.40%	3.7.2	Visual
Minor					
201	Hardware or strapping improperly assembled		0.65%	3.2	Visual/Manual
202	Handle missing or not secure		0.65%	3.2	Visual/Manual
203	Car seal missing, unsealed, or improperly positioned		0.65%	3.2	Visual
204	Evidence of poor workmanship		0.65%	3.7.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Check test for deterioration of primers. (See applicable primer specification) Major Defect. If the total elapsed time between the original acceptance of any primer lot and the assembly of that lot into cartridges exceeds two years, or if the primers have been subjected to adverse conditions, however brief, at any time since previous tests, the applicable primer lot shall be subjected to and must satisfactorily pass the check test specified in the applicable primer specification before that primer lot is assembled into cartridges. The test shall be performed by the contractor on assemblies selected by the Contracting Officer's representative at the facility assembling the complete round cartridges (see 6.3).

4.4.3.2 Hardness of gasket. (See Dwg 8597096) Major Defect. Ten gaskets from each lot shall be tested as specified in 4.5.4 for hardness. Any failure of a gasket to comply with the requirements on the applicable drawing shall reject the lot of gaskets which it represents.

4.4.3.3 Cartridge case crimp. (See 3.3 and Dwg 8886487) Major Defect. The sampling plan and acceptance criteria for this test shall be in accordance with MIL-STD-414, Section B, Part II, Table B3, Code Letter I and an AQL of 1.5 percent. The test method and procedure shall be as prescribed in 4.5.2. The samples chosen for this test shall have passed the profile and alignment check specified in 4.5.3.

4.4.3.4 Proving ground tests. The following tests shall be performed as specified in 4.5.5. All samples shall be observed for safety (see 3.4.4).

4.4.3.4.1 Muzzle velocity. (See 3.4.1) Major Defect. Beginning with the first lot produced and continuing until three consecutive lots have complied with the requirements specified herein, the sampling plan and acceptance criteria for this test shall be in accordance with MIL-STD-414, Section B, Part II, Table B3, Code Letter J; and an AQL of 1.0 percent shall be used. In addition, if the muzzle velocity standard deviation, multiplied by the factor (0.77), exceeds 10.5 fps, the lot shall be rejected.

4.4.3.4.1.1 Reduced sampling. After three consecutive lots have met the acceptance criteria of 4.4.3.4.1, the sampling plan and acceptance criteria for this test shall be in accordance with MIL-STD-414, Section B, Part II, Table B3 Code Letter G; and, an AQL of 1.0 percent shall be used. In addition, if the muzzle velocity standard deviation, multiplied by the factor (0.65), exceeds 10.5 fps, the lot shall be rejected.

4.4.3.4.2 Functioning (see 3.4.3). Major Defect. The sample cartridges used in the test for muzzle velocity shall be observed for functioning on first or subsequent ground impact. When on tightened sampling for muzzle velocity (see 4.4.3.4.1), if three or more projectiles fail to function, the lot shall be rejected. When on reduced sampling (see 4.4.3.4.1.1), if two or more projectiles fail to function, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

4.4.3.4.3 Tracer functioning (see 3.4.2). Major Defect. All samples fired in ballistic tests shall be observed for tracer functioning. When on tightened sampling for muzzle velocity (see 4.4.3.4.1), if three or more tracers fail to function to the 2000 meter cloth target, the lot shall be rejected. When on reduced sampling (see 4.4.3.4.1.1), if two or more tracers fail to function to the 2000 meter cloth target, the lot shall be rejected.

4.4.3.4.4 Security (see 3.4.4). Critical Defect. Beginning with the first lot produced and continuing until three consecutive lots have complied with the requirements of 4.4.3.4.1, twenty-five samples, each, shall be conditioned to -50° + 5°F and 145° - 5°F; and fired for security. All samples shall be observed for premature functioning and projectile integrity from the gun's muzzle to ground impact. When on reduced sampling for muzzle velocity, ten cartridges shall be selected for this test and fired at 145° - 5°F, only.

4.4.4 Inspection equipment. The inspection equipment required by the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with 4.4.2.3. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract (see 6.2 herein and Section 6 of MIL-A-48078).

4.5 Test methods and procedures.

PRECAUTION. This specification covers sampling and testing of chemical, toxic or explosive materials which are potentially hazardous to personnel. Accordingly, it is emphasized that all applicable safety rules, regulations and procedures must be followed in handling and processing these materials.

4.5.1 Primer electrode - cartridge case circuit resistance. The electrical resistance between the primer electrode and the cartridge case shall be measured using an electrical circuit which limits the current through the primer to twenty milli-amperes (20mA), maximum, with the primer electrode as one contact point and the cartridge case as the other.

4.5.2 Cartridge case crimp (bullet pull). The samples selected for this test shall be tested in an appropriate tensile testing machine in order to determine the security of the cartridge case's crimp to the projectile. The load shall be applied in an axial direction with the testing machine head's rate of travel set at 0.100 inch per minute, minimum, to 0.125 inch per minute, maximum.

4.5.3 Profile and alignment. Each crimped cartridge's profile and alignment shall be verified by a gage corresponding to Dwg 8828098, which is to be horizontal within 0° $\pm$ 2.5°. The cartridge shall be inserted into the gage in accordance with the requirements of Dwg 8886487. The profile and alignment gage shall not be utilized as an alignment tool.

4.5.4 Hardness of gasket. Each gasket selected for this test shall have its hardness measured at three equidistant points on either of its flat surfaces.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

The test method and equipment required to perform this test shall be as prescribed by ASTM E18.

4.5.5 Proving ground tests. The samples ballistically tested herein shall be fired in a M68 gun. The ammunition in each phase shall be conditioned to the specified temperature until all propellant is stablized at a uniform temperature prior to firing, which normally requires a period of twenty-four hours, minimum. Sufficient warmers or spotters shall be fired by the proving ground to assure the temperature stabilization of the weapon prior to the start of any phase of these tests. Maximum chamber pressure (M11 gages) shall be recorded for all reference cartridges fired. Muzzle velocity shall be recorded for all projectiles, including warmers and spotters. All cartridges shall be observed for safety (see 6.4).

4.5.5.1 Muzzle velocity/target impact dispersion phase. The data generated in this phase will be used for the determination of acceptance from a muzzle velocity standpoint and will require the firing of reference cartridges to estalbish a velocity correction. This phase will be fired using a M60 series tank and a gun tube with a full to a fifty percent remaining life, minimum. The firing sequence shall be 5 reference, 15 test and 5 reference cartridges; or, when on tightened sampling, the sequence shall be 5 reference, 15 test, 5 reference, 15 test and 5 reference cartridges. All rounds fired shall be observed for security, projectile and tracer functioning and target impact dispersion. The ammunition fired in this phase shall be temperature conditioned to 70° $\pm$ 2.5°F (21° $\pm$ 1.5°C).

4.5.5.1.1 Target impact dispersion.

4.5.5.1.1.1 Target size and distance. The vertical cloth target distance is to be 2000 meters and the target size is to be 6 meters by 6 meters, minimum.

4.5.5.1.1.2 Grouping and cadence. The test and reference cartridges shall be fired in five round groups (occassions), with a cadence of not less than three minutes and not more than five minutes between successive firings. A cadence of less than three minutes may be used; however, this cadence must be maintained for all rounds to be fired on that occassion.

4.5.5.1.1.3 Removal of backlash from fire control system. After loading and locking a round in the gun chamber, the gunner shall traverse the gun off the center of the target, drop down below target center, traverse to the side opposite target center, elevate to target center, and traverse the gun back onto target center. If the gun sight indicates that the gun is aimed above or beyond target center, do not reverse the direction of the movement of the gun; but, instead, repeat the above traversing sequence. The distance traversed and dropped should be sufficient to remove backlash from the fire control system.

4.5.5.1.1.4 Spotting the target. Spotter rounds will be used to assure that the weapon is zeroed to assure engagement of target center. A minimum of three consecutive target hits within a circle of 1 mil radius from the center of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

target by the spotters which had been fired at the same elevation and deflection are required. An aiming point or reference cartridges may be used for this purpose. Once the weapon has been spotted on the target for a shot group, the elevation and deflection of the weapon thus determined shall remain the same for that shot group.

4.5.5.1.1.5 Calculation of probable error. Target impacts shall be measured to the nearest inch (2.54 centimeters) in both the horizontal and vertical distance from the center of the target. The vertical and horizontal hit pattern results for each shot group shall be expressed as probable errors in mils, pooled, and then recorded on the firing record (see 6.5 for calculation of pooled probable error).

4.5.5.1.2 Functioning. All test samples fired in the muzzle velocity/target impact dispersion phase shall be observed for projectile funtioning upon first or subsequent ground impact and recorded on the firing record. A distinction should be made whether a projectile functioned on first impact, subsequent impact, or failed to function.

4.5.5.1.2.1 Impact zone soil conditions. The proving ground shall use a firing point such that the area to the rear of the location of the vertical cloth target shall be free of mud, running or standing polls of water, or spongy soil conditions when observing projectile functioning for lot acceptance. A statement descriptive of soil conditions in the impact area shall be made by the test director and shall appear on the firing record (see 6.4.2).

4.5.5.1.3 Tracer functioning. All projectiles shall be observed for tracer functioning to the 2000 meter target. For projectiles with short tracer burn times, the distance over which the tracer burns shall be recorded to the nearest estimated 500 meters (i.e., failure, 500 meters, 1000 meters, 1500 meters).

4.5.5.2 Security phase. The data generated in the phase will primarily be used to determine the acceptance of a lot from a projectile metal parts integrity standpoint. The samples selected for this phase shall be temperature conditioned to -50 + 5°F (-45.5° + 3°C) or 145° - 5°F (63 -3°C) prior to firing. A fifty percent to a twenty-five percent remaining life, minimum, tube shall be used. Each sample fired shall be observed for breakup of projectile metal parts (in particular, a stream of smoke emanating from the projectile), tracer functioning, and projectile upon ground impact.

4.5.5.3 Assembly of reference ammunition. The reference projectiles shall be inertly loaded and assembled at the proving ground so as to assure an as-fired weight of 24.80 ± 0.02 pounds. These projectiles and other reference components shall be assembled into cartridges and crimped in accordance with the requirements of Dwg 8886487.

4.5.5.4 Safety. All cartridges fired in the proving ground tests shall be observed for premature bursts, hang-fires, or breakup of projectile metal parts. A premature burst or functioning, is the functioning, high or low

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

order, of a projectile at a time which is earlier that expected, that is, prior to impact with the intended target. The intended target when collecting target impact dispersion data is the ground impact area located behind the vertical target; and, not the vertical cloth target itself. Any test sample failing the safety criteria specified herein shall be cause for the cessation of the test phase in which the failure occurs, as well as, the remainder of the ballistic test; and, shall reject the lot represented by the failing test sample.

4.5.5.5 Retest. If for any reason the proving ground considers that test conditions have detrimetally affected the test results, additional cartridges, as necessary, shall be tested. A lot shall be retested whenever the proving ground deems it necessary; or, whenever any of the following conditions exist:

(a) The muzzle velocity correction factor computed from the average corrected muzzle velocity of the reference projectiles exceed 30 fps;

(b) The muzzle velocity standard deviation of the reference projectiles, multiplied by the factor 0.64 or 0.77, as applicable, exceeds 10.5 fps;

(c) Two or more test sample velocities are lost by the velocity-measuring equipment, when recording muzzle velocities for acceptance of a lot.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. The cartridge shall be preserved and packed in accordance with the requirements of Dwg 8836005.

5.2 Packing. The cartridge, in containers, shall be packed, Level A, in accordance with the requirements of Dwg 8836004.

5.3 Marking. The fiber containers and wooden packing boxes shall be marked and sealed in accordance with the requirements of Dwgs 8836004 and 8836005.

6. NOTES

6.1 Ordering data. See MIL-A-48078.

6.1.1 Procurement requirements. In addition to the requirements of MIL-A-48078, procurement documents shall specify the following:

(a) Provisions for Government verification inspection;

(b) Contractor warranty of components, which the contractor procures, for 180 days;

(c) Resubmission of a first article sample when a lapse in production of a significant change in manufacturing process occurs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

6.1.2 Data requirements. Deliverable data required by this specification is cited in the following paragraphs:

Paragraph	Data Requirement	Applicable DID
4.4.2.1	Quality Inspection Defect Report	DI-R-1721

(Copies of data item descriptions required by the contractor in connection with specific procurement functions should be obtained from the procuring acitivity or as directed by the Contracting Officer.)

6.1.2.1 Delivery of data to the technical activity. The following address is to be added to those listed in the contract (Form DD 1423) for delivery of one copy, each, to the technical activity, of the Ammunition Data Cards prepared by the contractor for the duration of the contract: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-TSC-S, Aberdeen Proving Ground, MD 21010.

6.2 Submission of inspection equipment designs. See 6.2.3 of MIL-A-48078. Submit inspection equipment designs as required to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, NJ 07801 and Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAC-D, Aberdeen Proving Ground, MD 21010.

6.3 Cost of primer check test. The Contracting Officer shall arrange for the contractor to be reimbursed for the expense incurred in the performance of the check tests. The test shall be conducted at Government expense without cost to the contractor who loaded the assemblies or to the contractor assembling the cartridge, and shall not constitute a bases for rejection against either contractor, except where deterioration has occurred as direct result from carelessness in handling, storage, etc., permitted while the primer lot was under the jurisdiction of either contractor.

6.4 Firing record information. The firing records shall include the serial numbers and nomenclature of all weapon and fire control components, weapon to target azimuth, target impact plots, meteorological data and component lot numbers of stock warmers and spotters used. Each round fired during a test shall be identified on the record in the sequence of firing. For each found fired, the record shall contain deflection, elevation, time of firing, muzzle velocity, tracer functioning, horizontal and vertical target impact coordinates and pertinent flight characteristics.

6.4.1 Delivery of firing records to the technical activity. The following addresses are to be added to the Ballistic Test Request (BTR) for the delivery of ballistic test reports to the technical activity: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-E and DRDAR-LCU-CV, Dover, NJ 07801.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

6.4.2 Impact field selection. Since this projectile will impact the ground with an acute angle of impact, the condition of the impact field is significant in the likelihood of the proper functioning of a projectile. Muddy, badly-cratered, or an excessively soft impact field characteristically would yield functioning results poorer than those of a firm, drop, or plowed field. The field chosen should be of a positive slope, well drained, and within good view of the spotters who are to determine whether or not a projectile has functioned as required.

6.5 Method for calculating pooled probable error. The individual probable error (PE) results of each of the "n" groups fired shall be pooled according to the following method:

$$\text{Pooled PE} = \frac{\sum_{i=1}^{n} (SS_i - 1)\,(PE_i)^2}{\sum_{i=1}^{n} (SS_i - 1)}^{1/2}$$

Where PE_i and SS_i are the probable error value and sample size, respectively, for each of the "n" groups of five samples each which were fired for muzzle velocity/target impact dispersion data.

6.6 Changes from previous issue. Due to the extensiveness of the changes, asterisks are not used in this revision to identify changes with respect to the previous issue.

6.7 Proving ground test summary.

Test Phase	Sample Size	Requirements	Sampling	Procedure
MV/TID	15*	Velocity	4.4.3.4.1	4.5.5.1.1
		Functioning	4.4.3.4.2	4.5.5.1.2
		Tracer Funct.	4.4.3.4.3	4.5.5.1.3
		Safety	4.4.3.4	4.5.5.4
Security	10**	MPTS Security	4.4.3.4.4	4.5.5.2
145° - 5°F		Safety	4.4.3.4	4.5.5.4

*When on tightened sampling for muzzle velocity, the sample size is 30 cartridges for the MV/TID phase.

**When on tightened sampling for muzzle velocity, the sample size for the security phase is 25 cartridges, each, at 145° - 5°F and -50° + 5°F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

Custodian:

Army - EA

Preparing Activity:

Army - EA

Project Number 1315-A230

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION
MIL-C-46956B

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?
   ☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Research
and Development Command
ATTN: DRDAR-TSC-S
Aberdeen Proving Ground, MD 21010

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:24Z
Check the source to verify that this is the current version before use.