MIL-M-46960D (PA)
9 June 1975
Superseding
MIL-M-46960C (MU)
17 December 1971

MILITARY SPECIFICATION

MINE, ANTIPERSONNEL, M16A2
PARTS FOR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the parts for one type of mine designated as Mine, Antipersonnel, M16A2.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this Specification to the extent specified herein.

*SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition Standard Quality Assurance Provisions, General Specification for

*STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

DRAWINGS

U.S. ARMY PICATINNY ARSENAL

8885204 - Mine, Anti-personnel, M16A2, Metal Parts Arrangement

5332

FSC: 1345

S/S release

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:25Z
Check the source to verify that this is the current version before use.

(Copies of Specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

*For meaning of asterisk see paragraph 6.5.

3. REQUIREMENTS

3.1 Material. - Materials shall be in accordance with applicable drawings and specifications.

3.2 Parts. - The mine parts shall comply with all requirements specified on applicable drawings, and with all requirements specified in applicable specifications.

*3.3 Workmanship. - All parts and assemblies shall be fabricated and finished in a thorough workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part or assembly nor shall they be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat, legible and sharply defined.

3.4 First Article Inspection. - This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

*4.1 Responsibility for Inspection and Standard Quality Assurance Provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

*4.2 Classification of inspections. - The following types of inspection shall be conducted on this item.

a. First Article Inspection

b. Quality Conformance Inspection

5332

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:25Z
Check the source to verify that this is the current version before use.

4.3 First Article Inspection

*4.3.1 Submission. - The contractor shall submit a first article sample (see 6.2c) as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2 and 4.3.3. The first article sample shall consist of fifty (50) complete sets of parts (i.e., 50 each of every component and every subassembly) and fifty (50) crimped can and cover assemblies.

*4.3.2 Inspections to be performed. - First article samples shall be inspected in accordance with the examination for defects paragraphs 4.4.2.1 thru 4.4.2.15 and the container assemblies shall be subjected to the tests of 4.5.1 and 4.5.2 in that order.

*4.3.3 Rejection. - (See MIL-A-48078).

4.4 Quality conformance inspection

*4.4.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

*4.4.2 Examination. - (See MIL-A-48078). Unless otherwise specified in the classification of defects and test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:25Z
Check the source to verify that this is the current version before use.

90%
5332

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-46960D (PA)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 8864743
*4.4.2.1	Body				NEXT HIGHER ASSEMBLY 8885204
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Pitch diameter of well thread		0.40%	3.2	Gage
102	Minor diameter of well thread, max		0.40%	3.2	Gage
103	Perpendicularity of well counterbore to pitch diameter of thread		0.40%	3.2	Gage
104	True position of well counterbore to the pitch diameter of thread		0.40%	3.2	Gage
Major B					
131	Total height		0.40%	3.2	Gage
132	Wall thickness, min.		0.40%	3.2	Gage
133	Outside diameter, max		0.40%	3.2	Gage
134	Depth of well counterbore		0.40%	3.2	Gage
135	Diameter of well counterbore		0.40%	3.2	Gage
136	Protective coating on interior inadequate (bare spot)		0.40%	3.2	Visual
137	Diameter of bourrelet		0.40%	3.2	Gage
138	Height of bourrelet, min		0.40%	3.2	Gage
Minor					
201	Exterior protective finish unsatisfactory (cuts or deep scratches)		0.65%	3.2	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:25Z
Check the source to verify that this is the current version before use.

3332

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-46960D (PA)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 8864743
*4.4.2.1 (cont)	Body				NEXT HIGHER ASSEMBLY 8885204
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
202	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

5

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:25Z
Check the source to verify that this is the current version before use.

5382

6

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-46960D (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.2	Cup, Detonator		8796341
			NEXT HIGHER ASSEMBLY 8885204

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Outside diameter		0.40%	3.2	Gage
132	Inside diameter		0.40%	3.2	Gage
133	Thickness thru bottom, min		0.40%	3.2	Gage
134	Diameter of flange		0.40%	3.2	Gage
Minor					
201	Total length		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:25Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
*4.4.2.3	Well		8864745
			NEXT HIGHER ASSEMBLY
			8885204

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Pitch diameter of exterior thread		0.40%	3.2	Gage
102	Major diameter of exterior thread		0.40%	3.2	Gage
103	Pitch diameter of delay holder thread		0.40%	3.2	Gage
104	Minor diameter of delay holder thread, max		0.40%	3.2	Gage
105	Length of delay holder thread, min		0.40%	3.2	Gage
106	Pitch diameter of bushing thread		0.40%	3.2	Gage
107	Minor diameter of bushing thread, max		0.40%	3.2	Gage
108	Length of bushing thread, min		0.40%	3.2	Gage
109	True position of outside diameter of flange with exterior threads		0.40%	3.2	Gage
Major B					
131	Outside diameter of bottom flange, max		0.40%	3.2	Gage
132	Thickness of bottom flange		0.40%	3.2	Gage
133	Total height		0.40%	3.2	Gage
134	Location of flash pipe		0.40%	3.2	Gage
135	Inside diameter of flash pipe, max		0.40%	3.2	Gage
136	Depth of booster well, min		0.40%	3.2	Gage
137	Diameter of booster well		0.40%	3.2	Gage
138	Depth of propelling charge counterbore		0.40%	3.2	Gage
139	Diameter of propelling charge counterbore		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:25Z
Check the source to verify that this is the current version before use.

5332

8

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-46960D (PA)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 8864745
*4.4.2.3 (cont.)	Well				NEXT HIGHER ASSEMBLY 8885204
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major B					
140	Diameter of flash disc counterbore		0.40%	3.2	Gage
141	Wrench slots location and size, min		0.40%	3.2	Gage
Minor					
201	Location of booster well		0.65%	3.2	Gage
202	Location of filling hole		0.65%	3.2	Gage
203	Diameter of filling hole, max		0.65%	3.2	Gage
204	Depth of filling hole counterbore		0.65%	3.2	Gage
205	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:25Z
Check the source to verify that this is the current version before use.

5332

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-46960D (PA)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
*4.4.2.4	Plug, Shipping	1 OF 1	8796349
			NEXT HIGHER ASSEMBLY 8885204

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Pitch diameter of thread		0.40%	3.2	Gage
132	Major diameter of thread		0.40%	3.2	Gage
133	Length to hexagon		0.40%	3.2	Gage
134	Threads damaged		0.40%	3.2	Visual
Minor					
201	Width of undercut, max		0.65%	3.2	Gage
202	Overall length		0.65%	3.2	Gage
203	Width across hexagon		0.65%	3.2	Gage
204	Diameter of undercut		0.65%	3.2	Gage
205	Protective coating damaged exposing base metal		0.65%	3.2	Visual
206	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22 07:25Z
Check the source to verify that this is the current version before use.

5332

10

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-46960D (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8796355
*4.4.2.5	Spool Assembly				NEXT HIGHER ASSEMBLY 8885204
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Wire unreeling or poorly tacked		0.40%	3.2	Visual
132	Wire missing or damaged (cut or nicked)		0.40%	3.2	Visual
Minor					
201	Wire above spool surface		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:25Z
Check the source to verify that this is the current version before use.

5337

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-46960D (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8796359
*4.4.2.6	Bushing				NEXT HIGHER ASSEMBLY 8885204
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Pitch diameter of internal thread		0.40%	3.2	Gage
102	Minor diameter of internal thread, max		0.40%	3.2	Gage
103	Pitch diameter of external thread		0.40%	3.2	Gage
104	Major diameter of external thread		0.40%	3.2	Gage
Major B					
131	Overall length		0.40%	3.2	Gage
132	Length to flange		0.40%	3.2	Gage
133	Inside diameter		0.40%	3.2	Gage
134	Wrench flats location and size, max		0.40%	3.2	Gage
Minor					
201	Width of external thread undercut below flange, max		0.65%	3.2	Gage
202	External thread damaged		0.65%	3.2	Visual
203	Protective coating damaged exposing base metal		0.65%	3.2	Visual
204	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:25Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-46960D (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.7	Housing, Delay		8796371
			NEXT HIGHER ASSEMBLY 8885204

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Major diameter of thread		0.40%	3.2	Gage
102	Pitch diameter of thread		0.40%	3.2	Gage
Major B					
131	Total length		0.40%	3.2	Gage
132	Diameter of charge cavity		0.40%	3.2	Gage
133	Wrench slots location and size, min		0.40%	3.2	Gage
Minor					
201	Thickness thru bottom of charge cavity		0.65%	3.2	Gage
202	Diameter of charge cavity counterbore		0.65%	3.2	Gage
203	Diameter of flash hole in bottom		0.65%	3.2	Gage
204	Outside diameter		0.65%	3.2	Gage
205	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:25Z
Check the source to verify that this is the current version before use.

5332

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-46960D (PA)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
*4.4.2.8	Washer, Delay	1 OF 1	8796372
			NEXT HIGHER ASSEMBLY 8885204

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Outside diameter		0.40%	3.2	Gage
132	Height		0.40%	3.2	Gage
133	Diameter of hole		0.40%	3.2	Gage
134	Taper of hole		0.40%	3.2	Gage
135	Corners not sharp		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:25Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-46960D (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.9	Disc, Filler		8864737
			NEXT HIGHER ASSEMBLY 8885204

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Diameter		0.40%	3.2	Gage
132	Thickness		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:25Z
Check the source to verify that this is the current version before use.

5332

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-46960D (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8864738
*4.4.2.10	Disc, Sealing				NEXT HIGHER ASSEMBLY 8885204
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Diameter		0.40%	3.2	Gage
132	Thickness		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:25Z
Check the source to verify that this is the current version before use.

5.3.32

16

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-46960D (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.11	Disc, Flash		8861739
			NEXT HIGHER ASSEMBLY 8885204

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Diameter		0.40%	3.2	Gage
132	Thickness		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:25Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.12	Holder, Delay		8864742
			NEXT HIGHER ASSEMBLY 8885204

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Pitch diameter of interior thread		0.40%	3.2	Gage
102	Minor diameter of interior thread, max		0.40%	3.2	Gage
103	Length of interior thread, max		0.40%	3.2	Gage
104	Pitch diameter of exterior thread		0.40%	3.2	Gage
105	Major diameter of exterior thread		0.40%	3.2	Gage
106	Length of exterior thread, min		0.40%	3.2	Gage
Major B					
131	Total length		0.40%	3.2	Gage
132	Length to delay assembly cavity		0.40%	3.2	Gage
133	Diameter of detonator hole		0.40%	3.2	Gage
134	Outside diameter, max		0.40%	3.2	Gage
135	Wrench slots location and size, min		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:25Z
Check the source to verify that this is the current version before use.

5332

18

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-M-46960D (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8864744
*4.4.2.13	Container, Assembly, without Top Cover				NEXT HIGHER ASSEMBLY 8885204
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Inside diameter, min		0.40%	3.2	Gage
132	Inside height, min		0.40%	3.2	Gage
133	Thickness of sidewall and bottom (prior to forming)		0.40%	3.2	Gage
134	Diameter of bottom well face, min		0.40%	3.2	Gage
135	Protective coating inadequate (bare spots other than slight scratches		0.40%	3.2	Visual
Minor					
201	Outside diameter, max		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:25Z
Check the source to verify that this is the current version before use.

5332

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-46960D (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8864744
*4.4.2.14	Top Cover				NEXT HIGHER ASSEMBLY 8885204
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Diameter of bushing hole		0.40%	3.2	Gage
132	Location of bushing hole		0.40%	3.2	Gage
133	Diameter of well face, min		0.40%	3.2	Gage
134	Height to well face		0.40%	3.2	Gage
Minor					
201	Radius missing		0.65%	3.2	Visual
202	Protective coating improper or inadequate		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:25Z
Check the source to verify that this is the current version before use.

5.3.3.2

20

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-M-46960D (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.15	Cup, Lining		8880564
			NEXT HIGHER ASSEMBLY
			8885204

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Inside diameter		0.40%	3.2	Gage
132	Height		0.40%	3.2	Gage
133	Wall thickness		0.40%	3.2	Gage
134	Protective coating inadequate exposing base metal		0.40%	3.2	Visual
Minor					
201	Radii, max		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:25Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

*4.4.3.1 Air pressure test of crimped container assembly (see dwg. 8864744) Major B defect. - Eighty (80) samples shall be selected from each lot and tested as specified in 4.5.1 using equipment in accordance with 4.4.4. If two (2) or more assemblies fail to comply with the applicable drawing requirements the lot shall be rejected.

*4.4.3.2 Seam tensile strength (see dwg. 8864744) Major B defect. - Fifty (50) samples shall be selected from the samples previously subjected to the air pressure test of 4.4.3.1 and tested as specified in 4.5.2 using equipment in accordance with 4.4.4. If two (2) or more assemblies fail to comply with the applicable drawing requirements the lot shall be rejected.

*4.4.4 Inspection Equipment. - The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/ Inspection Method' column in the tables starting with paragraph 4.4.2.1, and the test method paragraphs (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and 6.3 herein.

4.5 Test methods and procedures

4.5.1 Air pressure test of crimped container assembly. - The crimped container assembly shall be subjected to an internal air pressure as specified on the applicable drawing. The interior volume of the container shall be filled with a solid cylinder such that the free volume remaining between the cylinder and the container shall not exceed two cubic inches. Provision may be made in the cylinder for air passages or test equipment adapter provided the maximum free volume is not exceeded. Observation shall be made for a pressure drop as specified in 4.4.3.1. Test equipment shall be in accordance with 4.4.4.

4.5.2 Seam tensile strength. - A tensile test specimen, which is one inch wide at the seam and for at least one inch in both directions from the seam, shall be cut from the container assembly. The specimen shall be pulled apart in a tensile testing device capable of measuring the load applied to plus or minus five pounds. Observation shall be made to determine compliance with the applicable drawing requirement. Test equipment shall be in accordance with 4.4.4.

5332

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:25Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging, Packing and Marking

5.1.1 Level C. - Packaging, Packing and marking shall be in accordance with MIL-STD-1169.

6. NOTES

*6.1 Intended use. - The metal parts covered by this specification are intended for assembly of the M16A2 anti-personnel mine.

*6.2 Ordering data. - Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Provisions of MIL-A-48078.

c. Provisions for submission of first article samples.

*6.3 Submission of Inspection Equipment Designs for Approval. (See MIL-A-48078). Submit equipment designs as required, to Commander: Picatinny Arsenal, ATTN: SARPA-QA-T-T Dover, New Jersey 07801.

*6.4 Distribution of ammunition data cards. - Distribution of data cards shall include the following: Commander, Picatinny Arsenal, ATTN: SARPA-QA-A-M, Dover, New Jersey 07801.

6.5 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1345-A-131

5332

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:25Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

5332

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:25Z
Check the source to verify that this is the current version before use.