NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/47E
15 November 1996
SUPERSEDING
MIL-B-3628/47D
30 July 1993

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, RIFLE TEAM MATCHES, MARINE CORPS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

DASH NO.	TITLE
-1:	Elliott Trophy Rifle Team Match
-2:	San Diego Trophy Rifle Team Match
-3:	Wharton Trophy Rifle Team Match
-4:	Wirgman Trophy Rifle Team Match
-5:	Lloyd Trophy Rifle Team Match
-6:	Smith Trophy Rifle Team Match

MATERIAL: Red Brass

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:06Z
Check the source to verify that this is the current version before use.

FINISH:
OBVERSE:
PENDANT: Gold Plated, Rose Gold Plated, Relieved, Polished Highlights.
SUSPENSION BAR AND LINKS: Gold Plated, Rose Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 20.
REVERSE:
PENDANT: Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.
SUSPENSION BAR AND LINKS: Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

DIMENSIONS:
HEIGHT (Overall):
ASSEMBLED: 2 inches (5.08 cm) (REF)
PENDANT (Excluding Lugs): 1-9/16 inch (3.97 cm) (REF)
SUSPENSION BAR (Excluding Lugs): 7/32 inch (0.56 cm) (REF)
WIDTH (Overall):
PENDANT: 1-5/16 inch (3.33 cm) (REF)
SUSPENSION BAR: 1-3/16 inches (3.02 cm) (REF)
THICKNESS:
PENDANT (At Thickest Point): 0.110 inch ± 0.005 inch (0.279 cm ± 0.012 cm)
SUSPENSION BAR (At Rim): 0.065 inch ± 0.005 inch (0.165 cm ± 0.012 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The lugs are an integral part of both the pendant and the suspension bar.

3. The connecting links shall be formed from 0.042 inch ± 0.002 inch (0.107 cm ± 0.005 cm) diameter wire, shall be oblong shaped and 3/16 inch ± 1/64 inch (0.48 cm ± 0.04 cm) long by 1/8 inch ± 1/64 inch (0.32 cm ± 0.04 cm) wide.

4. The attaching device shall be a prong and flat ball clutch type. The prongs shall be located on the horizontal center line of the back of the suspension bar equidistant from each end and 7/8 inches ± 1/32 inch (2.22 cm ± 0.08 cm) apart.

5. Dash Numbers -1 through -6 have the same design. Only the name on the suspension bar differs. Dash No. -1 is shown as an illustrative example.

Custodian:
Army - IH
Navy - NU
Review activities:
Navy - MC
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0864)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:06Z
Check the source to verify that this is the current version before use.