INCH-POUND

MIL-DTL-3628/48J
15 September 2014
SUPERSEDING
MIL-DTL-3628/48H
15 August 2009

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, PISTOL TEAM MATCHES, U.S. MARINE CORPS

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.



DASH NO.
-1: HOLCOMB PISTOL TEAM MATCH
-2: EDSON PISTOL TEAM MATCH
-3: SHIVELY PISTOL TEAM MATCH
-4: FINN PISTOL TEAM MATCH

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH:
OBVERSE:
PENDANT: 24K Gold Plated, Relieved, Polished Highlights and shall match The Institute of Heraldry (TIOH) Metal Chip Number 8.
SUSPENSION BAR AND LINKS: 24K Gold Plated, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:06Z
Check the source to verify that this is the current version before use.

REVERSE:
PENDANT: 24K Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.
SUSPENSION BAR AND LINKS: 24K Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

DIMENSIONS:
HEIGHT (Overall):
ASSEMBLED: 2 inches (REF)
PENDANT (Excluding Lugs): 1-1/2 inch (REF)
SUSPENSION BAR (Excluding Lugs): 9/32 inch (REF)
WIDTH (Overall):
PENDANT: 1 inch (REF)
SUSPENSION BAR (Including Balls): 1-17/32 inches (REF)
THICKNESS:
PENDANT (At Thickest Point): 0.110 inch ± 0.005 inch
SUSPENSION BAR (At Rim): 0.065 inch ± 0.005 inch

ATTACHING DEVICE AND LINKS:
1: The attaching device shall be a prong and flat ball clutch type

2: The prongs shall be located on the horizontal center line of the back of the suspension bar equidistant from each end and 1-1/8 inches ± 1/32 inch apart.

3: The connecting links shall be formed from 0.042 inch ± 0.002 inch diameter wire, shall be oblong shaped and 3/16 inch ± 1/64 inch long by 1/8 inch ± 1/64 inch wide.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The lugs are an integral part of both the pendant and the suspension bar.

3. For dash -1 through dash -4 shall have the same design except for the suspension bar. The name on the suspension bar shall match dash number as indicated.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Navy - MC

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2014-197)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:06Z
Check the source to verify that this is the current version before use.