
MIL-B-3628 / 49C
31 October 1969
SUPERSEDING
MIL-B-3628/49B
11 July 1968

MILITARY SPECIFICATION SHEET

Badge, Qualification, GLIDER, Army

This specification is mandatory for use by all Departments and Agencies of the Department of Defense. The complete requirements for procuring the item(s) described herein shall consist of this document and the issue in effect of Specification MIL-B-3628.



DASH NO.

-1: Regular Size
-2: Dress Miniature
-3: Regular Size, Subdued



MATERIAL:
-1,-2: 1/20 SILVER FILLED (FRONT ONLY) OVER A COMMERCIAL COPPER BASE ALLOY
(C) -3: RED BRASS OR ALUMINUM

DIMENSIONS (INCHES):
HEIGHT (OVERALL):
-1,-3: 11/16 (REF)
-2: 13/32 (REF)
WIDTH (OVERALL):
-1,-3: 1-1/2 (REF)
-2: 7/8 (REF)
THICKNESS (AT THICKEST POINT):
-1,-3: .110 ± .010
-2: .080 ± .005

FINISH:
-1,-2: SILVER PLATED, OXIDIZED RELIEVED SATIN FINISH. REVERSE AND EDGES CLEAN.
(C) -3: DULL FLAT BLACK ENAMEL FINISH OR ANODIZED AND DYED AS APPLICABLE

NOTES:
1. A FORCER MAY BE USED TO BRING UP THE DESIGN OF THE GLIDER NOSE FOR DASH NOS. 1 AND 3 ONLY.

2. THE ATTACHING DEVICE SHALL BE PRONG AND CLUTCH TYPE. THE PRONGS SHALL BE LOCATED AT THE INTERSECTION OF THE GLIDER WING AND THE CENTER OF THE FEATHERED WING.

3. PIERCING INDICATED IS FOR DASH NOS. 1 AND 3 ONLY.

4. DASH NOS. 1 AND 2 MAY BE MADE FROM STERLING SILVER FOR COMMERCIAL SALE AND IF SO THE THICKNESS DIMENSIONS GIVEN SHALL BE USED FOR REFERONLY. THE WEIGHTS SPECIFIED BELOW SHALL GOVERN. THE FINISH FOR STERLING SILVER BADGES SHALL BE AS SPECIFIED EXCEPT THE REQUIREMENT FOR SILVER PLATING SHALL NOT APPLY.
WEIGHT (MINIMUM): -1: 110 GRAINS
-2: 40 GRAINS

(C) 5. DASH NOS. 1 AND 2 ARE AUTHORIZED TO BE MANUFACTURED OF ANODIZED ALUMINUM FOR COMMERCIAL SALE ONLY. THE BADGE SHALL BE ANODIZED AND FINISHED TO MATCH THE STANDARD SAMPLES.

CUSTODIAN:
ARMY - IH
REVIEW ACTIVITY:
OTHER - DP
USER ACTIVITY:
ARMY - SM

PREPARING ACTIVITY:

THE INSTITUTE OF HERALDRY,
UNITED STATES ARMY

Project No. 8455-0131

FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:07Z
Check the source to verify that this is the current version before use.