MILITARY SPECIFICATION SHEET

Badge, Qualification, PARARESCUE, Air Force

This specification is mandatory for use by all Departments and Agencies of the Department of Defense. The complete requirements for procuring the item(s) described herein shall consist of this document and the issue in effect of Specification MIL-B-3628.

MATERIAL: 1/20 SILVER FILLED (FRONT ONLY) OVER A COMMERCIAL COPPER BASE ALLOY

DIMENSIONS (INCHES):
HEIGHT (OVERALL): 1-1/2 (REF)
WIDTH (OVERALL): 1-17/32 (REF)
THICKNESS (AT THICKEST POINT): .105 ± .010

FINISH: SILVER PLATED, OXIDIZED, RELIEVED SATIN FINISH WITH REVERSE AND EDGES CLEAN

NOTES:
1. THE BADGE MAY BE MADE FROM STERLING SILVER FOR COMMERCIAL SALE AND IF SO THE THICKNESS DIMENSION GIVEN SHALL BE USED FOR REFERENCE ONLY. THE MINIMUM WEIGHT SHALL BE NOT LESS THAN 300 GRAINS. THE FINISH FOR STERLING SILVER BADGES SHALL BE AS SPECIFIED EXCEPT THE REQUIREMENTS FOR SILVER PLATING SHALL NOT APPLY.

2. ATTACHING DEVICE SHALL BE PRONG AND CLUTCH TYPE. THE PRONGS, FABRICATED FROM NICKEL SILVER SHALL BE 5/16 ± 1/64 INCH IN LENGTH AND SHALL BE LOCATED ON THE HORIZONTAL CENTERLINE EQUIDISTANT FROM EACH END AND 1-1/8 ± 1/64 INCH ON CENTERS.

3. THE BADGE SHALL BE DAPPED 1/16 INCH IN THE HORIZONTAL DIRECTION.

CUSTODIAN:
AIR FORCE - 11
REVIEW ACTIVITY:
AIR FORCE - 11,82,85
OTHER - DP

PREPARING ACTIVITY:
THE INSTITUTE OF HERALDRY, UNITED STATES ARMY

Project No. 8455-0131

FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:08Z
Check the source to verify that this is the current version before use.