NOT MEASUREMENT SENSITIVE

MIL-B-3628/50D
30 July 1993
SUPERSEDING
MIL-B-3628/50C
10 February 1988

MILITARY SPECIFICATION SHEET

BADGE, QUALIFICATION, PARARESCUE, AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3628.



MATERIAL: Red Brass or Nickel Silver

FINISH: Nickel Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.

DIMENSIONS:

HEIGHT (Overall): 1-1/2 inches (3.81 cm) (REF)
WIDTH (Overall): 1-17/32 inches (3.89) (REF)
THICKNESS (At Thickest Point): 0.105 inch ± 0.010 inch (0.268 cm ± 0.025 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-10-16T19:08Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The attaching device shall be prong and clutch type. The prongs shall be located at the horizontal center line of the badge equidistant from each end and 1-1/8 inches ± 1/64 inch (2.86 cm ± 0.04 cm) apart.

3. The badge shall be dapped 1/16 inch (0.16 cm) in the horizontal direction.

Custodian:
Army - IH
Air Force - 11

Review activities:
Air Force - 82, 99
DLA - CT

User activities:
Air Force - 45

Preparing activities:
Army - IH

(Project No. 8455-0693)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:08Z
Check the source to verify that this is the current version before use.