INCH-POUND

MIL-DTL-3628/50F
28 April 2014
SUPERSEDING
MIL-DTL-3628/50E
15 November 1996

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, PARARESCUE, U.S. AIR FORCE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.



MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230) or Nickel Silver 65/35 (UNS Alloy No C-752)

FINISH: Nickel Plated, Mirror –like Polished and shall match The Institute of Heraldry Metal Finish Chip Number 16.

DIMENSIONS:
HEIGHT: 1-1/2 inches (REF)
WIDTH: 1-17/32 inches (REF)
THICKNESS: (At thickest point): 0.105 inch $\pm$ 0.010 inch

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:08Z
Check the source to verify that this is the current version before use.

ATTACHING DEVICE:

1: Attaching device shall be prongs and clutches type.

2: The prongs shall be located on the horizontal center line of the badge equidistant from each end and 1-1/8 inches ± 1/64 inch apart.

3: The badge shall be dapped 1/16 inch in the horizontal direction.

NOTE:

The term (REF) refers to the measurements taken from the Government furnished hub or die.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2014-099)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:08Z
Check the source to verify that this is the current version before use.