NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/50H
1 July 2020
SUPERSEDING
MIL-DTL-3628/50G
26 August 2015

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, PARARESCUE, U.S. AIR FORCE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.



MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230) or Nickel Silver 65/35 (UNS Alloy No C-752)

FINISH: Nickel Plated, Mirror –like Polished and shall match The Institute of Heraldry Metal Finish Chip Number 16.

DIMENSIONS:
HEIGHT: 1-1/2 inches (REF)
WIDTH: 1-17/32 inches (REF)
THICKNESS: (At thickest point): 0.105 inch $\pm$ 0.010 inch

ATTACHING DEVICE:
1: Attaching device shall be prongs and clutches type.

2: The prongs shall be located on the horizontal center line of the badge equidistant from each end and 1-1/8 inches $\pm$ 1/64 inch apart.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:07Z
Check the source to verify that this is the current version before use.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Shall be spherically dapped to radius of 6 inches + 1/16 inch – 0 when measured on the reverse.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2020-356)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:07Z
Check the source to verify that this is the current version before use.