NOT MEASUREMENT SENSITIVE


MIL-B-3628/51D
9 July 1990
SUPERSEDING
MIL-B-3628/51C
10 February 1988

MILITARY SPECIFICATION SHEET

BADGE, QUALIFICATION, PATHFINDER, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3628.



MATERIAL:
-1, -3: Gilding metal
-2: Red brass or gilding metal

-1: Regular Size
-2: Regular size, subdued
-3: Dress miniature

DIMENSIONS:
HEIGHT (Overall):
-1, -2: 1-3/16 inch (3.02 cm) (REF)
-3: 11/16 inch (1.75 cm) (REF)
WIDTH (Overall):
-1, -2: 1-1/2 inch (3.81 cm) (REF)
-3: 7/8 inch (2.22 cm) (REF)
THICKNESS (At thickest point of torch):
-1, -2: .100 inch ± .010 inch (0.254 cm ± 0.025 cm)
-3: .075 inch ± .010 inch (0.190 cm ± 0.025 cm)

FINISH:
-1, -3: Hard enameled, gold plated, mirror-like polished finish
-2: Dull, flat black enamel finish

NOTES:
1. Piercing shall be as indicated.
2. Enameled areas shall be as indicated. The color shall conform to the TIOH chip numbers listed below or the standard sample.

COLOR	CHIP NUMBER
Gray	27
Red	1

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:08Z
Check the source to verify that this is the current version before use.

3. Vitreous enamel shall be smooth and flush with the dikes however, the enamel need not be stoned.
4. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of manufacturer. Epoxy resin shall be smooth and flush with the dikes however, the epoxy need not be stoned. Epoxy resin shall be a stoning epoxy, have a shore D hardness of 85, and incorporate an ultraviolet inhibitor.
5. The enamel for dash no. 2 shall match chip no. 37038 of FED-STD 595.
6. Attaching device shall be two prongs and clutches. The prongs shall be located on the vertical centerline of the torch and equidistant from each end. For dash no. 1 and 2, the prongs shall be 1 inch ± 1/32 inch (2.54 cm ± 0.08 cm) apart and for dash no. 3, the prongs shall be 9/16 inch ± 1/32 inch (1.43 cm ± 0.08 cm) apart.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-A530)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:08Z
Check the source to verify that this is the current version before use.