A-A-50066
October 31, 1983

COMMERCIAL ITEM DESCRIPTION

ICE CREAM CABINETS, MECHANICALLY REFRIGERATED

The General Services Administration has authorized the use of this Commercial Item Description in preference to Military Specification MIL-I-20565 for specific sizes of items listed in this document.

Intended use. The ice cream cabinets are for stocking bulk or packaged ice cream in food dispensing facilities.

Salient characteristics.

Cabinets

An ice cream cabinet shall consist of a mechanically refrigerated, insulated compartment capable of holding ice cream in standard 2-1/2, 3, and 5 gallon bulk containers of 9-7/8 inch maximum diameters. The outer shell of the cabinet shall be of stainless steel or baked enamel coated sheet steel. The interior surfaces shall be stainless steel, baked enamel or galvanized steel sheet. The top shall be one piece construction of stainless steel sheet and shall extend over the cabinet sides. Top access lids shall be provided. The lids shall be of the flip-flap design (totally removable lid, hinged in the center to permit opening either half). Lifting handles shall be installed on the lids, and bumpers shall be provided to prevent marring of the top surface when the lids are open. Lid openings shall be of sufficient size and number to permit insertion of the total capacity of 2-1/2, 3, or 5 gallon standard ice cream containers. The lids and the spaces between the inner liner and outer shell shall be completely filled with insulation. The insulation shall be industrial-type fiberglass insulation board, expanded polystyrene, or fluorocarbon expanded polyurethane preformed to shape or foamed-in-place.

Sizes. The ice cream cabinets shall be in the following sizes:

15 gallons capacity; 120 volts, 60 hertz, single phase
25 gallons capacity; 120 volts, 60 hertz, single phase
35 gallons capacity; 120 volts, 60 hertz, single phase
45 gallons capacity; 120 volts, 60 hertz, single phase

FSC 4110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

Dimensions. The ice cream cabinets shall not exceed the maximum dimensions specified in table I.

TABLE I.

Size (gal)	Length (inches)	Width (inches)	Height (inches)
15	44	32	34-1/2
25	54	32	34-1/2
35	65	32	34-1/2
45	78	32	34-1/2

Refrigeration system.

The refrigeration system and component parts shall be completely installed and connected to make a fully autonatic, self-contained, mechanically cooled ice cream cabinet. The refrigeration system shall consist of an electric motor driven air-cooled condensing unit, evaporator, and necessary accessories including controls, motor starters, and protectors, all constructed and mounted to prevent vibration.

Condensing units shall be designed for 120 volts, 60 hertz, single phase. The use of transformers to obtain the motor voltage or frequency is prohibited. Where transformers are required as part of the control system they shall be furnished and installed as part of the cabinet. The ice cream cabinet shall be equipped with an adjustable thermostat to maintain storage compartment temperatures between -10°F and 15°F in any ambient between 50°F and 100°F. The assembled refrigeration system shall be completely dehydrated and fully charged with refrigerant and oil.

Standards of compliance.

The ice cream cabinets shall comply with Underwriters Laboratories, Inc. Standard No. 471 and National Sanitation Foundation Standard No. 1.

Marking. The units shall be legibly marked with the manufacturer's name or trademark and model or part number plus the contract number and National Stock Number.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same as the product sold in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for in the contract.

Source: https://assist.dla.mil -- Downloaded: 20261O-26T08:38Z
Check the source to verify that this is the current version before use.

Packaging.

Commercial packaging. Each ice cream cabinet shall be packaged in accordance with commercial practice.

Commercial packing. Each ice cream cabinet shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall comply with the Uniform Freight Classification, as applicable.

Export packaging. Each ice cream cabinet shall be cleaned, preserved and cushioned to afford protection against corrosion, deterioration and physical damage during shipment and storage. The owner's manual shall be placed within the cabinet. The lid shall be secured to the cabinet in a closed position with strapping or filament reinforced pressure-sensitive tape. Cushioning or other appropriate material shall be placed between the cabinet surfaces and securement to protect the finish.

Export packing. Each ice cream cabinet shall be packed in a snug-fitting wood-cleated plywood box conforming to domestic type, style A or J, grade B, type 2 load of PPP-B-601 or nailed wood box conforming to class 1, style 2 or 4, grade B of PPP-B-621. The contents of the box shall be cushioned, blocked and braced to prevent movement while the box is in transit. Each shipping container shall be closed and strapped in accordance with the appendix of PPP-B-601 or PPP-B-621, as applicable.

Marking of shipping containers (commercial and export). Commercial marking for shipping containers is acceptable provided the following information is included:

National stock number
Item description
Quantity, unit of issue
Date of packaging (month/year)
Contract number
Name, address and zip code of contractor

Sources of information for nongovernment association documents.

National Sanitation Foundation
P.O. Box 1468
Ann Arbor, MI 48106

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

A-A-50066

Underwriters Laboratories, Inc.
333 Pfingsten Road
Northbrook, IL 60062

National Motor Freight Traffic Association, Inc., Agent
National Motor Freight Classification
American Trucking Associations, Inc., Traffic Department
1616 P. Street, N.W.
Washington, DC 20036

Uniform Classification Committee, Agent
Uniform Freight Classification
Uniform Classification Committee, Suite 1106
222 South Riverside Plaza
Chicago, IL 60606

MILITARY INTERESTS:

Custodians

Army - GL
Navy - YD
Air Force - 99

Review Activities

Army - MD
Navy - MC
DSA - GS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project No. 4110-0371

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.