A-A-50073
January 30, 1985

COMMERCIAL ITEM DESCRIPTION

CONVEYOR, BELT: POWERED, MEAT PROCESSING

The General Services Administration has authorized the use of this Commercial Item Description in preference to Military Specification MIL-C-43631(GL).

1. Classification. The conveyor shall be of the following types as specified (see 5.1).

Type I - Ground meat, molded blocks - Conveying Of
Type II - Meat processing, preground - Conveying Of

2. Salient characteristics

2.1 Type I.

2.1.1 Design. The belt conveyor shall be designed to transfer 3600 molded meat blocks per hour, weighing 1-1/2 pounds, from the molding machine to the wrapping table. The belt conveyor shall consist of a support structure, conveyor, roller unit belt, motor, cable and plug assembly.

2.1.2 Support structure. The support structure shall be fabricated from galvanized steel. The structure shall support the conveyor and be equipped with four adjustable legs. Two legs shall be located at the drive end, adjustable from 33 to 41 inches high, and two legs shall be located at the idler end, adjustable from 13-1/2 to 15-1/2 inches high.

2.1.3 Conveyor. The conveyor belt speed shall be 55 to 65 feet per minute. The conveyor assembly shall be provided with an electric motor driven pulley unit mounted on the drive (high) end and an idler, mounted at the idler (low) end. An adjustable tension pulley shall be provided. The overall length of the assembled conveyor in operation position, including roller unit and conveyor section, shall be 71 inches minimum to 76 inches maximum.

2.1.4 Roller unit. A roller unit shall be provided on the drive end of the conveyor. The roller unit shall have ten rollers equipped with ball bearings on each end of the roller. The roller unit shall be a minimum of 8 inches wide by 9-3/4 inches long.

2.1.5 Belt. The belt shall be a minimum of 6 inches wide, USDA approved construction, white and cleated.

FSC 7320

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:38Z
Check the source to verify that this is the current version before use.

2.1.6 Motor. Unless otherwise specified (see 5.1), the motor shall operate on a 120 volt, 60 Hertz, 1 phase power source and have a minimum rating of 1/30 HP equipped with an "ON-OFF" control switch accessible to the operator.

2.1.7 Cable and plug assembly. The conveyor shall be equipped with a 6-foot minimum, 3 wire power supply cord with grounding type plug.

2.2 Type II.

2.2.1 Design. The belt conveyor shall consist of a support structure, conveyor with side panels, roller units, removable belt, motor and cable, switch and hopper assembly. The belt conveyor shall be designed to transfer 300 pounds per minute of pre-ground meat product to large volume mixer/grinders.

2.2.2 Support structure. The support shall be galvanized steel equipped with two telescoping legs on the discharge end, with size position height adjustment, and two legs on the hopper end. The discharge chute shall be capable of being adjusted from 51 to 68 inches. The four legs shall be equipped with 5-inch diameter casters having a 2-inch height adjustment.

2.2.3 Conveyor. Conveyor speed shall be 45 to 55 feet per minute. The distance between conveyor roller centers shall be 13 feet. Removable 9-inch high stainless steel side panels shall be provided. A large stainless steel hopper on the loading end (lower) shall be provided. The hopper shall be not less than 27-1/2 inches high from the floor. The conveyor shall be equipped with a stainless steel lower pulley cover and a stainless steel panel under the conveyor belt.

2.2.4 Belt. The conveyor belt shall be a minimum of 18 inches wide, white, USDA approved construction, cleated, capable of being removed without tools, loosened and aligned by lever.

2.2.5 Motor. The conveyor motor shall be 1-HP, totally enclosed, fan cooled and unless otherwise specified (see 5.1), operate on nominal 208 Volt, 3-phase, 60 Hz power source. The motor starter shall be of the manual type mounted in a water tight enclosure accessible to the operator.

2.2.6 Cord and plug. The conveyor shall be equipped with 9-1/2 foot, 4 wire heavy duty flexible power supply cord with a twist lock grounding type plug conforming to configuration L 15-20 for use with a water tight connector or receptacle.

2.3 Standards compliance. The types I and II belt conveyors shall conform to Underwriters Laboratories (UL) No. 73.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

2.4 Identification plate. In addition to the marking and identification required by UL No. 73, the identification plate for the types I and II belt conveyors shall include the contract number and national stock number.

2.5 Workmanship. All workmanship shall conform to good commercial practice.

3. Quality assurance. The contractor is responsible for assuring that the items furnished to the Government conform to all requirements specified in referenced documents and herein. The contractor shall furnish a certificate of compliance certifying that the items being furnished comply with the stated requirements. The Government reserves the right to inspect the items to verify the certification and may reject any item or lot of items when it is determined that:

a. Any required component or design characteristic is missing or not as specified herein.

b. Any aspects of design, construction, assembly, function or finish is not in accordance with good commercial practice.

c. Packaging, packing, palletization and marking is not as specified.

4. PACKAGING.

4.1 Packaging and packing. Packaging and packing shall be commercial or export as specified (see 5.1).

4.2 Commercial.

4.2.1 Commercial packaging. Each conveyor shall be packaged in accordance with commercial practice.

4.2.2 Commercial packing. Each conveyor shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Container shall comply with the National Motor Freight Classification or Uniform Freight Classification, as applicable.

4.3 Export.

4.2.2 Export packing. Each conveyor shall be disassembled to the extent determined by the supplier to protect parts susceptible to damage during shipment and storage and for reduction of cubage. Parts removed shall be packaged in a weather-resistant fiberboard box constructed and closed in accordance with Method IV as specified in PPP-B-636. The conveyor and parts shall be cleaned, preserved, and cushioned to afford protection against corrosion, deterioration and physical damage during shipment and storage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

4.3.2 Export packing. Each conveyor with its packaged parts shall b packed in a snug-fitting wood-cleated plywood box conforming to class 2, style 2 or 4, grade B, type 2 load of PPP-B-621. The contents of the box shall b cushioned, blocked, braced, and waterproofed in accordance with the applicable requirements of MIL-STD-1186. Each shipping container shall be closed and strapped in accordance with the appendix of PPP-B-601 or PPP-B-621.

4.4 Marking of Interior Boxes and Shipping Containers (commercial and export). Commercial marking for interior boxes and shipping containers is acceptable provided the following information is included:

National Stock Number
Item description
Date of Packaging (Month/Year)
Contract Number
Name, Address and Zip Code of Contractor 1/
Quantity, Unit of Issue
Gross Weight and Cube 1/

1/ Interior boxes do not require this information.

5. NOTES

5.1 Ordering data:

a. Title, number, and date of this document
b. Type belt required (see 1.).
c. Selection of applicable packaging required (See 4.1).
d. Electrical characteristics, if other than specified (see 2.1.6 and 2.2.5).

5.2 Sources of information for nongovernment association documents.

National Electrical Manufacturers Association
155 East 44th Street, New York, NY 10017

National Motor Freight Traffic Association, Inc., Agent
National Motor Freight Classification
American Trucking Associations, Inc., Traffic Department
1616 P Street, N.W., Washington, DC 20036

Uniform Classification Committee, Agent
Uniform Freight Classification
Uniform Classification Committee, Suite 1106
22 South Riverside Plaza, Chicago, IL 60606

Underwriters Laboratories, Inc.
333 Pfingsten Road
Northbrook, IL 60062

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodian

Army - GL

Review Activities

Army - MD
DLA - GS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

Preparing Activity:

Army - GL

Project No. 7320-0753

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:38Z
Check the source to verify that this is the current version before use.