A-A-50073A
May 17, 1989
SUPERSEDING
A-A-50073
January 30, 1985

COMMERCIAL ITEM DESCRIPTION

CONVEYOR, BELT: POWERED, MEAT PROCESSING

The General Services Administration has authorized the use of this commercial item description in preference to MIL-C-43631(GL).

1. CLASSIFICATION

1.1 Classification. This commercial item description covers a conveyor of the following types as specified (see 5.2).

Type I - Ground meat, molded blocks - Conveying Of
Type II - Meat processing - Conveying Of

1.2 Part identification number. The part identification number shall consist of the commercial item description number and the type number as follows:

AA50073 - I

Type
CID number

2. SALIENT CHARACTERISTICS

2.1 Type I.

2.1.1 Design. The belt conveyor shall be designed to transfer 3600 molded meat blocks per hour, weighing 1-1/2 pounds, from the molding machine to the wrapping table. The belt conveyor shall consist of a support structure, conveyor, roller unit belt, motor, cable and plug assembly.

AMSC N/A FSC 7320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

2.1.2 Support structure. The support structure shall be fabricated from galvanized steel or stainless steel. The structure shall support the conveyor and be furnished with four legs. The four legs shall be equipped with 3 inch diameter locking casters. Two legs shall be located at the drive end, adjustable from 33 to 41 inches high, and two legs shall be located at the idler end, adjustable from 13-1/2 to 15-1/2 inches high. Additional cross support bracing fabricated from galvanized steel shall be provided at the drive end to prevent twisting when moved.

2.1.3 Conveyor. The conveyor belt speed shall be 55 to 65 feet per minute. The conveyor assembly shall be provided with an electric motor driven pulley unit mounted on the drive (high) end and an idler, mounted at the idler (low) end. An adjustable tension pulley shall be provided. The overall length of the assembled conveyor in operation position, including roller unit and conveyor section, shall be 71 inches minimum to 76 inches maximum.

2.1.4 Roller unit. A roller unit shall be provided on the drive end of the conveyor. The roller unit shall have ten rollers equipped with ball bearings on each end of the roller. The roller unit shall be a minimum of 8 inches wide by 9-3/4 inches long.

2.1.5 Belt. The belt shall be a minimum of 6 inches wide, USDA approved construction, white and cleated.

2.1.6 Motor. Unless otherwise specified (see 5.2), the motor shall operate on a 120 volt, 60 Hertz, 1 phase power source and have a minimum rating of 1/30 horsepower equipped with an "ON-OFF" control switch accessible to the operator.

2.1.7 Cable and plug assembly. The conveyor shall be equipped with a 6 foot minimum length, 3 wire power supply cord with grounding type plug.

2.2 Type II.

2.2.1 Design. The belt conveyor shall consist of a support structure, conveyor with side panels, roller units, removable belt, motor and cable, switch and hopper assembly. The belt conveyor shall be designed to transfer 300 pounds per minute of meat product to large volume mixer/grinders.

2.2.2 Support structure. The support structure shall be galvanized steel or stainless steel equipped with two telescoping legs on the discharge end, with size position height adjustment, and two legs on the hopper end. The discharge chute shall be capable of being adjusted from 51 to 80 inches. The four legs shall be equipped with 5-inch diameter casters (two swivel and two rigid), each having a 2 inch height adjustment.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:38Z
Check the source to verify that this is the currentversion before use.

2.2.3 Conveyor. The conveyor speed shall be a minimum of 50 feet per minute. The distance between conveyor roller centers shall be 10 feet. Removable 5 inch minimum high stainless steel side panels shall be provided. A large stainless steel hopper on the loading end (lower) shall be provided. The hopper shall not be less than 27-1/2 inches high from the floor. The conveyor shall be equipped with a stainless steel lower pulley cover and a stainless steel panel under the conveyor belt.

2.2.4 Belt. The conveyor belt shall be a minimum of 13 inches wide, white, USDA approved construction, cleated, capable of being removed without tools, loosened and aligned by lever.

2.2.5 Motor. Unless otherwise specified (see 5.2), the conveyor motor shall be a minimum ½ horsepower, totally enclosed, fan cooled, and shall operate on a nominal 208 volt, 60 Hertz, 3 phase power source. The motor starter shall be of the manual type mounted in a watertight enclosure accessible to the operator.

2.2.6 Cord and plug. The conveyor shall be equipped with a 6 foot minimum length heavy duty flexible power supply cord with a twist lock grounding type plug conforming to configuration L 15-20 for use with a water tight connector or receptacle.

2.3 Codes and standards. The types I and II belt conveyors shall conform to Underwriters Laboratories (UL) No. 763.

2.4 Data name plate (Government unique requirement see 5.4). The conveyor shall be furnished with a data name plate in accordance with the applicable requirements of MIL-STD-130 except the requirements for: (a) Methods of applying; (b) Identification tags; (c) Information not required and (d) Optional marking information shall not apply. The data plate shall be made of minimum 20 gauge corrosion-resisting metal and attached to the conveyor by rivets, screws, or welding in such a manner as to meet the applicable National Sanitation Foundation sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved or applied by photosensitive means:

National Stock Number
Procurement Contract Number
Specification Data
Manufacturer's Name, Address and Telephone Number
Supplier's Name, Address and Telephone Number (List only if different from Manufacturer)
Manufacturer's Model Number
Government Approved Manual Number (when specified, see 5.2)

Each plate shall be placed so that it is readily visible to the operator during normal operating use and so as to not adversely affect the life and utility of the conveyor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify that the product offered meets the salient characteristics and requirements of the description and except for those government unique requirements specified, conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same as the product offered for sale in the commercial marketplace. The contractor shall certify the product meets the "Government unique" requirements except when specific quality assurance provisions are specified for the Government unique requirements. In this case, the contractor shall provide data resulting from inspection conducted in accordance with the specified quality assurance. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4. PACKAGING

4.1 Packaging and packing. Packaging and packing shall be commercial or export as specified (see 5.2).

4.2 Commercial packaging and packing. Each conveyor shall be cleaned, preserved, packaged, packed and unitized in accordance with ASTM D 3951.

4.3 Export packaging and packing.

4.3.1 Export packaging. Each conveyor shall be disassembled to the extent determined by the supplier to protect parts susceptible to damage during shipment and storage and for reduction of cubage. Parts removed shall be packaged in a weather-resistant fiberboard box constructed and closed in accordance with Method IV as specified in PPP-B-636. The conveyor and parts shall be cleaned, preserved, and cushioned to afford protection against corrosion, deterioration and physical damage during shipment and storage.

4.3.2 Export packing. Each conveyor with its packaged parts shall be packed in a snug-fitting wood cleated-plywood box or nailed wood box conforming to overseas type, type 2 load of PPP-B-601; or class 2, style 2 or 4, type 2 load of PPP-B-621, respectively. The contents of each box shall be cushioned, blocked, braced, and waterproofed in accordance with the applicable requirements of MIL-STD-1186. Each shipping container shall be closed and strapped in accordance with PPP-B-601 or PPP-B-621, as applicable.

4.4 Marking (commercial and export). Marking of unit pack, shipping container and unit load shall be in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

5. NOTES

5.1 Intended use. The type I conveyor covered by this commercial item description is intended for use in meat preparation departments of food handling establishments to transfer molded meat-loaf blocks from the meat molding attachment to a wrapping machine level. The type II conveyor is intended to transport unground meat to the top of the hopper of meat mixer/grinder machine.

5.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Type of conveyor required (see 1.1).
c. Electrical characteristics, if other than specified (see 2.1.6 and 2.2.5).
d. Government approved manual number to be included on the data name plate when manuals are purchased under the contract (see 2.4).
e. Type of packaging and packing (see 4.1).

5.3 Sources of documents.

5.3.1 Sources of nongovernment association documents.

ASTM D 3951 - Standard Practice for Commercial Packaging, is available from:

The American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103

UL Standard No. 763 - Motor-Operated Commercial Food Preparing Machines, is available from:

Underwriters Laboratories, Inc. (UL)
333 Pfingsten Road
Northbrook, IL 60062

5.3.2 Source of governmental documents. Copies of Military and Federal documents are available from:

Naval Publications and Forms Center
5801 Tabor Avenue
Philadelphia, PA 19120

5.4 Government unique requirements. Whenever "(Government unique requirements)" is included in the title of a paragraph under "salient characteristics" it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:38Z
Check the source to verify that this is the current version before use.

A-A-50073A

MILITARY INTERESTS:

Custodian

Army - GL

Review activities

Army - MD, TS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

PREPARING ACTIVITY:

Army - GL

Project No. 7320-0849

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.