A-A-50075
October 7, 1985

COMMERCIAL ITEM DESCRIPTION

IRONERS, FLATWORK, THERMAL FLUID

The General Services Administration has authorized the use of the Commercial Item Description.

1. Intended use. This commercial item description covers a thermal fluid, flatwork, ironer (see 5.1).

2. Salient characteristics.

2.1 Design and construction. The ironer shall consist of framing, removable side panels, chest, rolls, drive and a pressure system and a safety guard. The length of the ironer shall depend on the number of rolls and the width shall not be greater than 13 feet. The ironer shall have a smooth profile. The drive and pressure system shall be located inside the machine or by the machine in an out of the way location. The main frame and removable side panels shall be enameled.

2.1.1 Frames. The frames shall be steel and shall provide a sturdy and lightweight machine.

2.1.2 Panels. The panels shall be easily removable and shall have safety catches to present accidental removal.

2.1.3 Chest. Each chest shall be designed exclusively for thermal fluid as a heating medium. Chests shall be fabricated so that the chests shall end no less than 4 inches above the center line of the rolls. The oil pressure drop during operation shall be such that the resulting temperature drop in the chest shall not exceed 20°F. Chests shall be capable of accommodating a working oil pressure which insures the required temperature of 450°F.

2.1.4 Rolls.

2.1.4.1 Roll spring. The rolls shall be spring type to permit the effective use of a vacuum exhaust. The vacuum system shall provide for the rolls to extract moisture from the padding and provide a steam free atmosphere around the ironer. The combination of the vacuum system and drilled individually fitted springs shall result in minimum radiated heat. A canopy is not required.

FSC 3510

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

2.1.4.2 Roll padded resilent spring. The resilent padded roll is to be covered with padding and underpadding at the time of installation. The ironer shall be equipped with an interrupting device that reduces chest and roll contact by 30 percent when the machine is interrupted for any reason while it is in operation. When flatwork is resumed, the contact pressure shall automatically return to full.

2.1.5 Safety guard. The ironer shall have a safety guard installed across the entire length of the feed-end. The guard shall deactivate the drive mechanism when it is pushed and at the same time reduce the roll/chest pressure immediately before an operator's hand could reach the chest. Emergency stop buttons shall be installed at both the feed and discharge ends of the ironer.

2.2 Ironer operation. The ironer shall finish and dry not less than 1300 pounds per hour of 100 percent cotton flatwork at 50 percent moisture content. The ironer shall finish and dry not less than 2100 pounds per hour of blended fabric at 35 percent moisture content. The oil inlet temperature shall range from 430° to 450°F.

2.3 Workmanship. The completely fabricated item shall be free from defects such as fractures, splits, punctures, tears, dents, creases, miscasts, deteriorations or malformations. There shall be no sharp edges, burrs or slivers.

3. Quality assurance. The contractor is responsible for assuring that the items furnished to the Government conform to all requirements specified in referenced documents and herein. The contractor shall furnish a certificate of compliance certifying that the items being furnished comply with the stated requirements. The Government reserves the right to inspect the items to verify the certification and may reject any item or lot of items when it is determined that:

a. Any required component or design characteristic is missing or not as specified herein.

b. Any aspects of design, construction, assembly, function or finish is not in accordance with good commercial practice.

c. Packaging, packing and marking is not as specified.

4. PACKAGING

4.1 Packaging. Ironers shall be cleaned and preserved in accordance with method III of MIL-P-116.

4.2 Packing. Ironers, packaged as specified, and any additional rollers shall be packed in wood crates conforming to type I, style A of MIL-C-3774.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

4.3 Marking. In addition to any special markings required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129. Special handling marking requirements applicable to fragile items, arrows and words "UP", "THIS SIDE UP" and "CENTER OF BALANCE" shall apply. When additional rollers are crated separately, set markings shall be required.

5. NOTES

5.1 Intended use. The ironers are intended to be used in fixed laundry installations.

5.2 Ordering data. Title, number and date of this document.

MILITARY INTERESTS:

Custodian

Army - GL

Review Activities

Army - MD
DLA - GS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project No. 3510-0294

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.