A-A-50088A
April 26, 1988
SUPERSEDING
A-A-50088
December 22, 1986

COMMERCIAL ITEM DESCRIPTION

MEAT SLICING MACHINES, ELECTRIC

The General Services Administration has authorized the use of this commercial item description.

1. CLASSIFICATION

1.1 Classification. The meat slicing machines shall be furnished in the classification specified in ASTM F 919-85 and as changed in 2.1 below.

2. SALIENT CHARACTERISTICS

2.1 Salient characteristics. The food slicing machines shall be in accordance with ASTM F 919-85 except as follows:

a. Paragraph 2.1: Delete in entirety.

b. Paragraph 2.3, UL Standards: Delete "UL 73" and its title, and substitute: "UL 763, Motor Operated Commercial Food Preparing Machines".
Delete: "UL 969, Marking and Labeling Systems".

c. After paragraph 4.2.1.1(b): Add the following:

"(c) Rate 3 - Variable carriage speed"

d. Paragraph 6.1: Delete last sentence and substitute: "All meat slicers shall meet the requirements of *UL Standard No. 763.*"

e. Delete paragraph 6.1.1 and substitute the following:

"6.1.1 National Sanitation Foundation (NSF). Acceptable evidence of meeting the applicable requirement of NSF Standard No. 8 shall be one of the following:

(1) A listing in the current edition of the National Sanitation Foundation "Listing of Food Service Equipment" and display of the NSF seal on the finished slicer.

(2) A certification for the slicer issued by NSF under their special one-time contract evaluation/certification service.

FSC 7320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:38Z
Check the source to verify that this is the currentversion before use.

(3) A certified test report acceptable to the contracting officer with the advice of the Army Surgeon General, from an independent testing laboratory, indicating that the slicer has been tested and conforms to the specified NSF standards."

f. 6.1.2, lines 1 and 2: Delete "UL 73" and substitute "UL 763".

g. 7.1, line 2 and 7.3, line 3: Delete "UL Standard 73" and substitute "UL Standard 763".

h. Paragraph 8.3: After "Carriage Operation:", Add the following:

"The slicer shall be designed to prevent contact between the slicing knife and the carriage, the slice thickness guide plate, and the spike assembly of the end slice plate:"

i. Delete paragraph 13.1 and substitute the following:

"13.1 Data name plate (Government unique requirement see paragraph 5.3 of this description). The meat slicing machine shall be furnished with a data name plate in accordance with the applicable requirements of MIL-STD-130 except the requirements for; (a) Methods of applying, (b) Identification tags, (c) Information not required and (d) Optional marking information shall not apply. The data name plate shall be made of minimum 20 gauge corrosion-resisting metal and attached to the unit by rivets, screws, or by welding in such a manner as to meet the applicable NSF requirements for this equipment. The plate shall bear the following information which shall be stamped, engraved or applied by photosensitive means:

National Stock Number
Procurement Instrument Identification Number
Specification Data
Manufacturer's Name, Address and Telephone Number
Supplier's Name, Address and Telephone Number (List only if different from Manufacturer)
Manufacturer's Model Number
Government Approved Manual Number (See paragraph 5.1 of this description)
Contract Number and Manufacturer's Serial Number

Each plate shall be placed so that it is readily visible to the operator during normal operating use so as to not adversely affect the life and utility of the meat slicing machine."

j. Delete paragraph 14.1

k. Table I: Change as follows:
In "Minimum Slicing Knife Diameter (inches)" column, opposite Type I, Styles 1 and 2, Rate 1, and Type II, Style 2: Delete "11-3/4" and substitute "11-7/16".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

Add new entry to table as follows:

Type	Style	Rate	"Minimum Product Cross Section (inches)	Minimum Slices Per Minute	Minimum Range Slice Thickness (inches)	Minimum Slicing Knife Diameter (inches)	Minimum Knife Drive Motor HP
"I	1	3	10-3/4 x 3 and 7 diameter	0-55	1/48 to 5/8	11	1/3 "

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify that the product offered meets the salient characteristics and requirements of the description and conforms to the producer's own specifications and standards, and quality assurance practices, and is the same product offered for sale in the commercial marketplace. When specific quality assurance provisions are specified for any commercial characteristic the contractor shall furnish data resulting from inspection conducted in accordance with the specific quality assurance provisions. The Government reserves the right to require proof of such conformance prior to the first delivery from point of origin and any time thereafter as may be otherwise provided for under the provisions of the contract.

3.2 End item testing. One meat slicing machine shall be tested for each production lot and shall meet the quality assurance provisions of ASTM F 919-85, sections 9 through 12, except as follows:

Add the following paragraphs to section 9:

"9.6 On/Off Switch Test:

9.6.1 Significance - The purpose of this test is to insure the reliability of the on/off switch.

9.6.2 Procedure - The on/off switch (main power) shall be operated from start to complete stop for 180 cycles without failure.

9.7 Carriage Reliability Test:

9.7.1 Significance - The purpose of this test is to insure the reliability of the carriage operation and the engagement mechanism of the powered carriage feature.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

9.7.2 Procedure - The slicer shall be operated in the powered carriage mode over a single 36 hour period. A 5 pound load shall be placed in the carriage for the test. During the test period, the powered carriage feature shall be disengaged temporarily and operated manually for 2 complete cycles per hour during each of the 36 hours. This procedure shall be conducted in accordance with the manufacturer's operating instructions."

4. PACKAGING

4.1 Packaging. In lieu of the packaging, packing and marking specified in paragraph 15 of ASTM F 919-85 the meat slicing machines shall be packaged, packed and marked as specified below:

4.2 Packaging and packing. Packaging and packing shall be commercial or export as specified (see 5.1).

4.3 Commercial packaging and packing. Each slicer shall be cleaned, preserved, packaged, packed and unitized in accordance with ASTM D 3951.

4.4 Export packaging and packing.

4.4.1 Export packaging. Each slicer shall be cleaned, preserved and cushioned to protect against corrosion, deterioration and physical damage during shipping and storage. Disassembled parts and accessories, and owner's manual shall be packaged in a fiberboard box conforming to type CF or SF, class domestic, style optional of PPP-B-636.

4.4.2 Export packing. Each meat slicing machine with its parts package, or main components with parts for large slicers, shall be packed in a nailed and lock-corner wood box conforming to class II, style 2, 4 or 7, type I load of PPP-B-621 or a cleated-plywood box conforming to overseas type, style optional of PPP-B-601. Each box shall be waterproofed with a sealed case liner conforming to type I, II or IV, grade optional of MIL-L-10547. Each box shall be closed and reinforced, and skidded if the shipping weight exceeds 200 pounds, in accordance with the appendix of PPP-B-601 or PPP-B-621, as applicable.

4.4.3 Palletization. When specified (see 5.1), shipping containers and unit loads shall be palletized in accordance with MIL-STD-147.

4.5 Marking (commercial and export). Marking of unit packs, and shipping containers shall be in accordance with MIL-STD-129, or ASTM D 3951, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

5. NOTES

5.1 Ordering data:

a. Title, number, and date of this document.
b. Information required in paragraph 5.1 through 5.1.6 of ASTM F 919-85.
c. Government approved manual number (see 2.1 i).
d. Selection of applicable packaging and packing required (see 4.1.1).

5.2 Source for non-government association documents.

ASTM D 3951 - Standard Practice for Commercial Packaging; and
ASTM F 919-85 - Slicing Machines, Food, Electric, are available from:

The American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103

5.3 Government unique requirements. Whenever "(Government unique requirements)" is included in the title of a paragraph under "salient characteristics" it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

MILITARY INTERESTS:

Custodians

Army - GL
Navy - SA
Air Force - 99

Review Activities

Army - MD,TS
Navy - MS
Air Force - 84
DLA - GS

User Activity

Navy - CG

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS
HEW - FDA
VA - OSS

PREPARING ACTIVITY:

Army - GL

Project No. 7320-0844

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:38Z
Check the source to verify that this is the currentversion before use.