A-A-50089
DEC 1 8 1986

COMMERCIAL ITEM DESCRIPTION

SHELVING, COMMISSARY, GONDOLA TYPE

The General Services Administration has authorized the use of the commercial item description.

1. Classification. The shelving shall be of the following types and sizes as specified (see 5.2):

Type I - Island shelving

Size 1 - 6 feet high by 4 feet wide
Size 2 - 5 feet high by 4 feet wide
Size 3 - 6 feet high by 3 feet wide
Size 4 - 6 feet high by 4 feet wide

Type II - Wall shelving

Type III - Bakery shelving

2. Salient characteristics.

2.1 Type I and type II shelving. Type I shelving shall be of the island type with a base shelf or deck and have 3 adjustable cantilever shelves on each side of the back panel. Type II shelving shall be similar in construction, except that the deck and the adjustable cantilever shelves are required on only one side of the back panel. Commissary shelving shall be of steel frame type construction, consisting of: shelving base, uprights, brackets and cantilever shelves. Shelving shall be easily erected without skilled help or special tools. The front of the shelves shall be designed to accommodate 1.235-inch tag moldings. Decks shall have tag moldings with a 55° upward tilt. Back panels shall be constructed of 3/16-inch to 1/4-inch hardboard. Shelves, uprights, cantilever support brackets, and other related components, shall be designed for maximum strength and rigidity, and reinforced where necessary to comply with the load requirements specified in 2.4. The frame shall be equipped with 1-inch minimum adjustable leveling devices. Shelves shall be capable of being adjusted the entire height of the frame in 1-inch increments.

FSC 7125

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:38Z
Check the source to verify that this is the current version before use.

2.1.1 End panels with shelves. When specified, removable end panels with shelves, suitable for mass display of merchandise, shall be furnished. These end panels shall generally conform to the height, width and depth configuration of the island base shelf. The end panel shall have three adjustable cantilever shelves, as well as a base shelf. The end panel shall be constructed of 3/16-inch to 1/4-inch hardboard for pegged merchandise.

TABLE I. Shelving dimensions (inches)

	Overall width	Overall depth	Overall height	Base shelf depth	Upper shelves depth
Type I					
Size 1	48	59-61	71-73	27-29	24-25
Size 2	48	59-61	60-63	27-29	24-25
Size 3	36	59-61	71-73	27-29	24-25
Size 4	48	52-56	71-73	24-26	21-23
Type II	48	29-31	71-73	27-29	24-25

2.2 Type III shelving. The bakery shelving base, uprights, brackets, and shelves shall be all steel frame type construction, knockdown type, easily erected without skilled help. Bakery shelving units shall be equipped with illuminated canopy, mirrors, reversible wire bakery shelves, steel base shelf, end caps, and base flanges. Back panels shall be constructed of minimum 3/16-inch perforated hardboard or 5/8-inch laminated particle board. The frame shall be equipped with 1-inch minimum adjustable leveling devices. Each bakery display shelving shall be 12 feet long, consisting of three 4-foot sections. Each 4-foot section shall be equipped with four reversible wire bakery shelves. Reversible wire shelves shall be chrome or brass-plated. The wire shelves shall be 21 to 24 inches deep, with a downward tilting capability toward the front of 12 to 17 degrees. Wire shelves shall have a 2-1/2 to 2-7/8-inch high lip in front of the shelving. Overall height of shelving shall be 88 to 90 inches.

2.2.1 End panel and canopy. The end panel and canopy shall be constructed of solid wood, particleboard, sheet steel, or aluminum. The canopy shall be illuminated by fluorescent lights and shall have a fascia with end panels and a slanted mirror. Unless otherwise specified, lights shall be designed for operation on 120 volt, 60 hertz, 1-phase electric power supply.

2.2.2 Shelving base and kickplates. The shelving base shall be 6 to 10 inches from the floor and reinforced to withstand the shelving load requirements specified in 2.4. Kickplates shall be capable of being easily removed without the use of special tools.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:38Z
Check the source to verify that this is the current version before use.

2.3 Shelving load requirements.

2.3.1 Shelves. Shelves shall be capable of supporting the following uniformly distributed loads, with permanent deformation not to exceed 1/16-inch, when tested as specified in 3.2.1.

Types I and II	4-foot section	3-foot section
Shelves	640 lbs	480 lbs
Deck	800 lbs	800 lbs
Type III		
Shelves	100 lbs	---
Deck	800 lbs	---

2.3.2 Uprights. Uprights for wall shelving shall be capable of supporting uniformly distributed loads of 320 pounds per shelf, and 800 pounds per deck, with permanent deformation of the upright not to exceed 1/16-inch when tested as specified in 3.2.2. Uprights for island shelving shall be capable of supporting the above loads applied to one side of the back panel, creating an unbalanced condition. Permanent deformation of the uprights used in island shelving shall not exceed 1/16-inch when tested as specified in 3.2.2.

2.4 Data name plate (Government unique requirement see 5.4).

The shelving shall be furnished with a data name plate in accordance with the applicable requirements of MIL-STD-130 except the requirement for; (a) Methods of applying, (b) Identification tags, (c) Information not required and (d) Optional marking information shall not apply. The data name plate shall be made of minimum 20 gauge corrosion-resisting metal and attached to the shelving by rivets, screws, or welding in such a manner as to meet the applicable National Sanitation Foundation sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved, or applied by photosensitive means:

National Stock Number
Procurement Instrument Identification Number
Specification Data
Manufacturer's Name, Address and Telephone Number
Supplier's Name, Address and Telephone Number (List only if different from Manufacturer)
Manufacturer's Model Number
Government Approved Manual Number (see 5.2)

Each plate shall be placed so that it is readily visible and so as to not adversely affect the life and utility of the shelving.

2.5 Finish. Unless otherwise specified, shelving components that are normally painted shall be finished with an enamel conforming to color number 13613 of FED-STD-595.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

2.6 Workmanship. All workmanship shall conform to good commercial practice. Shelving shall be free of burrs, snags and rough or sharp edges.

3. Quality assurance.

3.1 Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, conforms to the producer's own drawings, specifications, standards, and quality assurance practices, complies with the referenced industry standards, and is the same as the product sold in the commercial marketplace, except for those additional requirements/ characteristics specified herein. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under provisions of the contract.

3.2 End item testing. The shelf load test of 3.2.1 and upright load test of 3.2.2 shall be performed on the shelves and uprights, respectively, to determine conformance to the requirements of 2.3.1 and 2.3.2. The lot size shall be the number of shelving units presented for acceptance at one time. The sample unit shall be one complete 3 or 4 foot wide section (as applicable) of shelving and the sample size shall be determined by the application of inspection level S-1 of MIL-STD-105 to the lot size. The failure of any sample unit to pass the tests specified shall be cause for rejection of the lot.

3.2.1 Shelf load test. A representative shelf shall be installed on the uprights. The uprights shall be restrained in such a manner that, when the shelf is uniformly loaded as specified herein,only the structural deflection of the shelf itself affects the measurement. The shelf shall be preloaded with a 100-pound load uniformly distributed to remove mechanical clearances prior to application of the total test load. A measuring device shall be zeroed in at the 100-pound load. Uniformly distributed test loads shall be applied for 1 hour and then removed. Permanent shelf deformation shall be measured at the 100-pound level after removal of the test load. Any permanent deflection in excess of 1/16-inch shall constitute failure of the test.

3.2.2 Upright load test. Shelves and decks shall be installed as required on the wall or island shelving using three uprights. Permanent deformation shall be measured at the top of the middle upright. Each shelf and deck shall be preloaded with a 100-pound load uniformly distributed to remove mechanical clearances prior to application of the total test load. A measuring device shall be zeroed in at the 100-pound load. Wall shelving shall then be uniformly loaded to a total of 320 pounds per shelf and deck. Island shelving shall be similarly loaded, but only on one side and both decks. The test load shall be applied for 1 hour and then removed. Permanent deformation of the top of the upright shall be measured at the 100-pound level after removal of the test load. Any deformation in excess of 1/16-inch shall constitute failure of the test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

4. PACKAGING.

4.1 Packaging and packing. Packaging and packing shall be commercial or export as specified (see 5.1).

4.2 Commercial packaging and packing. Each type of shelving shall be cleaned, preserved, packaged, packed, and unitized in accordance with ASTM D 3951.

4.3 Export packaging and packing.

4.3.1 Export packaging. Shelving shall be disassembled to the extent determined by the contractor to protect item during shipment and storage to reduce cubage. Small parts shall be packaged in a weather-resistant fiberboard box constructed and closed in accordance with Method IV as specified in PPP-B-636. Components shall be cleaned, preserved, and cushioned to protect against damage during shipment and storage.

4.3.2 Export packing. Shelving components and packaged parts shall be packed in a wood-cleated plywood box conforming to overseas type, style A or J, grade B, type 2 load of PPP-B-601, or nailed wood box conforming to class 2, style 2 or 4, grade B, type 2 load of PPP-B-621. Contents of the box shall be cushioned, blocked, and braced, and waterproofed in accordance with MIL-STD-1188. The box shall be closed and strapped in accordance with the appendix of PPP-B-601 or PPP-B-621, as applicable.

4.3.3 Palletization. When specified, shipping containers shall be palletized in accordance with MIL-STD-147 (see 5.2).

4.4 Marking (commercial and export). Marking of unit packs, shipping containers, and palletized unit loads shall be in accordance with MIL-STD-129, or ASTM D 3951, as applicable.

5. NOTES

5.1 Intended use. The shelving is intended to be used in Military commissaries for the purpose of displaying goods and supplies.

5.2 Ordering data.

a. Title, number, and date of this document.
b. Type and size of shelving required (see 1.).
c. Government approved manual number to be included on data name plate (see 2.4).
d. Selection of applicable packaging and packing required (see 4.1).
e. When palletization of shipping containers is required (see 4.3.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

5.3 Sources of documents.

5.3.1 Sources for nongovernment association documents.

ASTM D 3951 - Standard Practice for Commercial Packaging, available from:

The American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103.

5.3.2 Sources of governmental documents.

Military documents are available from:

Naval Publications and Forms Center
5801 Tabor Avenue
Philadelphia, PA 19120

5.4 Government unique requirements. Whenever "(Government unique requirements)" is included in the title of a paragraph under "salient characteristics" it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

MILITARY INTERESTS:

Custodians

Army - GL
Air Force - 99

Review Activities

Army - MD, TS
Air Force - 84

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project No. 7125-0114

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:38Z
Check the source to verify that this is the current version before use.